


New York State Department of Environmental Conservation
Division of Mineral Resources
Bureau of Oil & Gas Regulations, 3rd Floor
625 Broadway, Albany, New York, 12233-6500
Phone: (518) 402-8056 • Fax: (518) 402-8060
Website: www.dec.ny.gov



Alexander B. Grannis
Commissioner

August 12, 2010

Kevin M. Bernstein, Esq.
Bond, Schoeneck & King, PLLC
One Lincoln Center
Syracuse, NY 13202

**Re: SECOND NOTICE OF INCOMPLETE APPLICATION &
STATUS OF MATERIALS
ECL Article 23 Underground Storage Permit
Finger Lakes LPG Storage, LLC, Schuyler County**

Dear Mr. Bernstein:

This is sent to provide you and your client with a Second Notice of Incomplete Application ("NOIA") for Finger Lakes LPG Storage, LLC's ("Finger Lakes") subject application received by the Department on October 13, 2009, and Finger Lakes' May 14, 2010 submittals consisting of 1) Revised Reservoir Suitability Report and 2) Response to January 11, 2010 NOIA. In addition, the current status of each primary element necessary to complete the application is noted on the enclosure. It is acknowledged that Finger Lakes' May 14, 2010 submissions withdraw originally proposed storage Gallery 2 (Well Nos. 30, 31 & 45) from consideration. Instead, a new Gallery 2 (Well No. 58) is proposed for liquefied petroleum gas ("LPG") storage along with originally proposed storage Gallery 1 (Well Nos. 33, 34, 43, 44).

This Second NOIA does not address any other Department applications, permits and/or approvals that may be required in conjunction with the subject permit. Additional comments and/or questions, if any, on other required Department approvals and/or permits will be addressed separately by the Region 8 Avon Division of Environmental Permits office.

The following response is organized in the same fashion as the January 11, 2010 NOIA and handout detailing application and permitting requirements that was provided to Finger Lakes at the February 19, 2009 pre-application meeting. The enclosed comments and questions in *italics* must be addressed to continue processing Finger Lakes' application for an Underground Storage Permit for its proposed LPG facility. Prior comments and questions from the Department are included for background purposes. However, Finger Lake's May 14, 2010 responses to these comments and questions are not included but are instead referenced in the enclosure.

Please contact me if you have any comments or questions concerning this NOIA:

Sincerely,

A handwritten signature in black ink, appearing to read "Peter S. Briggs". The signature is written in a cursive style with a long horizontal flourish extending to the right.

Peter S. Briggs
Chief, Permits Section

Enclosure

c: W. Moler (Finger Lakes)
J. Maglienti, Esq.
L. Collart
B. Glynn
R. McDonough
N. Rice
W. Kelly

NYSDEC Division of Mineral Resources
SECOND NOTICE OF INCOMPLETE APPLICATION & STATUS OF MATERIALS
ECL Article 23 Underground Storage Permit
Finger Lakes LPG Storage, LLC, Schuyler County

1. **Organizational Report** - Finger Lakes' September 30, 2009 Organizational Report satisfies the Department's requirements at this time. An updated Organizational Report must be filed with the Department if a change occurs in any of the information provided on the report including a change in corporate structure.

Satisfactorily addressed by Finger Lakes' prior submission.

2. **Financial Security** - Financial security is required prior to issuance of any well drilling permit or approval of any well transfer request, and will be reviewed at the time such applications and/or requests are received by the Department.

Satisfactorily addressed by Finger Lakes' prior submission.

3. **Transfer of Well Plugging Responsibilities** - Approval of such transfer requires properly completed request for transfer forms, followed by compliance inspection of the wells by Regional staff and verification of financial security. All unplugged wells in Finger Lakes' Galleries 1 and 2 currently registered with other well owners [i.e., US Salt LLC and Seneca Lake Storage, Inc. ("SLSP")] must be transferred prior to Finger Lakes performing any proposed well work that requires a permit in Finger Lakes' name.

Satisfactorily addressed. A Request For Well Transfer was received from Finger Lakes in its May 14, 2010 submittal to address wells under consideration (i.e. Finger Lakes Gallery 1 and new Gallery 2), and the transfer was subsequently approved by the Department.

4. **Full Environmental Assessment Form** - In contrast to the individual Environmental Assessment Form required with each drilling permit application, the Full Environmental Assessment Form ("EAF") is required to address the whole storage project, including any compressor site, any proposed lateral pipelines to power plants or transmission lines, and any proposed discharges. The Full EAF will be used to identify:

- a. any need for additional Department permits including those that address brine handling and discharge/disposal.

Finger Lakes provided a Full EAF with its storage application received on October 13, 2009. The following corrections must be made, and a revised form submitted. However, because this NOIA is limited to Division of Mineral Resources' issues, Finger Lakes should coordinate its revisions and submission of the revised EAF with any comments received from the Region 8 Avon Division of Environmental Permits office, and submit only one revised form to the Department. Page 1 - The "Name of Lead Agency" must reflect the Commissioner's Lead Agency Decision when reached.

Page 2 - The address of the applicant must be corrected to reflect Finger Lakes' Organizational Report provided with the storage application.

Page 5 - The total amount of salt that will be removed from the site due to operational solution mining over the projected life of the project must be provided including a notation of the life of the project in years.

Page 8 - Additional approvals in the form of well transfers, well drilling permits and well plugging permits associated with the project will be required by the NYSDEC.

Page 10 – The form appears to be signed by Michael Armstrong, Director Engineering. Mr. Armstrong is not listed in Box 7 of Finger Lakes' Organizational Report provided with the storage application, and therefore is not authorized to sign submittals to the Department. Please have a person listed in Box 7 or Kevin Bernstein (project-specific authorization granted by Finger Lakes on October 20, 2009) sign the revised EAF.

Satisfactorily addressed for Underground Storage Permit application review purposes. All items noted above addressed and included in the revised EAF (Exhibit B of Finger Lakes' May 14, 2010 Response to NOLA). As acknowledged by Finger Lakes, well conversion permits from the Region 8 Avon Mineral Resources office are required in conjunction with the tentative storage permit.

5. **Map(s)** - Please prepare a map(s) at a minimum scale of 1" = 400' and include the following items. Submit as many separate maps as necessary to legibly depict the requested information.

Generally speaking, the facility map (4/14/09, last updated 7/9/09) provided with the Finger Lakes storage application is deficient in many of the same ways as were maps provided by Inergy Midstream, LLC ("Inergy") for its other LPG storage application at Savona. The deficiencies for the Savona application were previously communicated by the Department to Inergy although they apparently were not considered when preparing the Finger Lakes application map. Most remarkably, the proposed ultimate cavern outlines and remaining pillar thicknesses at the end of the life of the project are absent from Finger Lakes' map. Specific map deficiencies are noted below and must be corrected, and a revised map or maps submitted.

- a. Location, total depth, well type, well status and API well identification number of all wells listed in the Well Status and Condition Report described in item 9 below. Finger Lakes must supplement its map to include the requested information for all wells listed in the Well Status and Condition Report as described and required in below Item 9.

See below Item 5c italics for remaining issues.

- b. Location of all existing and proposed wells within and immediately adjacent to the storage area. Finger Lakes must supplement its map to include all wells listed in the Well Status and Condition Report as described and required in Item 9, including showing existing and plugged wells and gallery outlines in the south field located south of proposed LPG Gallery 2. The map must also show the locations of all proposed wells in Galleries 1 and 2.

See below Item 5c italics for remaining issues.

- c. Plan view of the proposed reservoir boundary (i.e., existing and proposed ultimate cavern outlines which take into account directional surveys for wells). Clearly label each cavern to denote its current status, current use and proposed use under the requested permit. Include distance, in feet, between proposed ultimate cavern outlines and/or other existing caverns.

Finger Lakes must supplement its map to include all requested information as described above. Wells in communication must be shown as such on the plan view. Presently, Finger Lakes' map provided with its storage application shows individual caverns in Gallery 1. Interconnections must be shown and a single gallery outline provided for both existing and proposed ultimate conditions for Galleries 1 and 2. The map must include a notation of the method by which the existing outlines were determined (e.g., sonar

survey, production records). Each gallery's length and span at proposed ultimate capacity must be shown on the map. The distance, in feet, between proposed ultimate cavern outlines and other caverns/galleries in the field must be shown (i.e., remaining pillar thicknesses). These determinations must take into account any additional solution mining that may occur as a result of brine production at the US Salt LLC operation. For proposed storage Galleries 1 and 2, all current and past sonar surveys (outermost outline) must be included on the plan view.

Finger Lakes may submit as many maps as needed to clearly display the requested information, however; all sonar survey outlines should be shown and appropriately labeled on a single map.

See italics on next page for remaining issues.

For the portion of the cavern outline currently shown on the map due west of Well No. 34, it is the Department's understanding that this linear feature would be re-evaluated prior to submission of this storage application because the sonar for Well No. 34 does not show such a feature. Rather, the linear feature shown is from Well No. 44's sonar. This issue with the map for the facility was discussed during our field visit in May 2009. Please explain why the linear feature was retained or correct this portion of the cavern outline.

Above issue satisfactorily addressed by Finger Lakes' May 14, 2010 Response to NOIA (Page 4 and Exhibit D).

In addition, for wells with directional surveys, wellhead and production casing shoe locations must be clarified on Finger Lakes' map or maps. In addition to any symbol used to denote casing shoe locations, wellhead symbols (e.g., 33, 43, 34, 44, new wells) must also be included in a legend.

The relative closeness of the gallery (Well Nos. 18, 5552, 57, aka International Gallery 10) immediately to the north of proposed storage Gallery 1 is of potential concern to the Department. For each of the three wells identified in the gallery, provide a well diagram showing the depth of top of salt, existing casing, mechanical plugs and cement. Please provide any additional information Finger Lakes may have to show that no interconnection between the noted galleries currently exists or will be formed during operation of the proposed project or if such a connection is made, that International Gallery 10 would adequately contain LPG stored in Gallery 1. Inadvertent communication between Finger Lakes Gallery 1 and International Gallery 10 could provide a possible route of escape for stored product at some future date after Gallery 1 is activated. In addition, do directional surveys exist for the identified wells (Well Nos. 18, 5552, 57)?

Is any pressure testing of International Gallery 10 contemplated? The Department may require re-entry and hydrostatic pressure testing of International Gallery 10 (along with full complement of directional survey, sonar survey, nitrogen/brine interface MIT on re-entered well) upon receipt and evaluation of Finger Lakes' response to this NOIA.

See italics on next page for remaining issues.

The following issues remain and must be addressed concerning Finger Lakes' Exhibit 2 "Finger Lakes LPG Storage Gallery Map" and related topics:

1. Please label "Finger Lakes Gallery 1" and "Finger Lakes Gallery 2" on the gallery map.
2. Please add and show the cavern outline from the most recent sonar (i.e., October 2009) of Well No. 58 (Gallery 2) on the gallery map.
3. If the purple outlines (Max Gallery Outline) of the caverns forming Gallery 1 also represent the current outlines of the gallery, they should be identified on the map as such on the gallery map.
4. The data table on the left side of the gallery map should be updated to reflect current information for Well Nos. 34 & 58.
5. The "Brinefield Color Code" on the gallery map shows a "red" cross for the "Top of Cavern" but this symbol is not used on the map, please correct color code or the map itself.
6. For all wells on the gallery map, please include a legend which explains the different symbols used to show well status.
7. "Well FL1" should be identified as a proposed well on the gallery map.
8. Explain why two different symbols are used on the gallery map to show the pressure connections between the caverns in Gallery 1 (i.e., between Well Nos. 33 & 43 and Well Nos. 43 & 34/44).
- 9.

a. Describe how the outline for Gallery 10 was determined and provide all supporting information. Provide a copy of all sonar surveys and production records for all wells in Gallery 10 as the notation on the map indicates the gallery outline was determined by "Sonar & Production Records." Additionally, Exhibit C of the May 14, 2010 Response to NOIA should be corrected to include the referenced sonar(s) unless none actually exist. If none exist, correct notation on map.

b.

c. Finger Lakes indicates that it could not obtain a cavern sonar survey on Well No. 52 because the casing extending through the cavern is surrounded by cement. Was any consideration given to cutting the casing and attempting to re-sonar? If "no," why not? If dropping the casing in Well No. 52 and re-sonaring is not doable, has Finger Lakes considered re-entering another well in the gallery (i.e., 18 or 57) to perform a sonar survey? Based on information supplied thus far by Finger Lakes, it appears there is still some uncertainty with regard to the actual pillar width between proposed storage Gallery 1 and Gallery 10. The Department is aware that Finger Lakes' parent Inergy Midstream, LLC applied for and received well re-entry permits for Well Nos. 18 & 57 in January 2010 but let the well permits recently expire before

- commencing work. What was the reasoning for obtaining the permits but not using them?
- d. The Department understands that Finger Lakes re-entered Well No. 52 to evaluate the well and cavern, and ran a directional survey, bond log, casing inspection log and a sonar survey. Because of the relative closeness of proposed storage Gallery 1 and Gallery 10, and perceived uncertainty of the actual pillar width between Galleries 1 & 10 (see Exhibit 20, Item 6 of "Section 6. Conclusions and Recommendations"), provided Well No. 52 is properly constructed, has Finger Lakes considered running a long-term brine pressure test on Gallery 10 and MIT on the Well No. 52, and then converting Well No. 52 for monitoring use of Gallery 1 storage operations? Ensuring LPG containment in Gallery 10, if inadvertently connected to Gallery 1, should be considered and pros/cons of such evaluated by Finger Lakes.
- e.

- d. All faults or other structural or stratigraphic features depicted on the cross-sections described in item 6a below. See Department responses to below Items 6a and 6b.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Response to NOIA (Page 4) and May 14, 2010 Reservoir Suitability Report (Pages 9-11 and Exhibits 15, 16 & 17).

- e. The proposed location of compressors and other surface equipment, structures, tanks, impoundments (e.g., brine ponds), discharge points, flare stacks and pipelines associated with the proposed storage operations. Satisfactorily addressed by Exhibit 1 and Exhibit 2 (Maps 1 & 2) of Finger Lakes' storage application.

Satisfactorily addressed by Finger Lake's revised submissions (Exhibits 1 & 2 of May 14, 2010 Reservoir Suitability Report).

- f. Notation of the applicant's surface and mineral rights within the vicinity of the proposed storage area. Such notation must be included with the applicant's storage rights affidavit required in below Item 10.

Satisfactorily addressed by the revised Storage Rights Affidavit and attachments (Exhibit E of Finger Lakes' May 14, 2010 Response to NOIA).

- g. Topographic and cultural features such as roads, railroads, oil or gas pipelines, utility rights-of-way, surface waters, springs, public and private water supplies, buildings or

dwellings, agricultural districts, significant landmarks and any other public area which may be used as a place of occupancy, resort, assembly, lodging, manufacture, storage or traffic. Satisfactorily addressed by Exhibit 1 and Exhibit 2 (Maps 1 & 2) of Finger Lakes' storage application.

Satisfactorily addressed by Finger Lake's revised submissions (Exhibits 1 & 2 of May 14, 2010 Reservoir Suitability Report).

6. **Reservoir Suitability Report** - This report must document suitability of the reservoir for storage. The report must include a cavern development plan & geomechanical (including finite element analysis) study including and analyzing, but not necessarily limited to, items listed below. Note that the geomechanical study must use supportable baseline cavern information and a justifiable projection for future cavern growth—existing cavern size(s) and shape(s) must be based on reliable information such as historical cavern development records and recent sonar surveys.

- a. **Geologic cross-sections of the area shown on the map listed in item 5 showing lithologies, storage wells (including casing strings and setting depths) and overlying and underlying formations, and vertical profiles of the existing and ultimate caverns including all prior sonar surveys. These cross-sections must also depict any faults or other structural or stratigraphic features that affect either continuity and extent of the formations shown or effectiveness of containment of gas in the storage reservoir.**

- b. Discussion of the information illustrated on the cross-sections described above. Any zones or planes of weakness referenced in other published reports (e.g., Jacoby) potentially affecting the suitability of the reservoir for storage must be documented and explained in the Reservoir Suitability Report.

Discussion of the project's regional and local geology and structural features is included on pages 1, 2, 3, 6, 7, 8 and pages 11 through 15 of Exhibit 10. On page 3, Finger Lakes states "The overlying sediments are characterized by broad, gentle east-west synclines and anticlines with axes generally paralleling the sharp folds of the underlying evaporates." Finger Lakes' discussion on page 8 of its application includes statements from Jacoby and Dellwig that "The structure contour map on top of the salt gives no indication of the faults breaking up into the overlying sediments" and that the "zones or planes of weakness" referenced in the same paper are confined to the salt section. For proposed storage Gallery 1, while general statements are made regarding the continuity of the Camillus Shale, it is unclear from the discussion in the application if Finger Lakes has performed its own independent analysis and evaluated each well's geophysical logs

(along a north-south line running through Gallery 1 from Well No. 18 or 57 to Well No. 31 and an applicant-selected representative east-west line through Gallery 1) to determine if repeat or missing sections occur as an indication of faulting in the caprock overlying the Syracuse salts. Please provide analysis if previously prepared. If such an analysis has not been performed, please do so and provide results. If the analysis shows that faults are present, they must be shown on the cross-sections. The objective of this requirement is to demonstrate the lack of potential pathways for the escape of stored product.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Response to NOIA (Pages 8-9) and May 14, 2010 Reservoir Suitability Report (Pages 2-3, 9-11 and Exhibits 15 & 16). Exhibit 15 "Gross Isopach Camillus Shale" and Exhibit 16 "Structure Base of Camillus Shale" of the Reservoir Suitability Report along with the discussion of geology and features provide documentation and support of adequate geologic containment for Finger Lakes' proposed use of Galleries 1 & 2.

- c. Discussion of any core test results including caprock and salt properties. Addressed by Item 7.3 and Exhibits 8 & 9 of Finger Lakes' storage application. Please explain how the referenced cores correlate to Finger Lakes' proposed Galleries 1 and 2. The caprock and salt properties discussed in Exhibits 8 & 9 should be used in the project-specific geomechanical analysis requested in Item 6.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Response to NOIA (Pages 9-10) and May 14, 2010 Reservoir Suitability Report (Pages 11-12 and Exhibits 18 & 19).

- d. Description of the material to be stored and analysis of the physical and operational parameters required for safe containment of the stored material and any displacement fluid for the life of the project. Satisfactorily addressed with respect to stored material. Finger Lakes states that propane and butane will be stored, and included MSDS for both as Exhibits 12 and 13 respectively. Finger Lakes also included a MSDS for Ethyl Mercaptan which will serve as an odorant when product is loaded into trucks. It is understood that the Ethyl Mercaptan is stored at the truck loading dock and is introduced into product only when trucks or containers are filled for public distribution. Operational parameters are discussed below in 6e.

Satisfactorily addressed with respect to stored material by Finger Lake's May 14, 2010 Reservoir Suitability Report (Exhibits 23, 24 & 25).

- e. Existing and proposed total storage capacity (i.e., water-filled capacity) which includes rubble pile capacity, if any, and minimum and maximum operating storage pressures. The underground storage permit for the facility will specify total capacity; any future increase in permitted total capacity, however caused, will require an underground storage modification permit in accordance with ECL §23-1301(5)(b).

For each gallery, please restate or state, in more precise terms a) existing total storage capacity (i.e., water-filled capacity) which includes rubble pile capacity, if any, b) proposed ultimate total storage capacity (i.e., water-filled capacity) which includes rubble pile capacity, if any, c) gallery length and span at proposed ultimate capacity, and d) operating storage pressures as follows for each proposed storage well: maximum storage pressure at the wellhead (psig), and minimum and maximum storage pressure gradients measured at the casing shoe (psi/ft) with corresponding casing shoe depth. For each gallery's stated existing and proposed ultimate capacity, explain how determined. Submission of a "Capacity Matrix" as was provided with the Savona LPG application would be one means of providing some of the above requested information.

The following issues remain and must be addressed concerning Finger Lakes' Cavern Development Plan and Proposed Operations:

- 1. Finger Lakes must elaborate and explain its cavern development plan and proposed operations in more precise terms, including the following.*
 - a. Finger Lakes must explain and identify what areas of the proposed storage galleries will remain as currently constructed and what areas of the galleries will be subject to operational solutioning (i.e., less than 2% annual growth) during the proposed LPG storage operations. It is understood that no active mining will take place once the storage caverns are put into service.*
 - b. Finger Lakes must explain how it intends to prevent operational solutioning certain areas of the storage galleries. An explanation by Finger Lakes that certain wells will be used only for monitoring is not sufficient as it does not explain why cavern space being used for LPG storage does not grow laterally due to operational solutioning. It is unclear from Finger Lakes application how lateral growth of the galleries will be prevented. Finger Lakes must describe any controls, including operational, that will be used to prevent gallery growth including lateral growth.*
 - c. Finger Lakes must describe any controls, including operational, it will use to protect the cavern roofs and limit operational solutioning of the cavern roofs.*
 - d. The maximum requested product fill level must be depicted on a plan view and vertical section of the storage galleries (i.e., show where product will be stored at maximum fill). The setting depth of the brine strings must also be shown on the vertical section. If the setting depth of any brine string will be used to control cavern growth, it should be stated and explained. The Department must understand Finger Lakes cavern development and operations plan.*

2.

3.

4.

5.

6. *For each well including proposed Well FL1, provide maximum storage pressure at the wellhead (psig).*

- f. Past and current sonar reports and surveys, and schedule for future sonar surveys. Sonar schedules must take into account the cavern development plan. Any other materials including other types of surveys and/or determinations of current cavern size and shape including records of prior cavern development. Directional surveys for wells for determining spatial relationship of caverns.

Recently run sonars and directional surveys have been provided by Finger Lakes (or its parent Inergy Midstream, LLC). The Department also has some past sonar surveys for some of the subject wells in its files. Finger Lakes must provide a listing of all available sonars so that the Department can verify it already has a copy.

Finger Lakes states that Gallery 1 sonar surveying is complete at this time and that future sonars will be conducted at least every ten years. With regard to Gallery 2, Finger Lakes states that "When the wells for gallery 2 are redrilled or new wells drilled, new sonars will be performed (and periodically thereafter every 10 years). Directional surveys will also be performed when the new wells are drilled." It is the Department's understanding that no wells in Gallery 2 will be redrilled (see "Finger Lakes Gallery 2," page 12 of application). Please clarify.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Response to NOIA (Page 12 & Exhibit C) and May 14, 2010 Reservoir Suitability Report (Pages 14-15).

- g. Discussion of historical earthquake activity, if any, within a one-half mile radius of the project area. Satisfactorily addressed by Item 13 and Exhibit 11 of Finger Lakes' storage application.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Reservoir Suitability Report (Page 17 and Exhibit 22).

- h. Proposed safety and emergency shut-down systems for the storage facility. Upon review of items a through h, the Department may require additional geologic and/or engineering analysis to further support the applicant's proposed operations.

If and when the storage permit is issued, prior to any injection of storage gas, Finger Lakes must provide two copies of its Emergency Response Manual to the Director of the Bureau of Oil & Gas Regulation in the Department's Albany office.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Response to NOIA (Page 12)

- 7. **Subsidence monitoring plan.** The subsidence monitoring plan must take into account the cavern development plan. Finger Lakes' proposal to continue US Salt's subsidence monitoring schedule of every 5 years for the proposed LPG storage facility is not acceptable because US Salt's five-year program is designed for solution salt mining and not storage of hydrocarbons. Early detection is inherently more critical at hydrocarbon storage facilities. Consistent with existing subsidence monitoring programs at the Savona and Harford Mills LPG storage facilities, if and when the storage permit is issued, subsidence monitoring will be required at least every 2 years at all injection, withdrawal and plugged wells in each gallery. In addition to the storage and plugged wells in Galleries 1 and 2, please identify additional monuments or wells, if any, that will be included in Finger Lakes bi-annual subsidence surveying program when implemented.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Response to NOIA (Pages 12-13) and May 14, 2010 Reservoir Suitability Report (Page 17).

- 8. **Mechanical integrity testing ("MIT") plan.** Proposed MIT pressures must be accounted for in the geomechanical analysis. On page 13 of its application Finger Lakes states that it will conduct a nitrogen/brine interface MIT at all storage wells prior to first injection of product and thereafter at least every five years. Please state proposed MIT test pressure for each well (Galleries 1 and 2) in psi/ft. Test pressures must be taken into account in the required geomechanical study. In addition, if and when the storage permit is issued and prior to injection of product, Finger Lakes will be required to submit for Department review and approval a summary of test data and a narrative report detailing the results of all MITs.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Response to NOIA (Pages 13-14) and May 14, 2010 Reservoir Suitability Report (Pages 18-19 and Exhibit 26).

- 9. **Well Status and Condition Report** - The purpose of this report is to show that prior to commencement of storage operations, the condition of all wells located within and immediately adjacent to the storage area is such that storage gas containment is not compromised. Please include the following items.
 - a. A well summary covering all plugged and unplugged wells which documents the well use histories and current status or downhole condition of each well.

See below Item 9b italics for remaining issues.

- b. A proposed remediation plan for wells described in item a above which are not adequately completed or plugged to ensure storage gas containment. With respect to Items a and b above, Finger Lakes provided information on the wells in proposed storage Galleries 1 and 2 as Tab D of its storage application, and at other locations within the application. Well construction and well history information is also included on page 4 of the storage application. Please provide a well diagram showing existing casing and cement for each plugged and unplugged well in Galleries 1 and 2. The diagrams for existing and proposed plugged wells must show the location of existing or proposed mechanical and/or cement plugs in the wellbore. Information on the historical use of Gallery 2 for LPG storage is provided on page 4 of the storage application and in Exhibit 10. Details and results of the Vertilog well casing evaluation logs recently run on the wells during re-entry are provided on page 5 of the storage application. Well Nos. 33 and 44 were recently relined to ensure integrity of the storage system. Provide an explanation as to why well No. 43 does not require relining.

For proposed storage Gallery 2, Finger Lakes' intended use of Well No. 30 is unclear. Page 2 of Tab D states "will be converted to LPG storage" while page 12 of the application states "Finger Lakes plans to replug and abandon well 30..." Please clarify.

Finger Lakes did not provide any information on wells "immediately adjacent to the storage area" as requested in Item 9. For the purpose of this requirement, immediately adjacent is defined as all wells in a cavern or gallery within 500 feet of the ultimate cavern outlines for proposed storage Galleries 1 and 2. For all identified immediately adjacent wells, provide well name, number, API No., current status, year plugged, if applicable, and well owner's name. For clarification sake, a tabulation of all wells (Galleries 1 and 2, and immediately adjacent) documenting each well's current status, proposed status and remedial or plugging work already performed or required is requested.

The following issues remain and must be addressed concerning Finger Lakes' Well Status and Condition Report:

- 1. Page 4 of Finger Lakes' May 14, 2010 Reservoir Suitability Report states that "Well 33 pressure was not affected when pressure was bled to 0 psig on wells 34, 43, 44." If communication exists between the wells as represented by Finger Lakes' proposal to operate Gallery 1 (Well Nos. 33, 34, 43, 44 and new well FL1) as a single storage reservoir, why didn't Well No. 33 respond when pressure was bled to zero on the other wells in the gallery?*
- 2. We acknowledge Finger Lakes provided copies of the "Micro Vertilog" and "Gamma Ray Segmented Bond Log" for Well Nos. 52 & 58, and references to the logging results are found in the May 14, 2010 application. Nevertheless, for each evaluation log run (except sonar surveys) and as a supplement to Exhibits 9 & 10 of Finger Lakes' May 14, 2010 Reservoir Suitability Report, please consolidate logging results and provide a narrative analysis explaining the results of each log on a well-by-well basis with particular attention to cement bonding across the Camillus Shale. For each well, please include the corresponding depths of the Camillus Shale in the narrative. Additionally, provide copies of evaluation logs run on Well Nos. 33, 34, 43 & 44.*
- 3. We understand Finger Lakes plans to P&A Well No. 34. We also are aware that Finger Lakes recently installed a new fully cemented 8" casing string in Well No. 33, a new fully cemented 4" string in Well No. 43 and a new fully cemented 6" string in Well No. 44. Explain why Well No. 58 does not need to be*

relined—if applicable, Finger Lakes may refer to its reply to Item 2 above. Further, it is the Department's understanding that no evaluation and base logs (i.e., casing evaluation, cement bond log) were performed on the wells reworked with new casing strings which were cemented in place. Evaluation and base logs of these wells and new well FL1 along with a narrative analysis of each log will be required prior to the injection of LPG as a condition of any tentative storage permit.

- c. A proposed monitoring/observation well protocol, if any, which lists proposed monitoring/observation wells, identifies their locations and describes the purpose, methodology and frequency of the planned monitoring and observation.

Finger Lakes did not identify any permanent monitoring or observation wells for its proposed LPG storage facility. Please confirm that Finger Lakes will not have any dedicated monitoring or observation wells.

Prior to commencing any work on an existing or new well, including re-entry, drilling, conversion and plugging, the applicant must contact the Regional Minerals Manager to determine application, notification and/or permitting requirements for individual wells in accordance with 6NYCRR Parts 550 - 559.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Response to NOIA (Page 15) and May 14, 2010 Reservoir Suitability Report (Exhibit 9).

10. **Storage Rights Affidavit** - Please provide an affidavit stating that the applicant has acquired at least 75% of the storage rights within the proposed storage formation in the reservoir and buffer zone, and reference and include a lease tract map. In addition to the affidavit itself, include a tabulation which corresponds to the lease tract map of the names and complete mailing addresses of all surface owners within and adjacent to the proposed storage area (reservoir and buffer zone). Finger Lakes did not provide the requested lease tract map and tabulation. Finger Lakes must provide a new affidavit, lease tract map (including ultimate cavern outlines) and tabulation.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Response to NOIA (Exhibit E).

11. **Permit Application Fee** - The application fee for a new underground storage facility is \$10,000. The fee was received by the Department on October 13, 2009. Please find enclosed receipt No. 558202.

Satisfactorily addressed by Finger Lakes' prior submission.

Other Comments/Questions

Page 1, 1st paragraph – The statement “US Salt has been in the business of salt production for over 100 years by solution salt mining underground salt deposits on property adjacent to Seneca Lake” is incorrect as written. The sentence should be revised to state “US Salt and its predecessors at the facility...” US Salt’s predecessors at the facility include Cargill, Akzo-Nobel, Akzo and International Salt.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Reservoir Suitability Report (Page 1).

Page 2, 5th paragraph – Finger Lakes states “Brine circulated from the caverns will be stored in one or more above-ground ponds.” Please clarify the location of the multiple ponds that may be used to store brine.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Reservoir Suitability Report (Page 2).

Page 4, 2nd full paragraph – Finger Lakes states “The wells were abandoned in 1986 when the storage contract terminated with TEPPCO since they required a larger volume of storage than what US Salt was willing to provide” is incorrect as written. US Salt did not own the subject facility in 1986. The sentence should be revised to state “...than what one of US Salt's predecessors at the facility was willing to provide.”

Satisfactorily addressed by Finger Lakes' May 14, 2010 Reservoir Suitability Report (Sentence deleted).

Page 5, 2nd full paragraph – Finger Lakes states “NYSEG performed a hydrotest on Gallery 2 and Inergy has reviewed the MIT and the entire Gallery had pressure integrity.” Please provide a copy of the referenced hydrotest of Gallery 2 performed by NYSEG. A recent long-term brine hydrotest for Gallery 1 was performed in May 2009, and the results are provided as Exhibit 7 of the storage application. It is understood that Finger Lakes will have performed or will perform a nitrogen/brine interface MIT on every storage well (injection and withdrawal) prior to the injection of any storage gas.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Reservoir Suitability Report (New Gallery 2, Pages 7-8 & Exhibit 12).

Page 5, 3rd full paragraph – Finger Lakes states “These tools are important to the operation of the reservoir since repetitive and comparative logs will alert Finger lakes to any changes that might affect the well and cavern operation.” What is Finger Lakes schedule for running comparative gamma ray and neutron logs?

Satisfactorily addressed by Finger Lakes' May 14, 2010 Response to NOIA (Page 16).

Page 5, last full paragraph – Finger Lakes states “Finger Lakes and Inergy are cognizant of the overall pressures required for safe operations of hydrocarbon storage caverns based on years of experience and will never permit leakage that would jeopardize the public or USDW.” At what frequency will Finger Lakes monitor the wellhead pressures of its storage wells to ensure safe operation of its facility? It is understood that Finger Lakes Emergency Response Manual will be provided at a later date per above Item 6h.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Response to NOIA (Page 17).

Satisfactorily addressed by Finger Lakes' May 14, 2010 Reservoir Suitability Report (Sentence deleted).

Page 6, 3rd full paragraph – Finger Lakes states “New sonars of caverns for the proposed Finger Lakes Gallery 1 showed the salt pillar thickness relationship...” Information on the existing salt pillar thicknesses is important. However, Finger Lakes neglected to include information on salt pillar thicknesses at the end of the life of the project (i.e., ultimate cavern dimensions for Galleries 1 and 2). As previously noted, this information must be included and analyzed as part of Finger Lakes application.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Response to NOIA (Page 17).

Page 11, last full paragraph – There appears to be a typo or missing word in the sentence containing “...and used for hydrocarbon storage.”

Satisfactorily addressed by Finger Lakes' May 14, 2010 Reservoir Suitability Report (Page 16).

Page 14, 1st paragraph – Finger Lakes states “State-of-the art hydrotesting has been performed on the gallery shown as Finger Lakes Gallery 1 (33, 43, 34 and 44). The same will be provided for Finger Lakes Gallery 2 (30, 31 and 45) when all well workovers and new drilling are completed.” It is the Department’s understanding that no wells in Gallery 2 will have workovers (see “Finger Lakes Gallery 2,” page 12 of application). Please clarify. In addition, if and when the storage permit is issued and prior to injection of product, Finger Lakes will be required to submit for Department review and approval test data and a narrative report detailing the results of the proposed Gallery 2 hydrotesting.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Reservoir Suitability Report (New Gallery 2, Pages 7-8 & Exhibit 12).

Exhibit 15, Mechanical Integrity Test Procedures – Finger Lakes states “The U.S. Environmental Protection Agency (USEPA) requires that storage wells undergo a mechanical integrity test (MIT) prior to fluid injection in order to assure protection of the underground source of drinking water (USDW).” For clarification sake, the USEPA does not regulate LPG storage wells where no active solution mining is occurring such as Finger Lakes’ proposal. Wells used for the injection of LPG are specifically excluded under the USEPA’s Underground Injection Control (UIC) Program. See CFR Part 144 which states “(2) Specific exclusions. The following are not covered by these regulations: ... (iv) Injection wells used for injection of hydrocarbons which are of pipeline quality and are gases at standard temperature and pressure for the purpose of storage.” (<http://ecfr.gpoaccess.gov/cgi/t/text/text-idx?c=ecfr&sid=e836eb638bc78ea602d31da7d5dca6dc&rgn=div8&view=text&node=40:22.0.1.1.6.1.35.1&idno=40>) While the USEPA can require a “gas” MIT for Class 3 solution mining wells, its standard test uses brine which is not satisfactory to the Department for underground gas storage MIT purposes. Nevertheless, the Department appreciates Finger Lakes’ intent that all storage wells will be tested prior to storage service, and the fact that Finger Lakes states elsewhere in its application that all storage wells in Galleries 1 and 2 will be tested using the nitrogen/brine interface test prior to product storage.

Satisfactorily addressed by Finger Lakes' May 14, 2010 Reservoir Suitability Report (New Gallery 2, Pages 18-19 & Exhibit 26).