## DEPARTMENT OF PUBLIC WORKS DIVISION OF SANITATION AND WATER SUPPLY HAZARDOUS WASTE SERVICES UNIT NASSAU COUNTY, NEW YORK WELL LOG

			Cleaners	WELL DATA HOLE DIAM.(IN): 12 "		G.W. READINGS						
	RED BY			HOLE DIAM.(IN): <u>12 "</u> FINAL DEPTH (FT): <u>37 '</u>		DATE		WTE				
	NO.: <u>F</u>			CASING DIAM. (IN.): 4 "	-		DTW					
	uth Fr			CASING LNTH. (FT): 17 '		02/92	21.3	3 31.85				
	ELEVAT			SCREEN SET.(FT.) <u>17'-37</u> SCREEN SLOT/TYPE: <u>.020PV</u>								
DRILL	ER: La	rry E.	Tyree (K. Watson)	WELL STATUS: Monitoring								
TYPE	OF RIG	: Fail	ing F-10 (Auger)		4	DEVELOPMENT						
			November 23, 1992	SAMPLER								
	<u>1</u> 0		ovember 23, 1992	TYPE: <u>Split Spoon</u> HAMMER <u>140</u> LB. (Auto				r 1 hour				
	<u> </u>			FALL: $30$ IN.	at	8 GPM						
	H LITH- USCS SAMPLE DESCRIPTION						SAMPLE					
<u>(ft.)</u>	OLOGY	CLAS.			NO.	REC.	DEPTH	BLOWS				
0 -			0-3' Brown-tan, clayey	sand-fill.								
-												
2												
-			3-10' Tan, fine to med:	ium, poorly sorted	1	10"	5-7'	37/2ft				
-		SW	quartz sand with fine t	co coarse gravel (30%)								
-			in a clean matrix.									
-						-						
10 -			-		2	14"	10-12	20/2ft				
-												
-			10-21' Tan-orange, fine									
-		SW	moderately sorted quart	z sand with medium								
-			gravel (10%) in a clear	n matrix.	3	15"	15-17	38/2ft				
-												
-												
-												
20 -					4	16"	20-22	31/2ft				
-												
_												
-			21-37' Tan-orange, fine	to coarse, poorly								
-			sorted quartz sand wit	some fine gravel, clean	5	24"	25-27	28/2ft				
-		SW	matrix.									
_												
-												
30 -					6	24"	30-32	20/2ft				
-												
_												
-												

WELL	NO. FC-	-1		PAGE	<u>2</u> c	f <u>2</u>	
<u>DEPTH</u> (ft.)	LITH- OLOGY	USCS CLAS.	SAMPLE DESCRIPTION	<u>NO.</u>		AMPLE DEPTH	BLOWS
- - - 40 - -		SP	25-42' Tan-brown, fine to medium, some coarse, well sorted quartz sand, trace granules.	7 8	12" 12"		39/2ft
50	TD= 42	2 ft.					

1.000

##