ADDENDUM NUMBER 4 TO THE CONTRACT DOCUMENTS FOR

REMEDIATION OF THE 34 FREEMAN'S BRIDGE ROAD SITE SCHENECTADY COUNTY, NEW YORK May 10, 2006

NYSDEC SITE NO. 4-47-028 CONTRACT NO. D005813

TO ALL HOLDERS OF THE CONTRACT DOCUMENTS:

Your attention is directed to the following changes and additions to the contract documents for the remediation of the 34 Freeman's Bridge Road Site. This addendum has been prepared in accordance with the provisions of the Contract Documents.

A. Section V, Bid Forms and Attachments

1. Replace the current bid form (addendum #3) with revised bid form (Attachment 4).

B. <u>Section XI, Supplementary Specifications</u>

- 1. Add Section 01057 (Attachment 1) truck scale to Section XI.
- 2. Section 13560 -16, LTTD continuous emissions monitoring table. Delete stack gas velocity testing from the parameters column.

C. Section XII, Measurement for Payment

- 1. Revise Item LS-1, Paragraph 1.1, (A) insert the following:
 - "17. The CONTRACTOR shall furnish all labor, tools, materials, equipment, appurtenances, and incidentals to provide a certified truck scale ready for use, for the purpose of determining the weight of material being taken off site for disposal."
- 2. Revise Item UP-1, Paragraph 5.1, (B) insert the following:
 - "13. Operation, repair, and maintenance of the scale for the duration of the work specified under this Project. Contractor shall employ a trained weighmaster familiar with the scale provided."

3. Revise Item UP-5 accordingly:

"BID ITEMS UP-5 through UP-5C - OFF-SITE DISPOSAL OF METALS-CONTAINING SOILS AND CONTAMINATED DEBRIS UNACCEPTABLE FOR BACKFILL

9.1 General

- A. Bid Items UP-5 through UP-5C shall provide a unit price for each ton of soil and debris managed and disposed of that is unacceptable for backfill due to being RCRA and/or TSCA-regulated. Under this item, the CONTRACTOR shall furnish all labor, materials and equipment to screen, manage (i.e., chip wood, clean and crush concrete), characterize to meet disposal facility's requirements, and dispose of debris which is encountered as approved by the ENGINEER. Payment for building demolition debris, excluding building foundations shall be paid under LS-2
- B. Cells designated on the Drawings (3-7) with metals concentrations exceeding site-specific cleanup goals for chromium, mercury, and lead shall be segregated, staged, and characterized for off-site disposal. The Contractor shall provide all materials, equipment, and labor necessary to stage, characterize, transport, and dispose of soils to meet TSDF requirements and pretreatment as necessary.
- C. The CONTRACTOR shall provide certified weigh tickets for both pre-loaded and post-loaded trucks.

9.2 Measurement for Payment

- A. Measurement for payment of Bid Items UP-5 through 5C shall be for the actual quantity (tons) of soil or debris which is properly managed and disposed as indicated by the ENGINEER's records. Payment shall be made per ton of material for this item."
- 4. Revise Item UP-4 and 4A, 8.2 and 8.4 (Addendum 3) accordingly:

"8.2 Measurement for Payment

A. Measurement for payment of Bid Item UP-4 shall be for the amount of

soil (cubic yards) acceptably treated, stockpiled, and sampled, based on in-place surveys in accordance with Specification 01051, Part 3.01 (A) performed by a NYS licensed land survey and approved by the ENGINEER. The Contractor shall ensure that clean overburden soils be segregated from treated materials in the backfilled excavation to the extent that the actual quantity of treatment materials may be determined."

8.4 Measurement for Payment

Measurement for payment of Bid Item UP-4A shall be for the amount of soil (cubic yards) acceptably treated, stockpiled, and sampled, based on in-place surveys in accordance with Specification 01051, Part 3.01 (A) performed by a NYS licensed land survey and approved by the ENGINEER. The Contractor shall ensure that clean overburden soils be segregated from treated materials in the backfilled excavation to the extent that the actual quantity of treatment materials may be determined."

Attachments:

1- Section XI, Specification 01057

A.

- 2 Supplemental Contractor Questions and Answers
- 3 Moisture Content Data and Test Pit Logs
- 4- Section V- Revised Bid Form

Carsten Floess, P.E.
Earth Tech Northeast, Inc.

ATTACHMENT 1 Section XI, Specification 01057

SECTION 01057 TRUCK SCALE

1. GENERAL

1.1 SCOPE OF WORK

- A.. The **CONTRACTOR** shall furnish all labor, tools, materials, equipment, appurtenances, and incidentals to provide a certified truck scale ready for use, for the purpose of determining the weight of material being taken off site for disposal.
- B. The work shall include, but is not necessarily limited to the following:
 - 1. Protection of work to remain.
 - 2. Delivery and set-up of scale, including weight indicator and ticket printer.
 - 3. Certification of scale by County Bureau of Weights and Measures.
 - 4. Employing a trained weighmaster familiar with the scale provided.
 - 5. Repair and maintenance of the scale for the duration of the work specified under this Project.
 - 6. Providing proper foundations and ramps for the scale in accordance with the manufacturer's recommendations and County Bureau of Weights and Measures.
 - 7. Removal of scale, foundations, and ramps once the **ENGINEER** determines that the exclusion zone has been remediated.

1.2 SUBMITTALS

A. The **CONTRACTOR** shall submit shop drawings for the scale, weight indicator, ticket printer, foundations and approaches, and proposed location (shown on **CONTRACTOR's** proposed Operations Plan).

1.3 RELATED SECTIONS

- A. Related sections include:
 - 1. Section 01050, Temporary Facilities.
 - 2. Section 02230, Transportation and Disposal.

2. PRODUCTS

2.1 MATERIALS AND EQUIPMENT

A. Truck Scale

- 1. The truck scale shall be 10 feet wide, 60 feet long and have a minimum gross capacity of 60 tons. If the **CONTRACTOR** proposes operations requiring a greater capacity scale, the scale provided shall be capable of accurately measuring the weights proposed by the **CONTRACTOR**.
- 2. The foundation required for the scale shall not be extensive.
- 3. Level approaches at both ends of the scale shall be 10 feet long at a minimum.
- 4. The truck scale shall be compatible with digital electronic instrumentation.
- 5. The truck scale shall be aboveground truck scale model number 14-8460-1 as manufactured by Fairbanks Scales of St. Johnsbury, Vermont or equal.

B. Weight Indicator

- 1. The weight indicator shall be of the same manufacturer as the truck scale and shall be fully compatible with the scale and ticket printer.
- 2. The weight indicator shall be digital and shall have a simple "re-zeroing" operation or push button.
- 3. The weight indicator shall have a digital display.
- 4. The weight indicator shall be Digital Weight Indicator, model number 90-166 as manufactured by Fairbanks Scales of St. Johnsbury, Vermont or equal.

C. Ticket Printer

- 1. The ticket printer shall be of the same manufacturer as the truck scale and shall be fully compatible with the scale and weight indicator.
- 2. The ticket printer shall be Ticket Printer model 50-3925, as manufactured by Fairbanks Scale of St. Johnsbury, Vermont, or equal.

3. EXECUTION

A. The **CONTRACTOR** shall deliver, install, certify, and have the truck scale and appurtenances in proper working order prior to removing materials for disposal from the site.

- B. The weight indicator and ticket printer shall be protected from weather and vandalism by being placed either in a suitable scale house or an office trailer.
- C. No weights will be accepted or paid for unless the **ENGINEER** witnesses the weighing and receives the associated weight ticket.
- D. The scale shall be located in an uncontaminated area. The **CONTRACTOR** may propose a location different from that shown on the Plans; however, the **ENGINEER** must approve of any location other than that shown on the Plans.

* END OF SECTION *

ATTACHMENT 2 Supplemental Contractor Questions and Answers

Addendum 4 May 10, 2006 34 Freeman's Bridge Road site Glenville, New York

NYSDEC Site No. 4-47-028

Ouestions and Answers

- 1. Q: Item UP-5 calls for disposal of a significant quantity of soil and debris. Waste disposal costs for debris and soil can vary widely depending upon the waste stream (i.e., RCRA debris, TSCA debris, and non-RCRA/non-TSCA debris). Can item UP-5 be broken out to provide unit price bidding for each of the respective waste streams in order to covers all possible disposal cost scenarios?
 - A: Section 5, Bid Form has been revised to add Items UP-5 A through 5C. Contractors shall provide unit pricing for the respective debris waste streams. If debris is categorized as both TSCA/RCRA then a change order will be processed for off-site disposal. The line item for metals-contaminated soils shall remain UP-5. We anticipate the metals containing soils failing TCLP. If characterization samples described in this addendum do not fail TCLP, then a change order will be processed for off-site disposal as non-hazardous waste soil.
- 2. Q: It is expected that thermal treatment of soils and removal of debris from the waste matrix will reduces volume of soils available for re-use as backfill. Since there is not unit price for imported backfill, is the topsoil volume expected to balance the deficit for on-site fill for restoration to original grade?
 - A: The contractor is not expected to provide imported backfill as part of this contract. The contractor will be required to submit a final grading plan based on the final volume of treated soils. The minimum requirements of the final grading plan are to provide for positive drainage and adequate erosion control. To the extent possible, the topsoil will balance the volume deficit due to removal of debris and reduction of soil volume through treatment.
- 3. Q: Site security is required seven days a week 24 hours per day. Can the contractor provide their own security during working hours? Please confirm if and when a hired security guard should be provided.
 - A: Site security shall be maintained 24 hours, 7 days per week. The Contractor may provide their own security personnel provided they meet all the requirements of Section 01050, Paragraph 1.08.

Addendum 4 1 of 4 May 10, 2006

- 4. Q. Section XI, Specification 13560-3, item no. 4. Explain heavily impacted with NAPL. The analytical results do not seem to agree with "heavily impacted".
 - A: Refer to the RI report for an in depth description of on NAPL. Some of the site soils are heavily impacted by NAPL relative to areas that are non-impacted.
- 5. Q: Section XI, Specification 13560-12 (C) How will the contractor be compensated for unforeseen delays or other scenarios out of the contractors control?
 - A: Unforseen delays will be evaluated on a case by case basis and in accordance with the terms of your contract.
- 7. Q: LTTD pad detail is not included. Drawing number 2 references number 8. No drawing 8 is in the index to drawings. Will the pad need to be constructed of concrete?
 - A: The contractor shall submit a as part of the Construction Work Plan and in accordance with Section VIII, Articles 5.23 to 5.29, the details for the LTTD staging pad. The minimum requirements for a LTTD process pads are shown in the detail on Drawing No. 7. The Contractor shall select process pad detail that complements the manufacturer's or subcontractor's recommendation for the specific LTTD equipment proposed for completion of the work.
- 8. Q: Section XI, Specification13560-16. Why is stack velocity a continuous emissions monitoring parameter?
 - A: Stack gas velocity will not be required during continuous emissions monitoring.
- 9. Q: What are the decontamination requirements of the LTTD plant, specifically will the baghouse bags need to be disposed of assuming the baghouse is only exposed to soils with contaminate levels below the project treatment goals?
 - A: No. The baghouse bags will not require disposal.
- 11. Q: What is the anticipated schedule/timing of the notice to proceed following notification of apparent low bidder assuming all submittals are timely and acceptable?
 - A: The Notice to Proceed should be expected 60 90 days from bid opening depending on the timeliness and quality of the contractor's submittals.
- 12. Q: Is there existing moisture content data for the soils to be treated, this information could not be found in the RI report, as indicated in Addendum No. 3?

Addendum 4 2 of 4 May 10, 2006

A: A summary of moisture content data and respective environmental conditions is attached (Attachment 3) to this addendum. Attachment 3 is <u>NOT</u> part of the Contract Documents for the remedial work at the 34 Freeman's Bridge Road Site. The Department neither represents that the Site conditions will be the same as in the attached document nor considers the attached documents as being comprehensive and an actual description of the site conditions. The Contractor shall be responsible for performing the remediation work based on the existing conditions at the Site.

The bulk density data associated with the moisture content, (as reported in Addendum #3), is not available. This was a misunderstanding, as it was thought this was completed along with moisture content analysis during the RI. Pocket penetrometer testing of select soils (i.e., deep structural borings) is provided in the Limited Site Data Package.

The Contractor has the option to collect additional bulk density data at their own cost and risk NYSDEC will require the Contractor to submit a concise letter work plan which addresses proposed scope, location(s) of test pits, anticipated sampling activity, basic air monitoring (i.e. PID), evidence of insurance, decontamination procedures and site restoration. All proposed work will be reviewed and approved through NYSDEC and site work will be coordinated with Earth Tech oversight.

- 13. Q: Will the Department accept an alternate bid using an "in-situ" LTTD system that can achieve temperatures of $800 \,^{\circ}$ F.
 - A: NYSDEC will not evaluate any substitutions prior to award of the contract per Section III, Article 7, page III-5. However, the contractor reserves the right to propose a substitution under Section VIII, article 5.7 (Page VIII-15) after bid award. However, there is no guarantee that NYSDEC will approve the substitution, in which case the Contractor would be required to complete the job as ex-situ at the given bid price.
- 14. Q: Clarify if all excavation should be performed in the dry.
 - A: Yes excavations should be performed in the dry. The contractor shall submit a dewatering plan as part of the Construction Work Plan and in accordance with h Section VIII, Articles 5.23 to 5.29. The minimum requirements for the dewatering plan are stated in Section 02240, paragraph 1.04 (D). The Contractor shall select a method of dewatering that complements the Contractor's plan for site containment and excavation in the interest of optimizing the moisture content of the LTTD feed soil to the extent possible
- 15. Q: In order to achieve substantial completion, does the contractor have to complete decontamination and demobilization of all his equipment, staging areas and pads?

A: No. The demobilization and proper disposition of all equipment, support structures, including any residual contamination is the responsibility of the contractor and can be performed as punchlist work. The Department will keep sufficient retainage to cover the cost of this work.

Addendum 4 4 of 4 May 10, 2006

ATTACHMENT 3 Moisture Content Summary and Test Pit Logs


Freeman's Bridge Soil Moisture Content										
Test Pit	Depth	% Moisture	<u>Date</u>							
TP 26	2-4	30	September 20, 2000							
TP 27	2-4	11	September 20, 2000							
TP 27	4-6	25	September 20, 2000							
TP 26	2-4	30	September 20, 2000							
TP 09	2-4	13	September 20, 2000							
TP 09	4-6	13	September 20, 2000							
TP 17	2-4	18	September 21, 2000							
TP 17	4-6	19	September 21, 2000							
TP 19	0-2	9	September 21, 2000							
TP 19	4-6	21	September 21, 2000							
TP 21	0-2	8	September 20, 2000							
TP 21	2-4	15	September 20, 2000							
TP 24	2-4	13	September 20, 2000							
TP 24	4-6	14	September 20, 2000							
TP 25	0-2	15	September 20, 2000							
TP 25	2-4	18	September 20, 2000							
TP 26	0-2	6	September 20, 2000							
MW 20	4-6	26	November 1,2000							
MW 19	6-8	25	November 1,2000							
TP 5	6-8	17	September 14, 2000							
TP 1	4-6	27	September 14, 2000							
TP 1	6-8	37	September 14, 2000							
TP 3	6-8	13	September 14, 2000							
TP 3	4-6	12	September 14, 2000							
TP 4	2-4	11	September 14, 2000							
TP 4	6-8	23	September 14, 2000							
TP 18	0-2	12	September 14, 2000							
TP 18	2-4	19	September 14, 2000							
TP 23	2-4	12	September 14, 2000							
TP 23	4-6	18	September 14, 2000							
TP 14	2-4	17	September 14, 2000							

34 Freeman's Bridge Road Site, Soil Moisture Content Data

Depth	% Moisture
2-4	13
4-6	13
4-6	27
6-8	37
2-4	17
2-4	18
4-6	19
0-2	12
2-4	19
0-2	9
4-6	21
0-2	8
2-4	15
2-4	12
4-6	18
2-4	13
4-6	14
0-2	15
2-4	18
2-4	30
0-2	6
2-4	11
4-6	25
6-8	13
4-6	12
2-4	11
6-8	23
	4-6 4-6 6-8 2-4 2-4 4-6 0-2 2-4 4-6 0-2 2-4 4-6 0-2 2-4 4-6 0-2 2-4 4-6 0-2 2-4 4-6 0-2 2-4 4-6 0-2 2-4

Test Pit	% Ave Moisture in Pit
TP 9	13.00
TP 1	32.00
TP 14	17.00
TP 17	18.50
TP 18	15.50
TP 19	15.00
TP 21	11.50
TP 23	15.00
TP 24	13.50
TP 25	16.50
TP 26	18.00
TP 27	18.00
TP 3	12.50
TP 4	17.00
Average:	16.64

	Average % Moisture
Depth Interval	with in Interval
0-2	10
2-4	17
4-6	19
6-8	23
Average	17



E A R	тн	9 ,	E c н TEST I	PIT LOG			Т	EST PIT NO.:
		RNATIONAL LTD. COM					_	TP03
	RO PARK	ROAD ORK 12205						~
ROJEC'		38925	118.0	START: DATE	9/11	/00	TIME:	1430
ROJEC'	T:	Freeman's 1	Bridge Road Property	FINISH: DATE	9/11	/00	TIME:	1600
LIENT:		NYSDEC	W. W	GRADE ELEVAT	ION: _			
ONTRA	ACTOR:	Precison In	ndustrial Maintenance	ATUM:			SGS Nav	83
PERAT	OR:	Ron Burns		WATER TABLE:			grade	
QUIPM		CAT 446B		INSPECTOR:	Kev	ın M	cGrath	
EPTH (ft bg)	PID (ppm)	SAMPLE ID	SOIL DESCRI				REMA	ARKS
			Topsoil and roots		0.25			
1	ND	TP03 (0-2)	Loose, dry, reddish-brov coarse medium(+) fine S occasional coarse gravel	AND, little (-) Silt and cobbles, bits of				
2 —			broken brick and crushe	d asphalt.				
3 —	ND	TP03 (2-4)						
4 —					4.0	Sha	rp color	change at 4.0'
5 — -	ND	TP03 (4-6)	Loose to medium dense dark brown and gray, po fine SAND, with Silt an c&d material including:	oorly sorted, coars d Gravel; abundan concrete, rebar, pij	e to it pes,		edoe-sha	B'long, hollow pped cast iron
6 —		TD02	wiring, cinder block, asp very large blocks of con		verar			
7 —	ND	TP03 (6-8)	l lage blocks of con-			l .	-	d, strong odor een at WT
8 —			-			Y	WT 8'	
_	16	TP03 (8-9)	8" layer of wood chips	and plant fibers				
9 —			End Test P	it @ 9.0 ft				
10	1		,					
	L.		<u> </u>					
to pres	sence of	f potential fi very greasy-	0 feet below grade due ree-phase product. Soils oily feel and left a visible ective gloves.	9 🔻	—	16 —	6	North

E A R	ТН	S	E C H TEST F	PIT LOG		1	TEST PIT NO.:
		RNATIONAL LTD. COM	IPANY			-	TP04
	RO PARK I	ROAD ORK 12205					
ROJEC		38925		START: DATE	9/12/00	TIME:	0815
ROJEC'	•	Freeman's I	Bridge Road Property	FINISH: DATE	9/12/00	TIME:	0840
LIENT:	•	NYSDEC		GRADE ELEVAT	rion:	-	
ONTRA	ACTOR:	Precison Ir	ndustrial Maintenance I	ATUM:	Grade: US	SGS NAV	⁷ 88 -
PERAT	OR:	Ron Burns	and the state of t	WATER TABLE	: 9.0' below	grade	
QUIPM	ENT:	CAT 446B	Backhoe	INSPECTOR:	Kevin Mo		
EPTH (ft bg)	PID (ppm)	SAMPLE ID	SOIL DESCRI	PTION		REMA	lRKS
		TP04(0-0.5)	, , ,				
1 —	ND	TP04 (0-2)	coarse medium fine(+) S. Gravel.	AND, little(-) fin	e 2.0		
3 —	ND	TP04 (2-4)	Loose, moist to dry, dark coarse-medium SAND, v and Silt; abundant c&d in metal, pipes, and concret	with coarse-fine C ncluding: brick, bl	l l		
5 —	ND	TP04 (4-6)	Medium dense, dry to we reddish-brown coarse(+) coarse Gravel; abundant of	medium SAND,			
6 — 7 — -	ND	TP04 (6-8)					
8 — 9 —	ND	TP04 (8-10)			9.5	WT .9'	
40]		Stiff, wet, Sitly-CLAY				
10			End Test P	?it@10.0			
Notes:) 12 & 13	,		↓ 10	16-		North

E A R	тн	9 T	есн TEST	PIT LOG		Т	TP09
12 METI	RO PARK	rnational ltd. con ROAD ORK 12205	PANY				-
PROÆC	T #:	38925 Freeman's	Bridge Road Property	START: DATE FINISH: DATE	9/18/00	TIME:	1050 1120
CLIENT: CONTRA OPERAT EQUIPM DEPTH (ft bg)	ACTOR: FOR: ÆNT:	Precison In Ron Burns CAT 446E SAMPLE ID		GRADE ELEVAT I A T U M : WATER TABLE: INSPECTOR: IPTION	Grade: US	grade	
1	ND	TP09 (0-2)	Topsoil and roots Loose, moist, brown, co SAND, little(-) fine Gra	parse meduim(+) fi	0.25 ne		
3 —	ND	TP09 (2-4)	Loose, moist to wet, da medium(+) fine SAND, Gravel; abundant c&d,	little(-) Silt and fin mostly brick with	ne		
4 — 5 —	ND	TP09 (4-6)	cinder block and asphal of concrete and metal o			6 0'	
6 — 7 — 8 —					8.5	0.0	
9 —			Somewaht stiff, gray an fine Sand	d light-brown SILT			
10			End Test P	its@9.0			
Notes:				↓ 9	12 —	4	North

E A R	T H		E c н TEST	PIT LOG			test pit no TP14
	•	RNATIONAL LTD. CON	MPANY				11.14
	RO PARK Y, NEW Y	ROAD ORK 12205		_			
ROJEC	T #:	38925		START: DATE	9/13/0	00 TIME:	1000
'ROJEC	T:	Freeman's	Bridge Road Property	FINISH: DATE	9/13/0	00 TIME:	1030
CLIENT:		NYSDEC	<u> </u>	GRADE ELEVA	TION: _		
CONTRA	ACTOR:	Precison I	ndustrial Maintenance	DATUM:	USGS	<u>S</u>	
PERAT	TOR:	Ron Burns		WATER TABLE			
EQUIPM		CAT 446E		INSPECTOR:	Kevir	1 McGrath	
OEPTH (ft bg)	PID (ppm)	SAMPLE ID	SOIL DESCR	IPTION		REMA	ARKS
			Topsoil 2".				
1	ND	TP14 (0-2)	Loose, wet, C mf S, l(+) mostly brick, some meta styrofoam.				
ر م			(FILL)				
2 —			i.			Water entering at ~ 45	ng excavation
3 —	ND	TP14 (2-4)				at 40	
, –	IND	(2-4)					
4 —					ł	Black oily	
						water. Hea 5.0	vy sneen.
5 —	ND					Strong odor	
	1110				5.5		
6 —			SS S, w gr br \$, k and lenses of Sand. (Na	(+) mf S, mottled pocl tive)	kets		
	`				6.0		
7 —	-					•	
8 —							
_	1						
9 —	1						
-	1						
10-	1						
	1	1					
Notes:			· · · · · · · · · · · · · · · · · · ·		1 ,		N T
						<u> </u>	North
				'		A	

E A R		T RNATIONAL LTD. COM	есн TESTI	PIT LOG			TEST PIT NO.: TP17	
12 METRO	PARK I	ROAD					-	
ALBANY, ROJECT		38925		START: DATE	9/18	3/00 TIME	: 1430	
ROJECT:	-		Bridge Road Property	FINISH: DATE	9/18			
LIENT:	•	NYSDEC		GRADE ELEVAT	ION:			
ONTRA	CTOR:	Precison In	ndustrial Maintenance	ATUM:	Gra	de: USGS N	AV 88	
PERATO	DR:	Ron Burns		WATER TABLE	6.0			
QUIPME	NT:	CAT 446B	Backhoe	INSPECTOR:	Kev	in McGrath		
1	PID (ppm)	SAMPLE ID	SOIL DESCRI	PTION		REI	MARKS	
1	211	TP07 (0-2)	Topsoil and roots Loose, moist, black and coarse medium(+) fine S Silt and fine Gravel; about bits of brick.	SAND, little (-)	0.25 ly	approximat of soil. Dr full to part	ix drums and ely 10 yards ums appear ially full of	
3	246	TP07 (2-4)	ons of ones.		4.5	a black "enamel-paint" lil substance. Collected sample of product. PID wand inserted in opening in drum, 3280 ppm		
5 —	128	TP07 (4-6)	Stiff, moist to wet, gray with fine Sand, somewh	_		V (0)		
6 —						→ 6.0		
7 —					7.0			
8 —								
9 —								
10-		·						
		<u> </u>	And the second s					
	y full		ms full and intact, 3 drum Drums placed in	s	-	25	North	

	9.	есн TEST	PIT LOG	TEST PIT NO.:
E A R T H	ERNATIONAL LTD. COM		rii LOG	<u>TP18</u>
12 METRO PARK	ROAD			
ALBANY, NEW Y PROJECT #:	38925		START: DATE 9/1	3/00 TIME: 0800
PROJECT:	Freeman's l	Bridge Road Property		3/00 _{TIME:} 0920
CLIENT:	NYSDEC		GRADE ELEVATION:	
CONTRACTOR	Precison I	ndustrial Maintenance	DATUM: Gr	ade: USGS NAV 88
OPERATOR:	Ron Burns		WATER TABLE: 3.0	' below grade
EQUIPMENT:	CAT 446B	Backhoe	INSPECTOR: Ke	vin McGrath
DEPTH PID (ppm)	SAMPLE ID	SOIL DESCR	IPTION	REMARKS
– 16	TP18(0-0.5)	Very loose, wet, coarse	medium SAND, and	
1 -	TP18	1	mostly brick and wood.	Strong odor.
228	(0-2)	Black stained soils from	1 2.5 to 4.0.	DI 1'1 TATADI (0.51
2 - 220				Blackish LNAPL at 2.5' to WT.
226	TP18			10 111.
3 —	(2-4)			Y 3.0
218	Dupl		4.0	Heavy sheen at WT.
4 —		E. d Die	4.0	Dieus of fice product
-		End Pit	(<i>a</i> , 4.0	observed on water acuumulated in open
5				pit.
6				
8				
9 —				
10				
Notes:			4	18 — North 9


	т н			PIT LOG			TP19
12 METI	RO PARK	rnational ltd. com ROAD ORK 12205	IPANY				-
ROJEC		38925		START: DATE	9/19/00	TIME:	0800
ROÆC	T:	Freeman's	Bridge Road Property	FINISH: DATE	9/19/00	TIME:	1130
LIENT:	: .	NYSDEC		GRADE ELEVAT	`ION:		
ONTR/	ACTOR:	Precison I	ndustrial Maintenance <u>r</u>	ATUM:	Grade: U	SGS NAV	7 88
PERAT	ΓOR:	Ron Burns		WATER TABLE	5.5' belov	v grade	
QUIPM	ŒNT:	CAT 446B	Backhoe	INSPECTOR:	Kevin M	cGrath	
EPTH (ft bg)	PID (ppm)	SAMPLE ID	SOIL DESCRIF	TION		REMA	RKS
	ND	TP19 (0-2)	Loose, moist, dark red-b		vel.		
			Medium dense, dry, black	` '			
3	ND	TP19 (2-4)	fine SAND and fine Grav mostly brick and block	er, abundani cæd	3.5		
ļ ——			Stiff, moist, gray Clayey-Sand. Very fine laminae		2		
5	ND	TP19 (4-6)	clay.		5.5	- ~ 5.5	
S —			Stiff, wet, gray and brow mottled with lenses and				
7	ND		fine Sand				
3 —							
9 	ND						
10			End Test Pi	t @ 10.0			
						· · · · · · · · · · · · · · · · · ·	
Notes:				↓ 10	12 —	4	North


E A R	т н	(E C H TEST F	PIT LOG				TP21
A	A tụco INTE	RNATIONAL LTD. CON	1PANY					11 21
	RO PARK I	ROAD ORK 12205						
ROJEC		38925		START: DATE	9/19/0	00	TIME:	1310
ROJEC	T: .	Freeman's	Bridge Road Property	FINISH: DATE	9/20/0	0C	TIME:	1100
LIENT:		NYSDEC		GRADE ELEVA				
ONTR	ACTOR:	Precison I	ndustrial Maintenance	ATUM:	Grade	e: US	GS NAV	/ 88
)PERAT	ΓOR:	Ron Burns		WATER TABLE				
EQUIPM		CAT 446E	1	INSPECTOR:	Kevir	ı Mc		
OEPTH (ft bg)	PID (ppm)	SAMPLE ID	SOIL DESCRI	PTION			REMA	ARKS
_		TD0 1	Hard packed gravel over	asphalt.	0.75			
1 —	10.4	TP21 (0-2)	Loose, moist to wet, black fine SAND, and fine Gra		lium			
3 —	28.6	TP21 (2-4)	Loose, wet, black, well so	orted coarse SAN	JD.	enter	ing pit fr	
4 —— 5 —— 6 ——	ND		and Gravel; abundant c& with piping, metal bits, b chips, drum lids, bung ca	d, mostly broken roken glass, conc	brick rete	streai Remo 25 ya	ards of h	
7 — 8 —			Stiff, wet, gray and brow mottled with lenses and fine Sand		nat			
9 —								
10-	<u> </u>		End Test P	it @ 10.0				
	1					<u> </u>		
l .	ed culv		/2 in excavation. backfilled	d		12 —		North

EARTH	9 7	есн TEST	PIT LOG		Т	TEST PIT NO.:
	TERNATIONAL LTD. COM		• • •		-	TP23
12 METRO PARK ALBANY, NEW Y						
PROJECT #:	38925		START: DATE	9/11/00	TIME:	1315
PROJECT:	Freeman's	Bridge Road Property	FINISH: DATE	9/11/00	TIME:	1400
CLIENT:	NYSDEC		GRADE ELEVA	TION:		
CONTRACTOR	Precison In	ndustrial Maintenance	DATUM:			88
OPERATOR:	Ron Burns		WATER TABLE			
EQUIPMENT:	CAT 446B	I	INSPECTOR:	Kevin Mo		
DEPTH PID (ppm)	SAMPLE ID	SOIL DESCR	IPTIOŇ		REMA	ARKS
		Topsoil and roots		0.25		
1 ND		Loose, dry, light brown coarse medium fine SAI occasional c&d, mostly	ND, little(-) Silt;	2.0		
2		Trash and debris. Abun-	dant plastic bags,			
3 — ND		broken glass, cans, bott stones, bricks, and block	les, paper, metal,			
4		1				
5 ND					7 5.5	
-				6.0	5.5	
6 — 1.9 7 — 1.9		Somewaht stiff, wet, g little(-) fine Sand. Mo and lenses of orange-bagray clay.	ottled with pockets	3		
8						
9 — 121						
10—						
					,	
		End Pit	11.0			
Notes:			↓ 1:	12 -	6	North

E A R		9 7	есн TEST	PIT LOG			TP24
12 METRO	PARK I		IPANY				
ALBANY, PROJECT	-	ORK 12205 38925		START: DATE	9/18/0	0 TIME:	0800.
ROJECT:	•		Bridge Road Property	FINISH: DATE	9/18/0		0900
CLIENT:	•	NYSDEC		GRADE ELEVA		1117333.	
	CTOR:	Precison I	ndustrial Maintenance	T DATUM:		: USGS NAV	7 88
OPERATO	-	Ron Burns		WATER TABLE	_: 7.5' be	low grade	
EQUIPME		CAT 446B	Backhoe	INSPECTOR:		McGrath	
DEPTH	PID (ppm)	SAMPLE ID	SOIL DESCR	IPTION		REMA	ARKS
1 —	ND	TP24 (0-2)	Topsoil and roots Loose, dry, light brown, coarse medium fine SAN trace fine Gravel.		0.25		
3 - 4	ND	TP24 (2-4)	Medium dense, moist to coarse medium SAND,	and fine Gravel;	3.0		
5 —	ND	TP24 (4-6)	occasional c&d, bricks a huge rebarred concrete	_			
7 - 8					8.5	7.5 slight odor be	elow water tabl
9 —			Somewhat stiff, gray and fine Sand	nd brown SILT, ar			
10			End Pit	@ 9.5			
Notes:				J 9.5		6 4 4	North .

Page 1 of 1





E A R	тн	<u>S</u>	E c н TEST I	PIT LOG		T	EST PIT NO.:	
		RNATIONAL LTD. COM				-	TP27	
12 METI	RO PARK	ROAD					-	
PROJEC		ORK 12205 38925		START: DATE	9/20)/00 time:	1430	
PROJEC		Freeman's I	Bridge Road Property	FINISH: DATE	9/20	0/00 _{TIME:}	1600	
CLIENT	: .	NYSDEC		GRADE ELEVAT	-			
CONTR	ACTOR:	Precison In	ndustrial Maintenance	ATUM:		de: USGS NA	V 88	
OPERA?	FOR:	Ron Burns		WATER TABLE:		below grade		
EQUIPM		CAT 446B		INSPECTOR:	Kev	vin McGrath	DIC	
DEPTH (ft bg)	PID (ppm)	SAMPLE ID	SOIL DESCRI	PTION		REMA	ARKS	
			Dense, coarse SAND ar	nd Gravel				
1	11	TP27			1.0			
' <u>-</u>	44	(0-2)	Loose, moist to wet, bla SAND, with coarse fine	Gravel; abundant		Odor from 1.0 to 6.0 ft below grade.		
2 —			c&d, including brick, asp	ohalt, concrete, wo	ood;	_		
3 —]	TP27	l l			- 6" layer of blackish staine sand 2.5- 3.0 ft. 250 ppm		
- -	46	(2-4)						
4	ļ				4.2			
,	-		Somewhat stiff, moist to	o wet, gray and gr	ay,			
5 —	54	TP27	SILT, and fine Sand; me		and			
_	-	(4-6)	pockets of fine sand and	d clay.	6.0	5.8		
6 —			CLIC CIL- CI	AX little () fine	1111 1111	1		
-	1		Stiff, wet gray Silty-CL trace fine Gravel; mode		Sanu,			
7 —	1		abundant fine laminae					
-	1		fine Sand.					
8 —			End test pit@	0,8.0				
9 —								
10-	-							
 		1	<u> </u>					
Notes:						12 -	North	
				8		12 1		
				▼			-	
1						· T		

ATTACHMENT 4 Section V, Revised Bid Form

Bid Form New York State Department of Environmental Conservation Project Number D005813, NYS Site Number 4-47-028

Payment Item	Description	Estimated Quantity	Unit or Lump	Total Amount	
Number			Words	Figures	(\$)
LS-1	Mobilization/Demobilization	1			
LS-2	Building Demolition	1			
LS-3	WWTP Mobilization, Start-up, and Testing	1			
LS-4	LTTD Demonstration Pilot Test	1			
UP-1	Site Facilities and Utilities	285 Days			
UP-2	Health and Safety	210 Days			
UP-3	Excavation of Soil and Debris	69,000 CY			
UP-4	LTTD treatment of Non-TSCA Soils	46,000 CY			
UP-4A	LTTD treatment of TSCA Soils	12,500 CY			
UP-5	Offsite disposal of metals containing contamining soils	3,540 Ton			

New York State Department of Environmental Conservation Project Number D005813, NYS Site Number 4-47-028

Payment Item	Description	Estimated Quantity	Unit or Lump Sum Pi	Total Amount	
Number			Words	Figures	(\$)
UP-5A	Off-site disposal of non- RCRA/non-TSCA debris	3,220 Ton			
UP-5B	Off-site disposal of RCRA contaminated debris	3,220 Ton			
UP-5C	Off-site disposal of TSCA contaminated debris	3,220 Ton			
UP-6	Backfill with treated and potentially clean overburden	65,500 CY			
UP-7	Post Excavation Confirmatory Soil Sampling	150 Sampling Suites			
UP-8	Water Treatment	1,000,000 Gallons			
UP-9	NAPL disposal -offsite	32,000			
UP-10	Monitoring Well Decommissioning	21 Wells			
UP-11	Site Restoration - Topsoil and Seeding	10 Acres			
			TOTAL for Pa	ages V-2 and V-3	

New York State Department of Environmental Conservation Project Number D-5813, NYS Site Number 4-47-028

Item No.	Item Description	Unit	Estimated	Unit or Lump Sui	Total Amount			
		Quantity		Words	Figures	(\$)		
	Pollution Liability Insurance	LS	1					
	This item is not to be calculated in the base Bid for the project. Contractor is referred to Article 4 of the General Conditions in the Contract Documents. The limits for Pollution Liability Insurance will be the same as defined in Article 4 of the General Conditions. After opening of bids, Department will determine if it is in Department's best interest to have Contractor obtain an additional \$4,000,000 Pollution Liability Insurance on a site specific basis, and if so, Contractor will be paid separately at the actual documented cost to obtain this additional insurance. The Bidder is required to fill in the above price if it can obtain site-specific Pollution Liability Insurance. This Bid amount will be the upper limit for payment of this item. The Department is to be listed on the Bidder's Company Policy as an additional insured at no additional cost to the Department .							
	Contractor Authorized Representative Contractor Name Date							