



PRECISION
ENVIRONMENTAL SERVICES, INC.
831 RT. 67, LOT 38 A
BALLSTON SPA, NY 12020
TEL: 518-885-4399
FAX: 518-885-4416

CERTIFIED WOMEN-OWNED BUSINESS ENTERPRISE

DRILLING LOG

Well/ Boring No.: MW-1R

Project: Dambrose Dry Cleaners Client: NYS DEC

Project No: 10-001-D4 Location: 1517-1519 Van Vranken Ave, Schdy, NY

Driller: Rich Comfort Logged by: Brian Baulsir

Drilling Contractor: Aquifer Drilling Drilling Method: Hollow Stem Auger

Date Drilled: 11/22/2010 Date Developed: 11/24/2010

TOC Elevation: 200.07 Total Depth of Hole: 16'

Boring Diameter: 6.25" Screen Diameter: 2" Length: 7'

Slot Size: 0.01 Riser Diameter: 2" Length: 9'

Type: PVC Sand Pack: 7' - 16' Bentonite Seal: 4.5' - 7'

Protective Casing: Flush Roadbox

See Site Map

Depth (ft.)	Well Construction	Recovery & Blow Counts	Sample Type / No.	Max PID (ppm)	Description / Soil Classification
0					
1					
2					
3					
4					
5					
6		50%	SS-1	ND	Brown to dark brown silt with some gravel, fine to coarse sand, and clay.
7		2/3/4/5			
8					
9					
10		50%	SS-2	ND	Dark gray silt with fine to coarse sand and trace clay.
11		2/3/3/3			
12		50%	SS-3	ND	Dark gray silt with fine to coarse sand and trace clay.
13		2/3/3/3			Wet at 13'.
14		50%	SS-4	ND	Dark gray silt with fine to coarse sand and trace clay.
15		1/3/4/4			
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					

ND = Not Detected by PID Analysis



PRECISION
ENVIRONMENTAL SERVICES, INC.

831 RT. 67, LOT 38 A
BALLSTON SPA, NY 12020
TEL: 518-885-4399
FAX: 518-885-4416

CERTIFIED WOMEN-OWNED BUSINESS ENTERPRISE

DRILLING LOG

Well/ Boring No.: MW-2R

Project: Dambrose Dry Cleaners Client: NYS DEC
Project No: 10-001-D4 Location: 1517-1519 Van Vranken Ave, Schdy, NY
Driller: Rich Comfort Logged by: Brian Baulsir
Drilling Contractor: Aquifer Drilling Drilling Method: Hollow Stem Auger
Date Drilled: 11/22/2010 Date Developed: 11/24/2010
TOC Elevation: 199.56 Total Depth of Hole: 15'
Boring Diameter: 6.25" Screen Diameter: 2" Length: 10'
Slot Size: 0.01 Riser Diameter: 2" Length: 5'
Type: PVC Sand Pack: 3' - 15' Bentonite Seal: 1' - 3'
Protective Casing: Flush Roadbox

See Site Map

Depth (ft.)	Well Construction	Recovery & Blow Counts	Sample Type / No.	Max PID (ppm)	Description / Soil Classification
0					
1					
2					
3					
4					
5					
6		60%	SS-1	ND	Brown to dark brown fine to coarse sand and silt with trace gravel.
7		2/3/2/2			
8					
9					
10		50%	SS-2	ND	Brown to dark brown fine to coarse sand with urban fill (concrete, glass, ash, etc.). Wet at 11.5'.
11		2/1/1/2			
12					
13		33%	SS-3	ND	Brown and gray silt with some fine to coarse sand and rock fragments.
14		2/4/12/12			
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					

ND = Not Detected by PID Analysis