


**BBL**<sup>®</sup>

BLASLAND, BOUCK & LEE, INC.  
engineers, scientists, economists

*Transmitted Via Overnight Delivery*

November 16, 2004

Mr. Mark Mateunas  
Bureau of Hazardous Site Control  
New York State Department of Environmental Conservation  
625 Broadway, 12<sup>th</sup> Floor  
Albany, NY 12233-7012



Re: McKesson EnviroSystems  
Bear Street Site  
Syracuse, New York  
Site No. 07-34-020  
BBL Project #: 0260.26003 #10

Dear Mr. Mateunas:

This *Biannual Process Control Monitoring Report* (Biannual Report) for the McKesson EnviroSystems, Bear Street Site (the site), located at 400 Bear Street in Syracuse, New York has been prepared by Blasland, Bouck & Lee, Inc. (BBL), on behalf of McKesson Corporation (McKesson), to present a description of the operation and maintenance (O&M) activities conducted and the monitoring results obtained during the period from January 2004 through June 2004. Additionally, this report also presents a detailed description of the supplemental remedial activities conducted between August 2 and August 12, 2004. This report has been prepared in accordance with the requirements of the New York State Department of Environmental Conservation- (NYSDEC-) approved *Site Operation and Maintenance Plan* (BBL, Revised August 1999) and a December 29, 1999 letter from David J. Ulm of BBL to Michael J. Ryan, P.E. of the NYSDEC, presenting the long-term process control monitoring program as an addendum to the Site O&M Plan. The Site O&M Plan and the addendum are collectively referred to herein as the O&M Plan.

The site is divided into two operable units: Operable Unit No. 1 (OU No. 1) - Unsaturated Soil and Operable Unit No. 2 (OU No. 2) - Saturated Soils and Groundwater. As a part of the NYSDEC-selected remedy for both of these operable units, there has been and continues to be ongoing O&M activities. Since completing the OU No. 1 remedial activities in 1994/1995 and commencing the OU No. 2 in-situ anaerobic bioremediation treatment activities in July 1998, the details regarding the O&M activities and the results of the process control monitoring program have been provided to the NYSDEC in biannual reports. A site description and history, along with a description of the remedial actions completed and the ongoing O&M activities being conducted were detailed in the previous biannual reports, including BBL's August 2001 Biannual Report covering the period from July 2000 through December 2000. That information has not changed and is not repeated herein.

During this reporting period (January 2004 through June 2004), no substantial system repairs were required and no unusual observations were made regarding system operations. The Area 3 in-situ anaerobic bioremediation treatment system has operated satisfactorily during this reporting period without interruption and approximately 784,000 gallons of water were pumped from the withdrawal trench and introduced into the Area 3 infiltration trenches as detailed herein.

6723 Towpath Road • P.O. Box 66 • Syracuse, NY 13214-0066  
Tel (315) 446-9120 • Fax (315) 449-0017 • www.bbl-inc.com • offices nationwide

The NYSDEC was notified of the June 2004 process control monitoring event (including hydraulic, biological, and chemicals of concern [COC] monitoring) prior to the commencement of the monitoring activities. The details and schedule of the supplemental remedial activities were also coordinated with the NYSDEC prior to initiating these activities.

The information provided in this letter has been organized into the following sections:

- **I. RAMM and Suga-Lik™ Introduction Activities** – A description of the Revised Anaerobic Mineral Media (RAMM) and Suga-Lik™ (Blackstrap Molasses) introduction activities.
- **II. Hydraulic Process Control Monitoring** – A description of the results of the hydraulic control monitoring activities conducted between January 2004 and June 2004.
- **III. Biological Process Control Monitoring** – A description of the June 2004 results of the biological process control monitoring and a comprehensive summary of the biological indicator (phospholipids fatty acids [PLFA] and poly-b-hydroxy alkanate [PHA]) results obtained since commencement of the in-situ anaerobic bioremediation treatment activities in 1998.
- **IV. COC Process Control and Biannual Groundwater Monitoring Program** – A description of the June 2004 results of the COC process control and biannual groundwater monitoring program, and a summary of the COC data obtained at the site from 1989 through June 2004.
- **V. Supplemental Remedial Activities** – A summary of the supplemental remedial activities conducted at the site between August 2 and August 12, 2004.
- **VI. Conclusions** – Conclusions based on the results of the process control monitoring activities and supplemental remedial activities.
- **VII. Recommendations** – Recommendations for the in-situ anaerobic bioremediation treatment program and monitoring activities.

#### **I. RAMM and Suga-Lik™ Introduction Activities**

Based on the results of the process control monitoring activities, the continued addition of RAMM into each of the three areas and the continued addition of Suga-Lik™ (with the RAMM) in Area 1 and downgradient of Area 2 were recommended in the June 2004 *Biannual Process Control Monitoring Report* to further stimulate the anaerobic biodegradation of the relatively low concentrations of COCs at these locations. As detailed in that Biannual Report, the relatively low COC concentrations detected at these locations may not provide a source of carbon sufficient to sustain microbial activity. To further stimulate growth of indigenous bacteria, the RAMM and Suga-Lik™ introduction activities listed below have been conducted.

- Continuing to introduce approximately 100 gallons of RAMM-amended groundwater into each of the three areas on a monthly basis.
- Continuing to add Suga-Lik™ with RAMM into the two Area 1 infiltration trenches on a monthly basis by manually filling each of the standpipes located in these trenches. Suga-Lik™ has been added during these monthly RAMM introduction activities to provide an easily metabolized carbon source to further stimulate the growth of the indigenous bacteria. Suga-Lik™ provides electron donors, while RAMM provides nutrients and electron acceptors.

- Continuing to introduce RAMM and Suga-Lik™ on a monthly basis into piezometers PZ-G, PZ-Q, PZ-R, and PZ-S located within and downgradient of Area 1. RAMM and Suga-Lik™ have been introduced into the shallow hydrogeologic unit within and downgradient of Area 1 using these piezometers to provide a better distribution of a readily degradable carbon source that otherwise may not reach these areas if distributed through the infiltration trenches only.
- Continuing to introduce RAMM and Suga-Lik™ on a monthly basis into piezometer PZ-W located downgradient of Area 2, near monitoring well MW-36.

Approximately 10 gallons of the RAMM/Suga-Lik™ solution has been introduced into each of the aforementioned piezometers and approximately 100 gallons of Suga-Lik™ and/or RAMM solution into each of the three areas on a monthly basis. The amount of Suga-Lik™ added to the RAMM has been proportional to the levels of COCs detected, at the dilution ratio of 1,000:1.

## **II. Hydraulic Process Control Monitoring**

As part of the hydraulic process control monitoring activities conducted during January 2004 through June 2004, groundwater-level measurements were obtained at existing monitoring wells and piezometers that are screened entirely within the sand layer of the shallow hydrogeologic unit and located in and around each of the three areas. Groundwater-level measurements were also obtained from selected monitoring wells (MW-6D located upgradient of Area 3 and MW-8D located within Area 3) screened entirely within the deep hydrogeologic unit. Additionally, a groundwater-level measurement was obtained from a staff gauge located in the Barge Canal adjacent to the site. The hydraulic process control monitoring activities were conducted on June 14, 2004. The monitoring locations are shown on Figure 1.

Table 1 summarizes the groundwater-level measurements obtained during the June 2004 hydraulic monitoring events, as well as those obtained since June 1998 (immediately prior to commencing the in-situ anaerobic remedial activities). Figure 2 depicts the potentiometric surface of the site's shallow hydrogeologic unit using the June 14, 2004 data set, which is consistent with previous hydraulic monitoring events. The results and corresponding conclusions of the hydraulic process control monitoring are also summarized below.

- A closed-loop hydraulic cell continues to be maintained in Area 3, as shown on Figure 2.
- The groundwater withdrawal rate in Area 3 ranged from approximately 0.7 gallons per minute (gpm) to 5.1 gpm. These rates continue to induce a higher hydraulic gradient across the area of relatively higher concentrations of COCs within Area 3 (relative to baseline conditions), while maintaining hydraulic containment in Area 3.
- In Area 3, approximately 75% of the recovered groundwater continues to be introduced to the secondary infiltration trench "B" and the remaining 25% continues to be introduced to the secondary infiltration trench "A." This introduction of recovered groundwater into the secondary infiltration trenches increases the rate at which RAMM-amended groundwater moves through the area of relatively higher concentrations of COCs (between the secondary infiltration trenches). The withdrawal of groundwater continues to induce a hydraulic gradient in Area 3 from perimeter monitoring wells MW-23S, MW-25S, and MW-17R toward the withdrawal trench.
- No discernable, long-term hydraulic effects were identified at or near Areas 1 and 2 as a result of introducing RAMM or RAMM/Suga-Lik™ into these areas on a monthly basis.

- The groundwater elevations measured at selected monitoring locations screened entirely within the deep hydrogeologic unit indicate that the operation of the Area 3 system is continuing to have no discernable effect on the hydraulic gradient of this unit.
- The weekly conductivity measurements of groundwater pumped from the withdrawal trench in Area 3 ranged from approximately 1 millisiemens per centimeter (mS/cm) to 2.14 mS/cm, which is within the range of the conductivity levels measured prior to system operation (1 mS/cm to 4 mS/cm). These measurements are well below the measured conductivity of the deep unit, which is greater than the calibration range of the field instrument (10 mS/cm). These data indicate that the operation of the Area 3 treatment system has not caused the freshwater/saltwater interface to upcone to the base of the withdrawal trench.

### III. Biological Process Control Monitoring

The biological process control monitoring includes collecting groundwater samples for laboratory analysis of PLFA and PHA, common biological indicators in both oxidized and reduced states (e.g., electron acceptors: nitrate, manganese, iron, sulfate, and carbon dioxide), and permanent gases (nitrogen, carbon dioxide, and methane). The monitoring locations are shown on Figure 1. In addition, the following groundwater quality parameters were also measured in the field during the June 2004 biological sampling event: pH, temperature, conductivity, dissolved oxygen (DO), and oxidation/reduction potential (ORP). To better evaluate the availability of macronutrients necessary for biological growth, groundwater samples collected from monitoring locations within the three areas, and from perimeter monitoring wells MW-29 and MW-30 (downgradient of Area 3) and MW-33 and MW-36 (downgradient of Areas 1 and 2, respectively) were analyzed for ammonia, potassium, and ortho-phosphate.

The results of the June 2004 biological process control monitoring activities are presented in Table 2 and shown on Figures 3 through 11. These biological process control monitoring results are summarized below.

- In general, the biomass (PLFA) levels increased or remained the same in most monitoring locations in Areas 1, 2, and 3 since the May 2003 sampling event, except at MW-31 in Area 1 where the PLFA level decreased (see Figure 3 [Area 1], Figure 6 [Area 2], and Figure 9 [Area 3]). The PLFA level decreased from 19 picomoles/milliliter (pmol/ml) (October 2003) to 1 pmol/ml (June 2004) at monitoring location MW-31. As discussed in Section IV, COCs were generally not detected in the June 2004 groundwater samples (see Figure 12) collected at monitoring location MW-31 where the PLFA level decreased.
- The highest biomass (PLFA) levels continue to be at monitoring locations TW-02R (Area 2) and MW-8S (Area 3), where the relatively higher concentrations of COCs have been detected (see Figures 6 and 9).
- In general, the levels of anaerobic bacteria in each of the three Areas have increased or remained the same since the previous sampling event.
- The PLFA data used to monitor environmental stress and turnover rate indicate that the microbial communities within Areas 1, 2, and 3 are undergoing limited stress and continue to have high turnover rates.
- PHA was not detected in any of the June 2004 groundwater samples collected from Areas 1, 2, and 3 suggesting there are sufficient carbon, electron acceptors, and nutrients to sustain microbial activity within these three areas.

- Consistent with the activities conducted during the previous biannual sampling event (October 2003), the groundwater samples were analyzed for ammonia, potassium, and ortho-phosphate to better evaluate the availability of macronutrients necessary for biological growth in each of the three Areas (see Table 2). The results of these additional analyses and the PHA/PLFA data indicate that there are sufficient amounts of macronutrients available within each Area to sustain microbial growth.
- Dissolved gases results, together with ORP data, continue to indicate that conditions in the saturated soils/groundwater of the shallow hydrogeologic unit within each area are reduced, thus conducive to anaerobic bioremediation processes.
- The biological data (i.e., microbial analytes, indicator compounds, and permanent gases) obtained since commencement of the in-situ anaerobic treatment program in 1998 indicate that the saturated soil/groundwater conditions within the shallow hydrogeologic unit within each area are consistently conducive to microbial degradation of the COCs by anaerobic microbial populations. Additionally, these data have consistently confirmed that there are sufficient carbon, electron acceptors, and nutrients to sustain microbial activity with each of the three areas.
- Common biological indicators were measured in groundwater samples collected from the four "sentinel" monitoring wells (MW-29, MW-30, MW-33, and MW-36) (see Table 2 and Figure 1). These results are consistent with previous sampling events and indicate no appreciable increase in RAMM constituents downgradient of each area.

#### **IV. COC Process Control and Biannual Groundwater Monitoring Program**

The COC process control and biannual groundwater monitoring activities were conducted on June 14, 2004 through June 18, 2004, in accordance with the long-term COC process control monitoring program presented in the O&M Plan. The existing monitoring wells and piezometers that were used to conduct the long-term process control monitoring program and a schedule for implementing this program were provided in the previous biannual progress report. The monitoring locations are shown on Figure 1.

In accordance with the requirements of the NYSDEC-approved monitoring program, laboratory analytical results for the June 2004 samples were validated. A summary of the validated COC groundwater analytical results is presented in Table 3 and shown on Figures 12 and 13. Copies of the validated analytical laboratory reports associated with the June 2004 sampling event are provided under separate cover. A summary of the COC analytical results is provided below for each of the three areas, and the downgradient perimeter monitoring locations. The presence or absence of non-aqueous phase liquid (NAPL) was also assessed in existing monitoring wells and piezometers during the process control monitoring event. NAPL was not identified in any of the monitoring wells or piezometers used during the process control monitoring program, except at MW-8S where approximately 0.01 foot of LNAPL was measured. Supplemental remedial activities were conducted in the area of MW-8S, as discussed in Section V.

#### **Area 1**

- As shown on Figure 12, the concentrations of most COCs detected in the groundwater samples collected from the monitoring locations within Area 1 during the June 2004 sampling event declined or remained relatively the same during implementation of the in-situ anaerobic bioremediation treatment program. Overall, the COC concentrations detected in groundwater samples collected from monitoring wells within Area 1 were generally low.

- The highest COC concentrations within Area 1 historically have been detected in groundwater samples collected from MW-32 and TW-01. The COC concentrations in the June 2004 groundwater samples collected from these wells ranged between not detected to just slightly above their respective groundwater standards. These data demonstrate a significant decrease in COC concentrations since commencement of the in-situ anaerobic bioremediation treatment program. For example, the aniline concentration detected at MW-32 was 6,300 ppb in September 1998, but aniline has not been detected above the NYSDEC Groundwater Quality Standard at this location since May 2003. Similarly, the aniline concentration detected at TW-01 in February 1999 was 9,000 ppb, but aniline has not been detected above the NYSDEC Groundwater Quality Standard of 5 ppb since October 2002 and the highest concentration detected since September 2000 was 15 ppb.
- In the groundwater sample collected from monitoring well MW-31 (approximately in the center of Area 1) during the June 2004 sampling event, COC concentrations ranged between not detected to an estimated 15 ppb (acetone). The acetone concentration decreased from 1,200 ppb in October 2003 to below the NYSDEC Groundwater Quality Standard in June 2004. The June 2004 acetone concentration is consistent with the concentrations detected in groundwater samples collected from MW-31 prior to October 2003 (see Figure 12). As noted in previous biannual reports, acetone is a common laboratory contaminant.
- The June 2004 COCs analytical data obtained for the monitoring well located immediately downgradient of Area 1 (MW-33) are relatively consistent with previous data collected since March 2001, including the aniline concentration of 2,700 ppb (Figure 12). Due to the aniline concentrations detected at MW-33, supplemental remedial activities were conducted in this area, as further discussed in Section V.

## Area 2

- As shown on Figure 12, most COC concentrations detected within Area 2 during the June 2004 sampling event have decreased or remained relatively the same during implementation of the in-situ anaerobic bioremediation treatment program. The COC concentrations detected in groundwater samples collected from monitoring wells within Area 2 were generally low, with the exception of TW-02R. Monitoring well TW-02R is located within Area 2 at a location identified as containing relatively higher concentrations of COCs (see Figure 12) and has typically exhibited the higher concentrations in Area 2 of N,N-dimethylaniline, methylene chloride, and aniline. The N,N-dimethylaniline and methylene chloride concentrations have significantly decreased since 1998: from 61,000 ppb and 86,000 ppb (September 1998), respectively, to not detected and an estimated 4 ppb (June 2004), respectively. The aniline concentrations detected at TW-02R, however, have remained relatively consistent since commencement of the in-situ anaerobic bioremediation treatment activities, including the 82,000 ppb concentration of aniline detected during June 2004. As further discussed in Section V, supplemental remedial activities were conducted at the TW-02R location due to these aniline detections.
- In the groundwater sample collected from monitoring well MW-36 (located downgradient of Area 2) during the June 2004 sampling event, only aniline and N,N-dimethylaniline were detected at concentrations greater than their respective NYSDEC Groundwater Quality Standard. Aniline and N,N-dimethylaniline were detected in June 2004 at concentrations of 33 ppb and 7 ppb, respectively, which are consistent with previous concentrations detected at MW-36 and are just slightly greater than the respective NYSDEC Groundwater Quality Standard. The acetone concentration decreased from 580 ppb in October 2003 to below the NYSDEC Groundwater Quality Standard in June 2004 (22 ppb). As previously mentioned, acetone is a common laboratory contaminant.

### Area 3

- As presented on Figure 13, the concentrations of most COCs that were previously detected at Area 3 monitoring locations above their respective NYSDEC Groundwater Quality Standards have decreased or remained relatively the same during the implementation of the in-situ anaerobic bioremediation treatment program.
- At monitoring well MW-8S, located in the center of Area 3 and within the area that has been identified as containing relatively higher concentrations of COCs (see Figure 13), the concentrations of COCs detected in June 2004 are relatively consistent with those detected since commencement of the in-situ bioremediation treatment activities in 1998, with the exception of aniline. Since commencing the treatment activities, the concentrations of aniline have generally increased: 1,200 ppb aniline was detected in September 1998 compared to 56,000 ppb in June 2004. Prior to starting the in-situ anaerobic treatment activities, much greater COC concentrations were detected at this location, including 7,700,000 ppb of methylene chloride in August 1995 compared to 1,200,000 ppb detected in June 2004. As further discussed in Section V, supplemental remedial activities were conducted at the MW-8S location due to the aniline and methylene chloride concentrations.
- At monitoring well MW-28, also located within Area 3 and the area of relatively higher concentrations of COCs, the methylene chloride concentrations detected in groundwater samples have decreased from 64,000 ppb (September 1998) to generally non-detect. Methylene chloride has only been detected once at MW-28 since October 2002 (May 2003 groundwater sample, 52 ppb methylene chloride). Since commencement of the in-situ anaerobic bioremediation treatment program in 1998, aniline concentrations have remained relatively consistent, including the aniline concentration of 910 ppb detected in June 2004. The other COCs have generally been not detected in groundwater samples collected at this location or detected at concentrations just slightly greater than their respective NYSDEC Groundwater Quality Standard. Based on these aniline detections, supplemental remedial activities were conducted at this location, as discussed in Section V.
- The aniline concentration detected in the groundwater sample collected from monitoring well MW-27 in June 2004 is the same as that detected in October 2003 (3,700 ppb). The other COCs detected in the groundwater sample collected from MW-27 in June 2004 were at relatively low concentrations, including acetone and methylene chloride. The COC concentrations ranged from not detected to 20 ppb (N,N-dimethylaniline), which is consistent with concentrations detected since the implementation of the in-situ anaerobic treatment program in 1998. Acetone and methylene chloride concentrations decreased from 170 ppb and 240 ppb (October 2003), respectively, to an estimated 23 ppb and not detected (June 2004), respectively. The June 2004 acetone concentration of 23 ppb does not exceed the NYSDEC Groundwater Quality Standard. Due to the aniline detections, supplemental remedial activities were conducted at this location, as further discussed in Section V.

### Downgradient Perimeter Monitoring Locations

- As presented on Figure 13, COCs were not detected at downgradient perimeter monitoring locations above their respective NYSDEC Groundwater Quality Standards, except for benzene at MW-17R, which is hydraulically influenced by the Area 3 closed-loop hydraulic cell. The June 2004 COC results are consistent with the previous results obtained prior to October 2003. The October 2003 aniline and/or N,N-dimethylaniline concentrations detected above their respective NYSDEC Groundwater Quality Standards at downgradient perimeter monitoring locations MW-19, MW-23S, MW-24SR, and PZ-5D are inconsistent with the previous data at these locations and are considered anomalous.

- The aniline and N,N-dimethylaniline non-detect results for MW-18 were rejected during the validation process due to the deviation from a surrogate recovery that was below 10 percent. Aniline and N,N-dimethylaniline have consistently not been detected at MW-18; therefore, this location was not resampled.

#### V. Supplemental Remedial Activities

To enhance the overall remediation of OU No. 2, the supplemental remedial activities described in the June 2004 biannual report were conducted by BBL Environmental Services, Inc. (BBLES) between August 2 and August 12, 2004 to further address the relatively higher concentrations of COCs consistently detected in groundwater samples collected from monitoring wells MW-8S (Area 3) and TW-02R (Area 2). Additionally, supplemental remedial activities were also conducted immediately downgradient of Area 1 (near monitoring well MW-33) and in the vicinity of monitoring wells MW-27 and MW-28 (Area 3) to address the aniline concentrations detected at these locations. Mr. Chris Mannes of the NYSDEC was onsite August 5, 6, 9, and 10, 2004 during the supplemental remedial activities being conducted near MW-8S and TW-02R.

As detailed below the supplemental remedial activities consisted (in general) of the following activities:

- Well removal/abandonment to allow for soil removal activities in the areas of MW-8S and TW-02R;
- Soil removal in the areas of MW-8S, MW-27, and TW-02R;
- Soil amendment in the area of MW-28; and
- Replacement monitoring well and well point installation for conducting groundwater monitoring and monthly additions of RAMM and Suga-Lik™, respectively.

The supplemental remedial activities were conducted in accordance with the procedures and requirements set forth in the site-specific December 2003 *Health and Safety Plan* (HASP). The NYSDEC-approved August 1999 *Site Operation and Maintenance Plan* included a HASP, which was updated for the December 2003 HASP. The updates generally included the addition of mosquito borne diseases as biological hazards and the addition of benzene as a parameter in the Airborne Contaminant Action Level Table for air monitoring requirements. Daily safety meetings were held to cover the work to be accomplished, the hazards anticipated, the protective clothing and procedures required to minimize site hazards, and emergency procedures. During all intrusive subsurface activities, air monitoring was conducted in the worker breathing zone and at the work area perimeter by BBLES in accordance with the HASP. Air monitoring was conducted using an HNU photoionization detector (PID) for organic vapors; a MiniRAM portable dust monitor for total particulates; and a multiple gas monitor for oxygen, carbon monoxide, and flammable vapors or lower explosive limit (LEL). Air monitoring results indicated that the minimum action levels for these parameters, as set forth in the HASP, were not exceeded during the supplemental work.

A detailed description of the supplemental remedial activities is provided below.

#### Well Removal/Abandonment

Two shallow monitoring wells (MW-8S and TW-02R) were removed by Parratt-Wolff, Inc. (Parratt-Wolff) on August 3, 2004 and August 5, 2004, respectively, to allow for soil removal activities (discussed below). The locations of MW-8S and TW-02R are identified on Figures 14A and 14B. A 4.25-inch inside-diameter (i.d.) hollow-stem auger (HSA) was used to overdrill and remove monitoring wells MW-8S and TW-02R. A 12-inch outside-diameter (o.d.) HSA was then advanced to a depth of 20 feet bgs to remove soil that had surrounded MW-8S and TW-02R. The boreholes were backfilled with approximately 6 inches of bentonite, which was covered with imported clean material (pea stone) and amended with RAMM. An approximate 1-foot thick lift of bentonite was placed at the top of the upper silt/clay layer and additional pea stone was placed to a depth of approximately 3 feet bgs.



In addition, Parratt-Wolff abandoned deep monitoring well MW-8D on August 3, 2004, as it was adjacent to MW-8S. MW-8D was overdrilled with a 4.25-inch i.d. HSA and was grouted with cement/bentonite grout up to the shallow hydrogeologic unit (approximately 16 feet bgs) and the remaining depth was backfilled similar to MW-8S and TW-02R, as described above. The drill cuttings were collected and containerized in lined roll-offs, characterized, and properly disposed of offsite in accordance with applicable rules and regulations, as further discussed below.

### **Soil Removal in the Areas of MW-8S, MW-27, and TW-02R**

As part of the supplemental remedial activities proposed in the June 2004 biannual report, soil was removed near shallow monitoring wells MW-8S (Area 3) and TW-02R (Area 2). Between August 5, 2004 and August 9, 2004, a 12-inch o.d. HSA was used to remove soil from seven locations near monitoring well TW-02R to a depth of approximately 20 feet bgs. The approximate locations of the seven borings around TW-02R are shown on Figure 14A. This depth below grade is the total depth of monitoring well TW-02R, and is above the silt and clay layer underlying the shallow hydrogeologic unit. Approximately 6 cubic yards of soil were removed from an approximate 8-foot diameter area surrounding monitoring location TW-02R, with the exception of one boring, which was located approximately 6 feet downgradient of the original location of TW-02R. The boreholes were backfilled in the same manner as the boreholes of removed monitoring wells MW-8S and TW-02R described above.

Due to field conditions, a 12-inch o.d. HSA did not effectively remove the soils around MW-8S; therefore, on August 6, 2004 an excavator was used to excavate an area near that well. The approximate location of the excavation area around MW-8S is shown on Figure 14B. The excavation area was approximately 18 feet long by 7 feet wide and the depth of the excavation area was approximately 20 feet at its deepest point (i.e., excavation area was deepest in the center and became shallower towards the sides). This depth below grade is the total depth of monitoring well MW-8S, and is above the silt and clay layer underlying the shallow hydrogeologic unit. Approximately 65 cubic yards of soil were removed from the area surrounding monitoring location MW-8S. The top approximate 6 feet bgs near MW-8S was included in the OU No. 1 remedial activities and therefore the top 6 feet of soil was stockpiled, so it could be placed back into the excavated area. The soil removal area was backfilled with RAMM amended clean material (pea stone) to approximately 7 feet bgs, which was covered with an approximate 1-foot thick lift of a mixture of bentonite and RAMM amended pea stone. The stockpiled soil and additional imported clean fill were placed on top of the bentonite/pea stone mixture.

On August 9, 2004 soil was removed near monitoring well MW-27 and disposed of offsite instead of being amended with RAMM and Suga-Lik™ and placed back in the boreholes, as was proposed in the June 2004 biannual report. Similar to the soil removal activities conducted around TW-02R, a 12-inch o.d. HSA was used to remove approximately 1 cubic yard of soil from two locations near MW-27 to a depth of approximately 20 feet bgs. The approximate soil removal locations in the vicinity of MW-27 are shown on Figure 14B. The boreholes were backfilled in the same manner as the boreholes of removed monitoring wells MW-8S and TW-02R described above, except the pea stone was amended with Suga-Lik™ in addition to RAMM.

The drill cuttings and excavated soil generated during the soil removal activities were handled and disposed of in the same manner as drill cuttings generated during the well removal/abandonment activities described above. The roll-offs were covered at the end of the workday, during precipitation events, and after filling.

Two composite waste characterization samples were collected on August 19, 2004 from the soil contained in the roll-offs. These samples were submitted to Phoenix Environmental Laboratories, Inc. of Manchester, Connecticut for the following analyses:

- Toxicity Characteristic Leaching Procedure (TCLP) Metals by United States Environmental Protection Agency (USEPA) Method 1311 and 6000/7000 Series Methods;
- TCLP volatile organic compounds (VOCs) by USEPA Methods 1311 and 8260;
- TCLP semi-volatile organic compounds (SVOCs) by USEPA Methods 1311 and 8270;
- TCLP Pesticides and Herbicides by USEPA Methods 1311, 8081, and 8150;
- PCBs by USEPA Methods 3545-3550 and 8082;
- Ignitability by USEPA Method 1010;
- Reactivity Sulfide and Cyanide by USEPA Method 7.3; and
- Corrosivity by USEPA Methods 423/150.1.

A copy of the analytical data package for the waste characterization samples is provided in Attachment 1. The analytical results of the waste characterization samples indicated that the excavated soil does not exhibit hazardous characteristics. The soil contained in the lined roll-offs was transported to CWM Chemical Services, LLC in Model City, New York by Hazmat Environmental Group Inc. on October 5 and 7, 2004. Copies of the completed waste manifests (04001 through 04004) and corresponding bills of lading are provided in Attachment 2.

#### **Soil Amendment in the Area of MW-28**

As proposed in the June 2004 biannual report, the soil in the vicinity of monitoring well MW-28 was amended on August 4, 2004 by advancing a 12-inch o.d. HSA to a depth of approximately 20 feet and adding RAMM and Suga-Lik™ into the subsurface at two locations (approximate locations shown on Figure 14B). The two boreholes were backfilled with approximately 6 inches of bentonite, which was covered with the drill cuttings (soil) from these boreholes, amended with RAMM and Suga-Lik™. The drill cuttings were backfilled (returned) into their respective borehole to the depths they were removed from (e.g., soil removed from the bottom of the borehole was returned to the bottom of the borehole). Any drill cuttings not returned to the boreholes were managed and disposed of with the soil removed from the areas surrounding monitoring locations MW-8S and MW-27 (discussed above). An approximate 1-foot thick lift of bentonite was placed at the top of the upper silt/clay layer and additional drill cuttings were placed to the top of the boreholes.

#### **Replacement Monitoring Well and Well Point Installations**

Parratt-Wolff installed replacement monitoring wells (MW-8SR and TW-02RR) for abandoned monitoring wells TW-02R and MW-8S on August 10, 2004 at the approximate locations shown on Figures 14A and 14B, respectively. The replacement wells were constructed similar to their respective previously existing monitoring wells, and these locations will continue to be sampled biannually for COCs as part of the Process Control Monitoring Program. The well construction logs for these two replacement wells are provided in Attachment 3. MW-8D was not replaced, as identified in the previous biannual report (June 2004) the hydraulic data obtained over the 6-year operating history of the treatment system in Area 3 consistently indicated no discernable effect on the hydraulic gradient of the deep hydrogeologic unit. The newly installed wells were appropriately developed after installation.

In addition, eight well points were installed at the site to allow for monthly additions of RAMM and Suga-Lik™ (approximate locations are shown on Figures 14A and 14B). Six well points (WP-1 through WP-3 and WP-6 through WP-8) were installed in the shallow hydrogeologic unit around both monitoring wells MW-28 and MW-27 (Area 3) on August 4, 2004 and August 10 and 11, 2004, respectively. Two well points (WP-4 and WP-5) were also installed on August 9, 2004 in the shallow hydrogeologic unit around MW-33 instead of amending soil around MW-33 with RAMM and Suga-Lik™ as was proposed in the June 2004 biannual report. The well points were constructed of a 1-inch diameter black iron riser approximately 10 feet in length joined to a 10-foot stainless steel screened (slotted) interval at the bottom of the well point. The well construction logs for these eight well points are also provided in Attachment 3. The monthly additions of RAMM and Suga-Lik™ at these eight new well points began in September 2004 and are anticipated to enhance the anaerobic biodegradation of the aniline present in the shallow hydrogeologic unit at these locations.

## VI. Conclusions

The process control monitoring data presented in this Biannual Report will continue to be used to monitor the effectiveness of the in-situ anaerobic bioremediation treatment program. The conclusions presented below are based on the process control monitoring data obtained to date.

- A closed loop hydraulic cell continues to be maintained in Area 3.
- Operation of the Area 3 treatment system has not caused the freshwater/saltwater interface to upcone to the base of the withdrawal trench.
- The biological data obtained since commencement of the in-situ anaerobic bioremediation treatment program since 1998 have consistently verified that the saturated soil/groundwater conditions within the shallow hydrogeologic unit at Areas 1, 2, and 3 have been and continue to be conducive to degradation of the COCs by anaerobic microbial populations. Additionally, these data have consistently confirmed that there are sufficient carbon, electron acceptors, and nutrients to sustain microbial activity in each of the three areas.
- Aniline and N,N-dimethylaniline were not detected above the NYSDEC Groundwater Quality Standards at the perimeter sampling locations in June 2004, which is consistent with perimeter groundwater data obtained prior to October 2003 (in some cases since 1989). The aniline and/or N,N-dimethylaniline detections at concentrations above their respective NYSDEC Groundwater Quality Standards obtained during the October 2003 sampling event at downgradient perimeter monitoring locations MW-19, MW-23S, MW-24SR, and PZ-5D are inconsistent with the previous data at these locations and are considered anomalous.
- The COC concentrations detected in the groundwater samples collected from Area 1 since the in-situ anaerobic treatment program began in 1998 have generally decreased to or remained at concentrations ranging from not detected to just slightly greater than their respective NYSDEC Groundwater Standard. The data obtained from the monitoring locations within Area 1 demonstrate a significant decrease in COC concentrations since commencement of the in-situ anaerobic bioremediation treatment program.
- The aniline concentration detected in June 2004 (2,700 ppb) in the groundwater sample collected from the monitoring well located immediately downgradient of Area 1 (MW-33) remained generally consistent with the concentrations detected since March 2001. Based on these aniline concentrations, two well points were installed during the supplemental remedial activities in the vicinity of MW-33 to be used for monthly RAMM and Suga-Lik™ amendment activities. These activities started in September 2004.

- The COC concentrations within Area 2 have decreased or remained relatively the same during implementation of the in-situ anaerobic treatment program, with the exception of the aniline concentrations detected at monitoring location TW-02R. The data obtained from TW-02R demonstrate a significant decrease in N,N-dimethylaniline and methylene chloride concentrations since commencement of the in-situ anaerobic bioremediation treatment program. The aniline concentrations detected in groundwater samples collected from TW-02R increased from 38,000 ppb in September 1998 to 82,000 ppb in June 2004.
- The concentrations of most COCs that have been detected at Area 3 monitoring locations above their respective NYSDEC Groundwater Quality Standard have decreased or remained relatively the same since commencement of the in-situ anaerobic bioremediation treatment program in 1998. However, during the same time period aniline concentrations detected at monitoring location MW-8S increased from 1,200 ppb in September 1998 to 56,000 ppb in June 2004.
- The concentrations of methylene chloride and aniline at MW-8S and aniline concentrations at TW-02R have remained significantly higher than their respective NYSDEC Groundwater Quality Standard since commencement of the in-situ anaerobic bioremediation treatment activities, even with relatively high levels of biomass present. The relationship between relatively high COC concentrations and biomass levels suggest anaerobic biological processes were active, but may not have been efficiently removing COC mass at these two locations. In August 2004, approximately 70 cubic yards of soil were removed and disposed of offsite as part of the supplemental remedial activities conducted in the vicinity of MW-8S and TW-02R to enhance ongoing anaerobic bioremediation activities. The supplemental remedial activities also included the addition of RAMM amended pea stone to these soil removal areas.
- Since the commencement of the in-situ anaerobic bioremediation treatment activities, the aniline concentrations at MW-27 have increased and have consistently been relatively high at MW-28. Based on these aniline concentrations, approximately 1 cubic yard of soil was removed from the vicinity of MW-27 for offsite disposal and RAMM and Suga-Lik™ amended pea stone was added to this soil removal area as part of the supplemental remedial activities conducted to enhance ongoing remediation activities. In addition, RAMM and Suga-Lik™ was added to soil from two locations in the vicinity of MW-28 to supplement (enhance) ongoing remediation activities. Also, as part of the supplemental remedial activities, six well points were installed around MW-27 and MW-28 to be used for monthly RAMM and Suga-Lik™ amendments activities, which started in September 2004.

### **VII. Recommendations**

Based on the process control monitoring data obtained to date and the conclusions summarized above, the addition of RAMM and/or Suga-Lik™ in each of the three areas and the hydraulic control activities in Area 3 will continue to be implemented consistent with the operation procedures followed since January 2002 and described in Section I. Monthly additions of RAMM and Suga-Lik™ began in September 2004 at the eight new well points (WP-1 through WP-8) installed near MW-27 and MW-28 (Area 3), and MW-33 (downgradient of Area 1).

As discussed in this report and summarized in Table 4, the ongoing monitoring activities conducted at the site are included in the Biannual Groundwater Monitoring Program and the Process Control Monitoring Program. The activities included in the Biannual Groundwater Monitoring Program will continue, and include the biannual collection of chemical and hydraulic data from downgradient perimeter wells/piezometers to determine whether or not groundwater that contains concentrations of COCs in excess of their respective NYSDEC Groundwater Quality Standard is migrating beyond the site boundary. The Process Control Monitoring Program has consisted of collecting COC, microbiological, and hydraulic groundwater data on a biannual basis to assess the effectiveness of the in-situ anaerobic bioremediation activities.

Changes to the Process Control Monitoring Program were proposed in the June 2004 Biannual Report and were anticipated to be implemented during the second reporting period of 2004. Based on your November 1, 2004 conversation with BBL (Cathy Geraci), the Process Control Monitoring Program during the second reporting period of 2004 has been implemented consistent with the monitoring procedures followed since October 2002 (summarized in Table 4). BBL understands that the NYSDEC is evaluating the proposed revised Process Control Monitoring Program and will have a decision in the near future. The proposed revised Process Control Monitoring Program is detailed in Table 5 and the proposed changes (as well as the basis for the change) are summarized below.


- The biological data (i.e., microbiological analytes, indicator compounds, and permanent gases) obtained during the 6 years since commencement of the in-situ anaerobic bioremediation treatment program have consistently verified that the saturated soils/groundwater of the shallow hydrogeologic unit within each area are conducive to anaerobic bioremediation. Additionally, these data have consistently confirmed that there are sufficient carbon, electron acceptors, and nutrients to sustain microbial activity in each of the three areas. Because the biological data in each of the three areas have been consistent, the biological monitoring activities are proposed to be eliminated from the Process Control Monitoring Program.
- The COC sampling schedule is proposed to be changed from biannual to annual at upgradient monitoring location MW-1 and monitoring locations MW-3S, MW-9S, MW-29, MW-30, and MW-34, due to the consistent concentrations of COCs detected below or slightly higher than the NYSDEC Groundwater Quality Standards at these monitoring locations.
- The COC sampling at monitoring location TW-01 is proposed to be discontinued because of the low COC concentrations detected since September 2000 and its close proximity to MW-32. The COC concentrations detected at these two locations in Area 1 have been similar over the past 6 years, except that aniline has consistently been detected at higher concentrations in groundwater samples collected from MW-32 since March 2000. Monitoring well MW-32 has been and will continue to be sampled biannually under the Process Control Monitoring Program.

The second 2004 biannual monitoring event was conducted between November 1, 2004 and November 5, 2004. Consistent with the previous sampling events, BBL coordinated the schedule of the sampling event with you and Mr. Chris Mannes (NYSDEC - Region 7 Office). A summary of the O&M activities and the results of the process control monitoring activities will continue to be presented to the NYSDEC on a biannual basis.

Prior to coordinating the schedule for the first sampling event in 2005, BBL will follow up with you regarding NYSDEC's approval of the proposed changes for the Process Control Monitoring Program. In the interim, if you have any questions or require additional information, please do not hesitate to contact me or Cathy Geraci at (315) 446-9120.

Sincerely,

BLASLAND, BOUCK & LEE, INC.

  
David J. Ulm  
Senior Vice President

CWS/jlc  
Attachments

cc: Mr. Jim Burke, P.E., New York State Department of Environmental Conservation  
Mr. Gerald J. Rider, Jr., New York State Department of Environmental Conservation  
Mr. Chris Mannes, New York State Department of Environmental Conservation  
Ms. Henriette Hamel, R.S., New York State Department of Health  
Ms. Jean A. Mescher, McKesson Corporation  
Mr. Christopher R. Young, P.G., de maximis, inc.



Table 2

**Biological Monitoring Data**  
6/14 - 6/18/04

**McKesson Envirosystems**  
**Former Bear Street Facility**  
**Syracuse, New York**

Monitoring Location	Biological Parameters																					
	PLFA (Pmol/mL)	PHA (Pmol/mL)	Turnover Rate	Environmental Stress	Nitrate (mg/L)	Nitrogen (mg/L)	Total Fe (mg/L)	Dissolved Fe (mg/L)	Total Mn (mg/L)	Dissolved Mn (mg/L)	Sulfate (mg/L)	Sulfide (mg/L)	Carbon Dioxide (mg/L)	Methane (mg/L)	Potassium (mg/L)	Ortho- Phosphate (mg/L)	Ammonia (mg/L)	pH	D.O. (mg/L)	Temp. (C)	ORP (mV)	Cond. (mS/cm)
<b>AREA 1</b>																						
MW-1	7	ND	0.20	0.11	<0.200	15	R	R	R	R	95.3	<2.00	32	0.000048	--	--	--	6.98	1.07	16.47	-53	1.19
TW-01	4	ND	0.12	0.07	<0.200	19	2.91	0.728	0.944	0.864	273	<2.00	98	0.56	7.59	0.95	1.14	6.92	0.35	11.73	-102	1.58
MW-31	1	ND	0.00	0.08	<0.400	8.7	6.70	0.706	1.80	1.56	43.6	<2.00	240	9.7	6.00	<0.04	1.57	6.92	0.43	14.16	-86	3.11
MW-32	1	ND	0.00	0.09	<0.200	19	4.09	1.09	1.05	1.08	275	<2.00	120	0.78	5.20	0.140	0.921	6.59	0.35	11.87	-104	1.78
MW-9S	27	ND	0.08	0.02	<0.400	12	11.3	3.47	1.66	1.59	24.8	<2.00	160	4.5	3.95	0.099	0.270	6.73	1.42	15.65	-126	1.96
MW-33	--	--	--	--	2.33	4.3	0.898	0.332	0.892	0.782	153	<2.00	420	12	8.88	0.18	0.392	6.32	0.33	15.30	-333	4.80
<b>AREA 2</b>																						
TW-02R	113	ND	0.07	0.04	<0.200	14	1.76 J	2.48 J	R	R	7.92	<2.00	240	6.8	9.80	0.13	77.9	6.74	0.49	13.51	-185	4.52
MW-34	4	ND	0.01	0.09	<0.200	12	6.62	1.11	8.18	0.860	14.1	<2.00	190	3.4	29.3	0.10	7.58	6.57	0.37	14.09	-177	2.20
MW-35	3	ND	0.14	0.09	<0.200	18	0.849	0.524	0.497	0.406	40.6	<2.00	79	0.0076	3.44	0.16	0.942	6.92	0.92	14.56	-67	0.83
MW-36	--	--	--	--	0.273	9.8	0.244	0.139	4.01	3.02	72.0	<2.00	310	4.7	22.6	0.69	18.1	6.64	0.75	13.95	-142	4.17
<b>AREA 3</b>																						
MW-3S	12	ND	0.18	0.08	0.465	15	3.15	1.90	2.64 J	3.21 J	9.08	<2.00	58	2.4	--	--	--	6.73	0.68	12.88	-114	0.47
MW-8S	192	ND	0.26	0.11	4.48	6.8	135	50.9	3.30	3.19	28.7	<2.00	630	6.9	14.70	0.98	272	6.05	0.69	14.03	-144	6.85
MW-27	3	ND	0.07	0.05	<1.00	13	20.8	2.84	1.03	0.978	24.7	<2.00	280	6.7	6.40	0.074	6.77	6.45	0.31	12.40	-268	3.30
MW-28	9	ND	0.18	0.11	<1.00	10	41.6	3.41	1.63	1.45	41.9	<2.00	300	5.2	5.77	<0.04	8.50	6.49	1.50	13.95	-118	3.81
MW-29	--	--	--	--	1.15	15	0.160	0.138	0.418	0.345	175	<2.00	120	2.8	9.10	0.08	0.821	6.71	0.25	13.51	-339	3.11
MW-30	--	--	--	--	1.26	18	0.267	0.146	0.166	0.0958	136	<2.00	120	2.4	8.40	0.16	0.768	6.79	0.25	11.80	-332	2.99

**Notes:**

1. PLFA = Phospholipid fatty acids.
2. PHA = Poly-b-hydroxy alkanooate.
3. Turnover Rate = The summation of cy17:0/16:1w7c plus cy19:0/18:1w7c.
4. Environmental Stress = The summation of 16:1w7/16:1w7c plus 18:1w7/18:1w7c.
5. Fe = Iron.
6. Mn = Manganese.
7. D.O. = Dissolved oxygen.
8. Temp. = Temperature.
9. ORP = Oxidation/reduction potential.
10. Cond. = Conductivity.
11. Pmol/mL = Picomoles per milliliter.
12. mg/L = Milligrams per liter.
13. C = Degrees Celsius.
14. mV = Millivolts.
15. mS/cm = Millisiemens per centimeter.
16. -- = Not measured.
17. < = Parameter was not detected at the listed limit.
18. J = Result is estimated, reported value is less than practical quantitation limit (PQL).
19. ND = Not detected.
20. R = The total iron and/or manganese detected at MW-1, TW-02R, and MW-3S were less than the concentrations of dissolved iron and/or manganese; based on the deviations these data were rejected or estimated accordingly.



Table 3

Summary of Historic Groundwater Monitoring Data

McKesson Envirosystems  
Former Bear Street Facility  
Syracuse, New York

Monitoring Well	Sampling Date	Screen Elev. (ft. AMSL) Top	Screen Elev. (ft. AMSL) Bottom	Acetone	Benzene	Toluene	Ethylbenzene	Xylene <sup>a</sup>	Methanol	Trichloroethene	Aniline	N,N-dimethylaniline	Methylene Chloride
MW-1	3/88	370.3	355.3	<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	1/89			<100	<1	<1	<1	<1	<1,000	<1	<11	<11	<1
	11/89			<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	11/90			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
	11/91			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
	11/92			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
	8/95			<1,000	<5	<5	<5	<5	<1,000	<5	<5	<10	<10
	9/98			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	3/00			0.7 JN	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	9/00			<10	<10	<10	<10	<10	<1,000 J	<10	<5	<10	<10
	3/01			8 J	<10 J	3 J	<10 J	5 J	<1,000	<10 J	<10 J	<10	<10 J
	9/01			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	10
	4/02			<10	<10	<10	<10	<10	<1,000 J	<10	<10	<10	<10
	10/02			<12	<5	<5	<5	<5	990 J	<5	<5	<5	<5
5/03			<25	<10	<10	<10	<20	<1,000	<10	<5	R	<10	
10/03			<12	<5	<5	<5	<10	<1,000	<5	<5	<5	<5	
6/04			<25	<5	<5	<5	<10	<1,000	<5	2 J	<5	<5	
MW-2S	3/88	368.1	353.1	<1,000	1,900	110	610	2,800	<1,000	<10	<10	<10	<10
	1/89			<1,000	2,000	65	330	1,200	<1,000	<10	<11	<11	<10
MW-3S	11/89			<1,000	1,800	<100	360	810	38,000	<100	<100	<100	<100
	3/88	365.1	350.1	<100	<1	<1	<1	<1	<1,000	50	<10	<10	110
	1/89			<10,000	<100	120	<100	<100	<1,000	1,100	<11	5,570	4,700
	11/89			<10,000	<100	<100	<100	<100	<1,000	100	<52	440	2,700
	11/91			2,900	10	10	4	31	<1,000	<10	790	170	<10
	8/95			<1,000	<5	<5	<5	<5	<1,000	<5	15	2 J	<10
	9/98			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	7/99			<10	1 J	0.7 J	<10	<10	<1,000	<10	9 J	<10	<10
	3/00			<10 J	<10	<10	<10	<10	<1,000 J	<10	<10	<10	<10
	9/00			<10 J	1 J	2 J	<10 J	<10 J	<1,000	<10 J	2 J	1 J	<10 J
	3/01			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	9/01			<10	3 J	8 J	1 J	2 J	<1,000 J	<10	690 D (69)	4 J	<10
	4/02			<12	<5	<5	<5	<10	370 J	<5	1.7 J	<5	<5
	10/02			<25	<10	<10	<10	<20	<1,000	<10	<5	R	<10
5/03			<12	<5	<5	<5	<10	<1,000	<5	<5	<5	<5	
10/03			<12	<5	<5	<5	<10	<1,000	<5	4 J	<5	<5	
6/04			6 J	<10	<10	<10	<20	<1,000	<10	0.8 J	<6	<10	
8/95	343.8	339	<1,000	<25 D	<25 D	<25 D	<25 D	<1,000	<25 D	1 J	5 J	200 D	
3/88	365.5	350.5	<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1	
1/89			<100	<1	<1	<1	<1	<1,000	<1	<11	19	280	
11/89			<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1	

Table 3

Summary of Historic Groundwater Monitoring Data

McKesson EnviroSystems  
Former Bear Street Facility  
Syracuse, New York

Monitoring Well	Sampling Date	Screen Elev. (ft. AMSL)		Acetone	Benzene	Toluene	Ethylbenzene	Xylene <sup>a</sup>	Methanol	Trichloroethene	Aniline	N,N-dimethylaniline	Methylene Chloride
		Top	Bottom										
MW-5 <sup>f</sup>	3/88	363.3	348.3	<100	<1	<1	<1	<1	<1,000	<1	230	130	<1
	1/89			<100	<1	<1	<1	<1	<1,000	<1	34	<11	<1
	11/89			<100	<1	<1	<1	<1	<1,000	<1	17	<10	<1
MW-6 <sup>c</sup> (Replaced by MW-6S)	1/89	365.5	355.9	<100	<1	<1	<1	<1	<1,000	<1	<11	<11	<1
	11/89			<10	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	8/95			<1,000	<5	<5	<5	<5	<1,000	<5	<5	<10	<10
MW-7 <sup>c</sup>	1/89	367	357.4	<100	<1	<1	<1	2	<1,000	<1	<11	<11	100
	11/89			<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
MW-8 <sup>c</sup> (Replaced by MW-8S) <sup>n</sup> (Replaced by MW-8SR)	1/89	364.7	355.1	<1,000,000	<10,000	<10,000	<10,000	<10,000	430,000	<10,000	2,900	24,000	3,200,000
	11/89			470,000	<10,000	<10,000	<10,000	<10,000	300,000	<10,000	8,500	52,000	2,800,000
	11/91			<1,000,000	<10,000	<10,000	<10,000	<30,000	150,000	<10,000	8,000	33,000	1,600,000
	8/95			<1,000	<250,000D	<250,000D	<250,000D	<250,000D	22,000	60,000 JD	<25,000D	380,000 D	7,700,000 D
	9/98			<10,000 J	<10,000	<10,000	<10,000	<10,000	7,900	3,300 J	1,200 J	26,000 D	140,000
	2/99			<20,000	<20,000	<20,000	<20,000	<20,000	16,000 JN	11,000 J	30,000 D	120,000 D	650,000 DB
	7/99			10 J	22 J	240 J	58 J	220 J	17,000	11,000 J	24,000	77,000	450,000 D
	3/00			<100,000	<100,000	<100,000	<100,000	<100,000	30,000 J	<100,000	62,000	270,000 D	1,300,000
	9/00			<50,000 J	<50,000 J	<50,000 J	<50,000 J	<50,000 J	14,000 J	9,200 J	42,000 J	59,000	540,000 BJ
	3/01			<50,000	<50,000	<50,000	<50,000	<50,000	53,000	11,000 J	90,000 D	120,000 D	990,000
	9/01			<400	<400	430	170 J	680	8,900 J	18,000 JD	21,000	29,000	440,000 BD
	4/02			2,100	50 J	410	100 J	400	<1,000	9,600 J	793,000 D	773,000 D	660,000 D
	10/02			120 J	23	310	73	267	<1,000	3,100	80,000	21,000 J	320,000
	5/03			<12	20 J	600 D	81	300	<1,000	6,700 D	79,000 D	29 J	910,000 D
	10/03			21	25	330 D	93	360	1,200 J	3,100 D	67,000 D	24,000 D	400,000 D
6/04	<25	40	330 F J	110	400	<1,000	5,900 D	56,000	51,000	1,200,000 D			
MW-9 <sup>c</sup> (Replaced by MW-9S)	1/89	365.6	356	1,600	NA	64	130	270	<1,000	<10	660	1,200	1,500
	11/89			<1,000	48	25	60	60	<1,000	<10	670	150	<10
	11/91			<100	<10	9	19	30	<1,000	<1	95	18	<1
	8/95			<1,000	11 JD	26 JD	69 D	226 JD	<1,000	<50	50	28	110 D
	7/99			<10	4 J	2 J	9 J	18	<1,000	<10	<10	5 J	<10
	3/00			<10	2 J	2 J	11	21	<1,000 J	<10	2 J	9 J	<10
	9/00			<10 J	11 J	2 J	6 J	18 J	<1,000	<10 J	1 J	6 J	<10 J
	3/01			<10	1 J	3 J	17	61	<1,000	<10	2 J	11	<10
	9/01			<10	10	3 J	7 J	35	<1,000 J	<10	<10	10	<10
	4/02			<23	10	2 J	6	17 J	370 J	<5	9	43	<5
	10/02			16 J	38	40	2 J	15 J	<1,000	<10	<5	2 J	<10
	5/03			<12	11	<5	7	18	<1,000	<5	0.9 J	3 J	<5
	10/03			<12	2 J	<5	5	19	<1,000	<5	1 J	<5	<5
6/04	14 J	6 J	2 J	8 J	19 J	<1,000	<10	<5	<5	<10			
MW-10 <sup>c</sup> (Replaced by MW-9D)	1/89	355.5	345.9	<1,000,000	<10,000	<10,000	<10,000	<10,000	210,000	<10,000	720	9,400	520,000
	11/89			<100,000	<1,000	<1,000	<1,000	<1,000	<1,000	<1,000	900	2,400	28,000
	11/91			<100	<1	3	2	<3	<1,000	<1	230	<10	41
	8/95			<1,000	<25 UD	<25 UD	<25 UD	<25 UD	<1,000	<25 UD	<5	<10	350 D

Table 3

## Summary of Historic Groundwater Monitoring Data

McKesson Envirosystems  
Former Bear Street Facility  
Syracuse, New York

Monitoring Well	Sampling Date	Screen Elev. (ft. AMSL)		Acetone	Benzene	Toluene	Ethylbenzene	Xylene <sup>a</sup>	Methanol	Trichloroethene	Aniline	N,N-dimethylaniline	Methylene Chloride	
		Top	Bottom											
MW-11 <sup>C</sup> (Replaced MW-6D)	1/89	355.1	345.5	<100	<1	<1	<1	<1	8,400	<1	<12	<12	1	
	11/89			<100	<1	<1	<1	<1	<1,000	<1	230	<52	<1	
	8/95			<1,000	<5	<5	<5	<5	<1,000	<5	<5	<10	<10	
MW-11S	12/94	359.9	354.9	<380	<10	<10	<10	<10	880	<10	<5	<10	<10	
	8/95			<1,000	<5	<5	<5	<5	<1,000	<5	<5	<10	<26	
	10/95			NA	<5	<5	<5	<5	NA	<5	NA	NA	<5	
MW-11D	12/94	349.8	344.8	<310	<5	<5	<5	<5	2,100	<5	<5	<10	<5	
	8/95			<1,000	<5	<5	<5	<5	<1,000	<5	<5	<10	<10	
	10/95			NA	<5	<5	<5	<5	NA	<5	NA	NA	<5	
MW-12D <sup>C</sup> (Replaced MW-8D) <sup>N</sup>	1/89	354.8	345.2	<100,000	<1,000	<1,000	<1,000	<1,000	12,000	<1,000	67	410	120,000	
	11/89			69,000	<1,000	<1,000	<1,000	<1,000	39,000	<1,000	<1,000	4,900	360,000	
	11/91			<1,000,000	<10,000	<10,000	<10,000	<30,000	<10,000	<10,000	<10,000	750	5,800	220,000
	8/95			<1,000	450 JD	450 JD	430 JD	1,250 JD	<1,000	<1,300 D	30 D	230 D	<13,000 D	
	8/96			13	<10	<10	<10	<10	<1,000	2 J	<5	<10	40	
MW-13S	11/89	368.7	359.1	<100	3	<1	<1	<1	<1,000	<1	<52	<52	<1	
	11/90			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1	
	11/91			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1	
	11/92			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1	
MW-14D <sup>F</sup>	1/89	359	349.4	<100	<1	<1	<1	<1	<1,000	<1	<11	<11	<1	
	11/89			<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1	
MW-15S	1/89	370	360.25	<100	<1	<1	<1	<1	<1,000	<1	<11	<11	<1	
	11/89			<100	<1	<1	<1	<1	<1,000	<1	<52	<52	<1	
MW-16D <sup>F</sup>	1/89	350.8	341.2	<100	<1	<1	<1	<1	<1,000	<1	<11	<11	<1	
	11/89			<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1	
MW-17 <sup>F</sup> (Replaced by MW-17R)	11/90	365.7	356.1	<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1	
	11/91			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1	
	11/92			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1	
	8/95			<1,000	<5	<5	<5	<5	<1,000	<5	<5	<10	<11	
	10/95			NA	<5	<5	<5	<5	NA	2 J	NA	NA	<5	
	8/96			11	<10	<10	<10	<10	<1,000	<10	<5	<10	<10	
	8/97			<10	<10	<10	<10	<10	<1,000	<10	<5	<10	<10	
	2/99			<10	1 J	<10	<10	<10	<1,000	<10	<10	<10	<10 J	
	3/00			<10	8 J	<10	<10	<10	<1,000 J	<10	<5	<10	<10	
	9/00			<10 J	15 J	<10 J	<10 J	<10 J	<1,000 J	<10 J	24 J	4 J	1 J	
	3/01			<10	8 J	<10	<10	<10	<1,000	<10	<10	<10	<10	
	9/01			<10	5 J	<10	<10	<10	<1,000	<10	<10	<10	<10	
	4/02			<10	6	<5	<5	<10	620 J	<5	150 (<5) <sup>b</sup>	110 (<5) <sup>b</sup>	<5	
	10/02			<25 J	14	<10	<10	<20	<1,000	<10	<5 <sup>L</sup>	<5 <sup>L</sup>	<10	
	5/03			<12	8	<5	<5	<5	<1,000	<5	<5	<5	<5	
	11/03			<12	7	<5	<5	<10	<1,000	<5	<5	<5	<5	
6/04	<25	5 J	<10	<10	<20	<1,000	<10	<5	<5	<10				

Table 3

Summary of Historic Groundwater Monitoring Data

McKesson Envirosystems  
Former Bear Street Facility  
Syracuse, New York

Monitoring Well	Sampling Date	Screen Elev. (ft. AMSL) Top	Bottom	Acetone	Benzene	Toluene	Ethylbenzene	Xylenes	Methanol	Trichloroethene	Aniline	N,N-dimethylaniline	Methylene Chloride
MW-18	11/89	325.15	316.15	<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	11/90			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
	11/91			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
	11/92			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
	12/94			<10	<5	<5	<5	<5	<200	<5	<5	<10	<5
	8/95			<1,000	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	2/96			<1,000	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	8/96			<10	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	2/97			<10	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	8/97			<10	<10	<10	<10	<10	<1,000	<10	<5 <sup>H</sup>	<10	<10
	9/98			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	2/99			<10 J	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	7/99			<10	<10	<10	<10	<10	<1,000 J	<10	<5	<10	<10
	3/00			<10	<10	<10	<10	<10	<1,000 J	<10 J	<5	<10	<10 J
	9/00			<10 J	<10 J	<10 J	<10 J	<10 J	<1,000 J	<10 J	<10 J	<10	<10 J
	3/01			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	9/01			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	4/02			<10	<10	<10	<10	<10	720 J	<10	280 J (<5) <sup>L</sup>	<5 <sup>L</sup>	<10
	10/02			6 J	<10	<10	<10	<10	<1,000	<10	<5 <sup>L</sup>	<5 <sup>L</sup>	<10
	5/03			<12	<5	<5	<5	<5	280 J	<5	<5	<5	<5
10/03			<12	<5	<5	<5	<5	<1,000	<5	0.7 J	<5	<5	
6/04			<25	<10	<10	<10	<10	<1,000	<10	R	R	<10	
MW-19	11/89	318.45	309.45	<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	12/94			<10	<5	<5	<5	<5	<200	<5	<5	<10	<5
	8/95			<1,000	<5	<5	<5	<5	<1,000	<5	<5	<10	<12
	10/95			NA	<5	<5	<5	<5	NA	<5	NA	NA	<5
	2/96			<1,000	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	8/96			<10	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	2/97			<10	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	8/97			<10	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	9/98			<10	<10	<10	<10	<10	<1,000	<10	<5 <sup>H</sup>	<5 <sup>H</sup>	<11
	2/99			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	7/99			<10 J	<10 J	<10 J	<10 J	<10 J	<1,000	<10 J	<10	<10	<10
	3/00			<10	<10	<10	<10	<10	<1,000 J	<10	<5	<10	<10 J
	9/00			<10 J	<10 J	<10 J	<10 J	<10 J	<1,000 J	<10 J	<10 J	<10	<10 J
	3/01			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	9/01			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	4/02			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
10/02			<25 J	<10	<10	<10	<10	<1,000	<5	<5 <sup>L</sup>	<5 <sup>L</sup>	<5	
5/03			<12	<5	<5	<5	<5	<1,000	<5	<5	<5	<5	
10/03			<11	<5	<5	<5	<5	<1,000	<5	51 J	16 J	<5	
6/04			<25	<10	<10	<10	<10	<1,000	<10	<5	<5	<10	

Table 3

## Summary of Historic Groundwater Monitoring Data

McKesson EnviroSystems  
Former Bear Street Facility  
Syracuse, New York

Monitoring Well	Sampling Date	Screen Elev. (ft. AMSL)		Acetone	Benzene	Toluene	Ethyl-benzene	Xylene <sup>A</sup>	Methanol	Trichloro-ethene	Aniline	N,N-dimethyl-aniline	Methylene Chloride
		Top	Bottom										
MW-20 <sup>F</sup>	11/89	329.85	320.85	<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	11/90			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
	11/91			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
	11/92			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
MW-21 <sup>F</sup>	11/89	323.65	314.65	<100	<5	<1	<1	<1	<1,000	<1	<10	<10	<1
MW-22	11/89	368.55	359.55	<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
MW-23S	12/94	364.1	354.1	<10	<5	<5	<5	<5	<200	<5	<5	<10	<5
	8/95			<1,000	<5	<5	<5	<5	<1,000	<5	<5	<10	<10
	2/96			<1,000	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	8/96			<10	<10	<10	<10	<10	<1,000	<10	7	<10	<10
	2/97			<10	<10	<10	<10	<10	<1,000	<10	11	<10	<10
	8/97			12	<10	<10	<10	<10	<1,000	<10	92	<10	<10
	9/98			<10	<10	<10	<10	<10	<1,000	<10	56 <sup>H</sup>	7 J	<10
	2/99			<10	<10	<10	<10	<10	<1,000	<10	<10	10	<10 J
	6/99			<10 J	<10	<10	<10	<10	<1,000 J	<10	<10 J	2 J	<10 J
	7/99			<10 J	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	3/00			<10	<10	<10	<10	<10	<1,000 J	<10	<5	2 J	<10
	9/00			<10 J	<10 J	<10 J	<10 J	<10 J	<1,000 J	<10 J	<10 J	2 J	<10 J
	3/01			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	9/01			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	4/02			<10	<5	<5	<5	<10	<1,000	<5	<5	<5	<5
	10/02			<25 J	<10	<10	<10	<20 J	<1,000	<10	<5 <sup>L</sup>	<5 <sup>L</sup>	<10
	5/03			<62	<25	<25	<25	<50	380 J	<25	<5	<5	<25
	10/03			<12	<5	<5	<5	<10	<1,000	<5	60	<5	<5
	6/04			<25	<10	<10	<10	<20	<1,000	<10	<5	<5	<10
	MW-23I			12/94	341.2	336.2	<10	<5	<5	<5	<5	<200	<5
8/95		<1,000	<5	<5			<5	<5	<1,000	<5	<5	<10	<10
2/96		<1,000	<10	<10			<10	<10	<1,000	<10	<5	<10	<10
8/96		<10	<10	<10			<10	<10	<1,000	<10	<5	<10	<10
2/97		<10	<10	<10			<10	<10	<1,000	<10	<5	<10	<10
8/97		<10	<10	<10			<10	<10	<1,000	<10	<5	<11	<10
9/98		<10	<10	<10			<10	<10	<1,000	<10	<5 <sup>H</sup>	<10	<10
2/99		<10	<10	<10			<10	<10	<1,000	<10	<10	<10	<10 J
7/99		<10 J	<10	<10			<10	<10	<1,000	<10	<10	<10	<10
3/00		<10	<10	<10			<10	<10	<1,000 J	<10	<5	<10	<10
9/00		<10 J	<10 J	<10 J			<10 J	<10 J	<1,000 J	<10 J	<10 J	<10	<10 J
3/01		<10	<10	<10			<10	<10	<1,000	<10	<10	<10	<10
9/01		4 J	<10	<10			<10	2 J	<1,000	<10	<10	<10	<10
4/02		<10	<5	<5			<5	<10	<1,000	<5	<5	<5	2 J
10/02		<25 J	<10	<10			<10	<20 J	<1,000	<10	<5 <sup>L</sup>	<5 <sup>L</sup>	<10
5/03		<12	<5	<5			<5	<5	<1,000	<5	<5	<5	<5
10/03		<12	<5	<5			<5	<10	<1,000	<5	<5	<5	<5
6/04		<25	<10	<10			<10	<20	<1,000	<10	1 J	<5	<10

Table 3

Summary of Historic Groundwater Monitoring Data

Mckesson Envirostystems  
Former Bear Street Facility  
Syracuse, New York

Monitoring Well	Sampling Date	Screen Elev. (ft. AMSL) Top Bottom	Acetone	Benzene	Toluene	Ethylbenzene	Xylene	Methanol	Trichloroethane	Aniline	N,N-dimethylaniline	Methylene Chloride
MW-24S <sup>f</sup> (Replaced by MW-24SR)	12/94	358.4	<10	<5	<5	<5	<5	<1,000	<5	<5	<10	<5
	8/95		<1,000	<5	<5	<5	<5	<1,000	<5	<5	<10	<10
	2/96		<1,000	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	2/97		<1,000	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	9/98		<10	<10	<10	<10	<10	<1,000	<10	<5 <sup>H</sup>	<10	<10
	6/99		<10 J	<10	<10	<10	<10	<1,000 J	<10	<10 J	<10 J	<10 J
	7/99		<10 J	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	3/00		<10 J	<10 J	<10 J	<10 J	<10 J	<1,000 J	<10 J	<10 J	<10 J	<10 J
	9/01		<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	6/02 <sup>k</sup>		NS	NS	NS	NS	NS	NS	NS	ND	ND	NS
	10/02		<25 J	<10	<10	<10	<10	<20 J	<1,000	<10	<5 <sup>L</sup>	<10
	10/03		<12	<5	<5	<5	<5	<10	<1,000	<5	<6	<5
	6/04		<25	<10	<10	<10	<10	<20	<1,000	<10	<5	<10
MW-24D <sup>f</sup> (Replaced by MW-24DR)	12/94	334.4	<10	<5	<5	<5	<5	<1,000	<5	<5	<10	<5
	8/95		<1,000	<5	<5	<5	<5	<1,000	<5	<5	<10	<10
	2/96		<1,000	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	2/97		<1,000	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	9/98		<10	<10	<10	<10	<10	<1,000	<10	<5 <sup>H</sup>	<10	<10
	7/99		<10 J	<10 J	<10 J	<10 J	<10 J	<1,000	<10 J	<10	<10	<10 J
	9/00		<10 J	<10 J	<10 J	<10 J	<1,000 J	<10 J	<10 J	<10 J	<10	<10 J
	9/01		<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	6/02 <sup>k</sup>		NS	NS	NS	NS	NS	NS	NS	ND	ND	NS
	10/02		<25 J	<10	<10	<10	<20 J	<1,000	<10	<5 <sup>L</sup>	<5 <sup>L</sup>	<10
	10/03		<12	<5	<5	<5	<10	<1,000	<10	<5	<5	<5
	8/95	356.2	<1,000	<5	<5	<5	<5	<1,000	<5	<5	<5	<10
	10/95		NA	<5	<5	<5	<5	NA	<5	<5	<10	<5
8/96		<10	<10	<10	<10	<10	<1,000	<10	<5	<10	<10	
8/97		<10	<10	<10	<10	<10	<1,000	<10	<5	<10	<10	
2/99		<10	<10	<10	<10	<10	<1,000	<10	<5	<10	<10	
6/99		<10 J	<10	<10	<10	<10	<1,000 J	<10	130	<10	<10 J	
7/99		<10 J	<10	<10	<10	<10	<1,000	<10	110 J	21 J	<10 J	
3/00		<10	<10	<10	<10	<10	<1,000	<10	5 J	<10	<10	
9/00		<10	<10	<10	<10	<10	<1,000 J	<10	<5	<10	<10	
3/01		<10 J	<10 J	<10 J	<10 J	<10 J	<1,000 J	<10 J	<10 J	<10	<10 J	
9/01		<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10	
4/02		<10	<5	<5	<5	<5	<1,000	<10	<10	<10	<10	
10/02		<25	<10	<10	<10	<20	<1,000	<10	<5	<5	<5	
5/03		<12	<5	<5	<5	<5	<1,000	<10	<5	<5	<5	
11/03		<12	<5	<5	<5	<10	<1,000	<10	<5	<5	<5	
6/04		<25	<10	<10	<10	<10	<20	<1,000	<10	<5	<5	

Table 3

## Summary of Historic Groundwater Monitoring Data

McKesson EnviroSystems  
Former Bear Street Facility  
Syracuse, New York

Monitoring Well	Sampling Date	Screen Elev. (ft. AMSL)		Acetone	Benzene	Toluene	Ethylbenzene	Xylene <sup>A</sup>	Methanol	Trichloroethene	Aniline	N,N-dimethylaniline	Methylene Chloride
		Top	Bottom										
MW-25D	8/95	349.55	344.55	<1,000	<5	<5	<5	<5	<1,000	<5	<5	1 J	<5
	10/95			NA	<5	<5	<5	<5	NA	3 J	<5	<10	<5
	8/96			15	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	8/97			<10	<10	<10	<10	<10	<1,000	<10	<5	<11	<10
	2/99			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10 J
	3/00			<10	<10	<10	<10	<10	<1,000 J	<10	<5	<10	<10
	3/01			<10	<10	<10	<10	<10	<1,000	<10	5 J	<10	<10
	4/02			<10	<5	<5	<5	<10	<1,000	<5	<5	<5	<5
	5/03			<12	<5	<5	<5	<5	<1,000	<5	<5	<5	<5
6/04	<25	<10	<10	<10	<20	<1,000	<10	<5	<5	<5			
MW-26	12/96	365	355.3	<10	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
MW-27	9/98	362.5	354.5	23	3 J	4 J	<10	3 J	<1,000	<10	340 DJ	<10	<10
	7/99			<10 J	4 J	2 J	3 J	8 J	<1,000	<10	740 D	<10	<10
	3/00			<10	6 J	<10	8 J	2 J	<1,000 J	<10	110 D	1 J	<10
	9/00			<10 J	4 J	<10 J	3 J	1 J	<1,000 J	<10 J	16 J	2 J	1 J
	3/01			<10	5 J	<10	5 J	2 J	<1,000	<10	260 D	2 J	<10
	9/01			<10	5 J	<10	2 J	<10	<1,000 J	<10	26	<10	<10
	4/02			<18	7	11	12	26	<1,000	<5	176,000 DJ	19 J	<5
	10/02			9 J	3 J	<10	<10	<20	<1,000	4 J	2,700 D	100 J	60 JN
	5/03			<12	8	11	23	51	<1,000	<5	15,000 DJ	11	43
	10/03			170	5	<5	<5	3 J	<1,000	<5	3,700 D	<5	240 D
6/04	23 J	5 J	4 J	2 J	6 J	<1,000	<10	3,700 D	20 J	<10			
MW-28	9/98	363.6	355.6	<5,000 J	<5,000	<5,000	<5,000	<5,000	2,200	<5,000	546 D <sup>H</sup>	54	64,000 J
	7/99			<500 J	<500	<500	<500	<500	<1,000	<500	1,100 D	40	39,000 D
	3/00			<10,000	<10,000	<10,000	<10,000	<10,000	<1,000 J	<10,000	1,300 D	30	130,000 J
	9/00			<1,000 J	<1,000 J	<1,000 J	<1,000 J	<1,000 J	<1,000 J	<1,000 J	540 DJ	<10	8,100 BJ
	3/01			<400	<400	<400	<400	<400	<1,000	<400	3,200 D	7 J	5,900 B
	9/01			<400	<400	<400	<400	<400	<1,000 J	<400	1,000 D	<10	4,700 B
	4/02			<49	8	6	9	10 J	<1,000	<5	33,400 D	57	4,600 D
	10/02			14 J	8 J	6 J	11	12 J	<1,000	<10	2,700 D	R	<10
	5/03			13	4 J	2 J	2 J	8 J	<1,000	<5	1,000 DJ	3 J	52
	10/03			24	11	6	12	13 J	<1,000	<5	1,900 D	<5	<5
6/04	20 J	4 J	2 J	5 J	4 J	<1,000	<10	910 D	<5	<10			

Table 3

Summary of Historic Groundwater Monitoring Data

McKesson Envirosystems  
Former Bear Street Facility  
Syracuse, New York

Monitoring Well	Sampling Date	Screen Elev. (ft. AMSL)		Acetone	Benzene	Toluene	Ethylbenzene	Xylene	Methanol	Trichloroethylene	Aniline	N,N-dimethylaniline	Methylene Chloride	
		Top	Bottom											
MW-29	9/98	362.9	345.9	<10	<10	<10	<10	2 J	<1,000	<10	<10	13	<10	
	2/99			7 J	<10	<10	<10	1 J	<1,000	<10	5 J	4 J	<10	
	7/99			<10	<10	<10	<10	<10	<1,000	<10	2 J	4 J	<10	
	3/00			<10	<10	<10	<10	<10	<1,000	<10	450 D	6 J	<10	
	9/00			<10 J	<10 J	<10 J	<10 J	<10 J	<1,000 J	<10 J	24 J	4 J	<10 J	
	3/01			<10	<10	<10	<10	<10	<1,000	<10	30	4 J	<10	
	9/01			<10	<10	<10	<10	<10	<1,000	<10	7 J	2 J	<10	
	4/02			<10	<5	<5	<5	<10	<1,000	<5	3 J	9	<6	
	10/02			<25 J	<10	<10	<10	<20	<1,000	<10	8	R	4 JN	
	5/03			<12	<5	<5	<5	<10	<1,000	<5	19	1 J	<3	
	10/03			<12	<5	<5	<5	<10	<1,000	<5	2 J	<5	<5	
	6/04			<25	<10	<10	<10	<20	<1,000	<10	3 J	<5	<10	
	MW-30	9/98	363.5	355.5	<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
		2/99			7 J	<10	<10	<10	<10	<1,000	<10	<10	2 J	<10
7/99				<10	0.7 J	<10	<10	<10	<1,000	0.5 J	<10	1 J	<10	
3/00				<10	<10	<10	<10	<10	<1,000	<10	18	2 J	4 J	
9/00				<10 J	<10 J	<10 J	<10 J	<10 J	<1,000 J	<10 J	9 J	2 J	2 J	
3/01				<10	<10	<10	<10	<10	<1,000	<10	8 J	2 J	<10	
9/01				4 J	2 J	<10	<10	<10	<1,000 J	<10	8 J	1 J	<10	
4/02				<10	<5	<5	<5	<10	<1,000	<5	250	210	<5	
10/02				<25 J	<10	<10	<10	<20 J	<1,000	<10	R	R	<10	
5/03				<62	<25	<25	<25	<50	<1,000	<25	18	0.6 J	8 J	
10/03				<12	<5	<5	<5	<10	<1,000	<5	4 J	<5	<5	
6/04				<25	<10	<10	<10	<20	<1,000	<10	<5	<5	<10	
MW-31		9/98	363.7	355.4	<10	12	<10	<10	<10	<1,000	<10	34	4 J	<10
		7/99			<10	16	<10	<10	<10	<1,000	<10	250 D	3 J	<10
	3/00			<10	16	<10	<10	<10	<1,000 J	<10	3 J	4 J	<10	
	9/00			<10 J	12 J	<10 J	<10 J	<10 J	<1,000	<10 J	10	6 J	<10 J	
	3/01			21	11	<10	<10	<10	<1,000	<10	<10	5 J	<10	
	9/01			<10	14	<10	<10	<10	<1,000 J	<10	91 D	3 J	<10	
	4/02			<14	9	<5	<5	<10	<1,000	<5	804 D	21	<5	
	10/02			<25	11	<10	<10	<20	<1,000	<10	560 D	1 J	<10	
	5/03			<12	9	<5	<5	<10	<1,000	<5	0.9 J	3 J	<5	
	10/03			1,200 D	13	<5	<5	<5	<1,000	<5	88	<5	<5	
	6/04			15 J	12	<10	<10	<20	<1,000	<10	3 J	<5	<10	
	MW-32	9/98	364	356	<10	16	2 J	5 J	3 J	<1,000	<10	6,300 D	4 J	<10
		7/99			3 J	14	2 J	4 J	<10	<1,000	56	<10	3 J	<10
		3/00			<10	5 J	<10	<10	<10	<1,000 J	<10	800 D	<10	<10
9/00				<10 J	12 J	<10 J	<10 J	<10 J	<1,000	<10 J	4,500 D	<10	<10 J	
3/01				<10	5 J	<10	<10	<10	<1,000	<10	1,900 D	2 J	<10	
9/01				<10	10	<10	<10	<10	<1,000 J	<10	1,100 D	2 J	<10	
4/02				<15	4 J	<5	<5	<10	<1,000	<5	4,620 D	11	<5	
10/02				<12	4 J	<5	<5	<10	<1,000	<10	50	R	<10	
5/03				<20	2 J	<5	<5	<10	<1,000	<5	0.6 J	0.7 J	<5	
10/03				6 J	1 J	<10	<10	<20	<1,000	<10	1 J	<5	<10	
6/04														



Table 3

Summary of Historic Groundwater Monitoring Data

McKesson EnviroSystems  
Former Bear Street Facility  
Syracuse, New York

Monitoring Well	Sampling Date	Screen Elev. (ft. AMSL)		Acetone	Benzene	Toluene	Ethylbenzene	Xylene <sup>A</sup>	Methanol	Trichloroethene	Aniline	N,N-dimethylaniline	Methylene Chloride
		Top	Bottom										
MW-36	9/98	363.6	355.6	<10	<10	<10	<10	<10	<1,000	<10	290 D	6 J	<10
	2/99			<10	<10	<10	<10	<10	<1,000	<10	860 D	4 J	<10
	7/99			8 J	0.8 J	<10	<10	<10	<1,000	<10	250	<10	<10
	3/00			<10 J	<10	<10	<10	<10	<1,000 J	<10	60	7 J	<10
	9/00			5 J	<10 J	<10 J	<10 J	<10 J	<1,000 J	<10 J	8 J	6 J	<5
	3/01			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	9/01			54	<10	<10	<10	<10	<1,000 J	<10	350 D	5 J	<10
	4/02			<20	<5	<5	<5	<10	<1,000	<5	9	41	<5
	10/02			12 J	<10	<10	<10	<20	<1,000	<10	2 J	2 J	<10
	5/03			9 J	<5	<5	<5	<10	<1,000	<5	67	4 J	<5
	10/03			580 D	<5	<5	<5	<10	<1,000	<5	100	<5	<5
	6/04			22 J	<10 J	<10 J	<10 J	<20 J	<1,000	<10 J	35	7	<10 J
TW-01	12/96	365.1	355.4	<10	82	4 J	6 J	4 J	<1,000	<10	2,090 D	13	4 J
	9/98			<10	15	<10	4 J	<10	<1,000	<10	4,400 DEJ	4 J	<10
	2/99			<10	24	2 J	2 J	2 J	<1,000	<10	9,000 D	6 J	<10
	7/99			<10	16	1 J	3 J	<10	<1,000	<10	4,400 D	4 J	<10
	3/00			<10	16	<10	<10	<10	<1,000 J	<10	280 D	4 J	<10
	9/00			<10 J	11 J	<10 J	<10 J	<10 J	<1,000	<10 J	15	2 J	<10 J
	3/01			<10	5 J	<10	<10	<10	<1,000	<10	<10	2 J	<10
	9/01			<10	10	<10	<10	<10	<1,000 J	<10	<10	2 J	<10
	4/02			<14	3 J	<5	<5	<10	<1,000	<5	8	13	<5
	10/02			<25	7 J	<10	<10	<20	<1,000	<10	<5	R	<10
	5/03			<12	7	<5	<5	<10	<1,000	<5	<5	1 J	<5
	10/03			<12	6	<5	<5	<10	<1,000	<5	0.6 J	<5	<5
6/04	6 J	3 J	<10	<10	<20	<1,000	<10	<5	<5	<10			
TW-02 <sup>F</sup> (Replaced by TW-02R) <sup>N</sup> (Replaced by TW-02RR)	12/96	363.3	353.3	53	10	77	16	65	<1,000	585 D	15,900 JD	3,920 D	42,449 D
	9/98			<500 J	<500 J	<500 J	<500 J	53,000	5,000	300 J	38,000 D	61,000 D	86,000 D
	2/99			<1,000	<1,000	190 J	<1,000	150 J	14,000 JN	<1,000	83,000 D	7,900	14,000 B
	7/99			630	37	240 J	31	150	<1,000	55	100,000 D	3,500 J	9,700 D
	3/00			<1,000 J	<1,000	160 J	<1,000	240 J	<1,000 J	<1,000	64,000 D	3,900	13,000
	9/00			190 J	28 J	95 J	35 J	160 J	<1,000	6 J	79,000	<10,000	390 J
	3/01			81	19	68	28	130	<1,000	<10	67,000 D	650 J	400 D
	9/01			57	25	70	31	140	<1,000 J	<20	63,000 D	32	48 B
	4/02			240	19	65	23	96	<1,000	<5	1,090,000 D	<5,300	14
	10/02			110 J	15	19	23	65	<1,000	<10	80,000 D	10 J	<10
	5/03			240	30	130	49	226	<1,000	<5	160,000 D	230	97
	10/03			68	28	75 J	<5	<10	<1,000	2 J	92,000 D	<260	91
6/04	140 J	19 J	39 J	31 J	111 J	<1,000	<10 J	82,000	<5,200	4 J			

Table 3

Summary of Historic Groundwater Monitoring Data

McKesson Envirosystems  
Former Bear Street Facility  
Syracuse, New York

Monitoring Well	Sampling Date	Screen Elev. (ft. AMSL)		Acetone	Benzene	Toluene	Ethylbenzene	Xylene	Methanol	Trichloroethane	Aniline	N,N-dimethylaniline	Methylene Chloride
		Top	Bottom										
PZ-4D	11/89	350.8	345.9	<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	11/90			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
	11/91			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
	11/92			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
	8/95			<1,000	<5	<5	<5	<5	<1,000	<5	<5	0.8 J	<5
	10/95			NA	<5	<5	<5	<5	NA	<5	<5	<10	<5
	8/96			<10	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	8/97			<10	<10	<10	<10	<10	<1,000	<10	<6	<12	<10
	2/99			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10 J
	3/00			<10	<10	<10	<10	<10	<1,000 J	<10	<5	<10	<10
	3/01			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	4/02			<10	<5	<5	<5	<10	<1,000	<5	<5	<5	<5
	5/03			<12	<5	<5	<5	<5	<1,000	<5	<5	<5	<5
	6/04			<25	<10	<10	<10	<20	<1,000	<10	<5	<5	<5
PZ-4S	11/89	362.79	357.88	<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	11/90			<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	11/91			<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	11/92			<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	8/95			<1,000	<5	<5	<5	<5	<1,000	<5	<5	<10	<18
	10/95			NA	<5	<5	<5	<5	NA	<5	NA	NA	<5
	8/96			<10	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	8/97			<10	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	2/99			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	6/99			<10 J	<10	<10	<10	<10	<1,000 J	<10	<10 J	<10 J	<10 J
	3/00			<10	<10	<10	<10	<10	<1,000 J	<10	<5	<10	<10
	3/01			<10	<10	<10	<10	<10	<1,000	<10	<10	3 J	<10
	4/02			<14	<5	<5	<5	<10	<1,000	<5	8 (<5) <sup>L</sup>	<5 (<5) <sup>K</sup>	<5
	10/02			<25 J	<10	<10	<10	<20 J	<1,000	<10	<5 <sup>L</sup>	<5 <sup>L</sup>	<10
5/03			<12	<5	<5	<5	<5	<1,000	<5	<5	<5	<5	
6/04			<25	<10	<10	<10	<20	<1,000	<10	<5	<5	<10	
PZ-5D	11/89	353.5	348.6	<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	12/94			<10	<5	<5	<5	<5	<200	<5	<5	<10	<5
	2/96			<1,000	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	2/97			<1,000	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	9/98			<10	<10	<10	<10	<10	<1,000	<10	<5 <sup>H</sup>	<10	<12
	7/99			<10 J	<10 J	<10 J	<10 J	<10 J	<1,000	<10 J	<10	<10	<10 J
	9/00			<10 J	<10 J	<10 J	<10 J	<10 J	<1,000 J	<10 J	<10	<10	<10 J
	9/01			<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	10/02			<25 J	<10	<10	<10	<20 J	<1,000	<10	<5 <sup>L</sup>	<5 <sup>L</sup>	<10
	10/03			<12	<5	<5	<5	<10	<1,000	<5	46	<5	<5
6/04			<25	<10	<10	<10	<20	<1,000	<10	<5	<5	<10	

Table 3

## Summary of Historic Groundwater Monitoring Data

McKesson EnviroSystems  
Former Bear Street Facility  
Syracuse, New York

Monitoring Well	Sampling Date	Screen Elev. (ft. AMSL)		Acetone	Benzene	Toluene	Ethylbenzene	Xylene <sup>A</sup>	Methanol	Trichloroethene	Aniline	N,N-dimethylaniline	Methylene Chloride
		Top	Bottom										
PZ-5S	11/89	361.42	356.52	<100	<1	<1	<1	<1	<1,000	<1	<11	<11	<1
	12/94			<10	<5	<5	<5	<5	<200	<5	<5	<10	<5
	2/96			<1,000	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	2/97			5 J	<10	<10	<10	<10	<1,000	<10	<5	<10	<10
	9/98			<10	<10	<10	<10	<10	<1,000	<10	<5 <sup>H</sup>	<10	<12
	6/99			<10 J	<10	<10	<10	<10	<1,000	<10	<10 J	<10 J	<10 J
	7/99			<10 J	<10 J	<10 J	<10 J	<10 J	<1,000 J	<10 J	<10	<10	<10 J
	9/00			<10 J	<10 J	<10 J	<10 J	<10 J	<1,000 J	<10 J	<10 J	<10	<10 J
	9/01			7 J	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
	10/02			<25 J	<10	<10	<10	<20 J	<1,000	<10	<5 <sup>L</sup>	<5 <sup>L</sup>	<10
	10/03			<12	<5	<5	<5	<10	<1,000	<5	<5	<5	<5
PZ-8S <sup>G</sup>	9/98	362.6	357.7	<10	<10	<10	<10	<10	<1,000	<10	<10	<10	<10
PZ-11D <sup>C</sup>	11/89	352.09	347.19	<100	<1	<1	<1	<1	<1,000	<1	<11	<11	<1
PZ-11S <sup>C</sup>	11/89	359.09	354.19	<100	<1	<1	<1	<1	<1,000	<1	<11	<11	<1
PZ-12D <sup>C</sup>	11/89	350	345.1	<100	<1	<1	<1	<1	<1,000	<1	<53	<53	<1
	11/90			<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	11/91			<100	<1	<1	<1	<1	3	<1	<10	<10	<1
	11/92			<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
PZ-12S <sup>C</sup>	11/89	360	355.1	<100	<1	<1	<1	<1	<1,000	<1	<10	<10	<1
	11/90			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
	11/91			<100	<1	<1	<1	<3	6	<1	<10	<10	5
	11/92			<100	<1	<1	<1	<3	<1,000	<1	<10	<10	<1
PZ-13D <sup>F</sup>	11/89	349.4	344.4	<100	<1	<1	<1	<1	<1,000	<1	<11	<11	<1
PZ-13S <sup>F</sup>	11/89	359.5	354.5	<100	<1	2	<1	2	<1,000	<1	<11	<11	<1
NYSDEC Groundwater Standards (Part 700)				50	1	5	5	5	NA	5	5	1	5

Table 3

Summary of Historic Groundwater Monitoring Data

McKesson Envirosystems  
Former Bear Street Facility  
Syracuse, New York

General Notes:

1. Concentrations are presented in micrograms per liter (ug/L), which is equivalent to parts per billion (ppb).
2. Compounds detected are indicated by bold-faced type.
3. Detections exceeding New York State Department of Environmental Conservation (NYSDEC) Groundwater Standards (Part 700) are indicated by shading.
4. Replacement wells for MW-6, MW-8, MW-9, MW-10, MW-11, and MW-12D were installed 8/95.
5. Replacement wells for MW-17, MW-24S, MW-24D, and TW-02 were installed 11/97 - 12/97.
6. The laboratory analytical results for the duplicate sample collected from monitoring well MW-23S during the 7/99 sampling event, indicated the presence of methanol at 5.1 mg/l. Because methanol was not detected in the original sample, the duplicate results were determined, based on the results of the data validation process, to be unacceptable. Furthermore, methanol has not been previously detected in groundwater samples collected from this monitoring well. Accordingly, the detection of methanol appears to be the result of a laboratory error and not representative of actual groundwater quality in the vicinity of monitoring well MW-23S.
7. N,N-dimethylaniline data for 10/02 sampling event for MW-1, MW-3S, MW-28, MW-29, MW-32, MW-35, and TW-01 were rejected due to matrix spike and matrix spike duplicate recoveries below control limits. Aniline and N,N-dimethylaniline data for 10/02 sampling event for MW-30 were rejected due to matrix spike and matrix spike duplicate recoveries below control limits. These wells and piezometers are not perimeter monitoring locations and were not resampled.
8. Replacement wells for MW-8S and TW-02R were installed 8/04.
9. Aniline and N,N-dimethylaniline results of nondetect for the 6/04 sampling event at MW-18 were rejected due to the deviation from a surrogate recovery that was below 10 percent. This well was not resampled.

Superscript Notes:

- <sup>A</sup> = Data presented is total xylenes (m- and p-xylenes and o-xylenes). For the 1995 data, the listed quantitation limit applies to the analyses conducted for m- and p-xylenes and o-xylenes.
- <sup>C</sup> = Wells/piezometers MW-6, MW-7, MW-8, MW-9, MW-10, MW-11, MW-12D, PZ-11D, PZ-11S, PZ-12D, and PZ-12S were abandoned during OU No.1 soil remediation activities (1994).
- <sup>F</sup> = Wells/piezometers MW-5, MW-14D, MW-16D, MW-17, MW-20, MW-21, MW-24S, MW-24D, TW-02, PZ-13S, and PZ-13D were abandoned 11/97 - 1/98.
- <sup>G</sup> = Piezometer PZ-8S was decommissioned 8/2000.
- <sup>H</sup> = MW-18, MW-19, MW-23I, MW-23S, MW-24DR, MW-24SR, MW-28, PZ-5S, and PZ-5D wells/piezometers were resampled for aniline during 12/98, because the 9/98 results were rejected due to laboratory error.
- <sup>I</sup> = Because aniline was detected at monitoring well MW-3S at a concentration of 690 ug/l during the September 2001 sampling event, this well was resampled for aniline on November 8, 2001. Aniline was detected in MW-3S during the November 8, 2001 resampling event at a concentration of 69 ug/l.
- <sup>K</sup> = MW-17R, MW-18, and PZ-4S wells/piezometers were resampled for aniline and N,N-dimethylaniline on June 18, 2002 because N,N-dimethylaniline and/or aniline was detected during the April 2002 sampling event. The results of this additional sampling event are shown in parenthesis. MW-24SR and MW-24DR were also sampled for aniline and N,N-dimethylaniline on June 18, 2002, because N,N-dimethylaniline and/or aniline was detected at nearby perimeter monitoring locations during the April 2002 sampling event.
- <sup>L</sup> = MW-17R, MW-18, MW-19, MW-23S, MW-23I, MW-24DR, MW-24SR, MW-25S, PZ-4S, PZ-5S, and PZ-5D wells/piezometers were resampled for aniline and N,N-dimethylaniline during 1/03, because the 10/02 results were rejected due to matrix spike and matrix spike duplicate recoveries below control limits. These wells and piezometers are perimeter monitoring locations.
- <sup>M</sup> = MW-24SR and PZ-5D well and piezometer were sampled during the June 2004 sampling event because N,N-dimethylaniline and/or aniline was detected at nearby perimeter monitoring locations during the October 2003 sampling event.
- <sup>N</sup> = Wells MW-8S, MW-8D, and TW-02R were abandoned 8/04.

Abbreviations:

- AMSL = Above Mean Sea Level (NGVD of 1929)
- NA = Not available.
- ND = Not detected.
- NS = Not sampled.

Analytical Qualifiers:

- D = Indicates the presence of a compound in a secondary dilution analysis.
- J = The compound was positively identified; however, the numerical value is an estimated concentration only.
- E = The compound was quantitated above the calibration range.
- JN = The analysis indicates the presence of a compound for which there is presumptive evidence to make a tentative identification. The associated numerical value is an estimated concentration only.
- B = The compound has been found in the sample as well as its associated blank, its presence in the sample may be suspect.
- < = Compound was not detected at the listed quantitation limit.
- R = The sample results were rejected.

**Table 4  
Long-Term Hydraulic, Biological, and COC Process Control Monitoring Schedule**

**McKesson Envirosystems  
Former Bear Street Facility  
Syracuse, New York**

Monitoring Location	Annual Sampling Schedule	
	First Sampling Event	Second Sampling Event
<b>Upgradient</b>		
MW-1	B1, B2, C	B1, B2, C
MW-3S	B1, B2, C	B1, B2, C
MW-3D	H	H
<b>Area 1</b>		
TW-01	B1, B2, C	B1, B2, C
MW-6D	H	H
MW-9S	B1, B2, C	B1, B2, C
MW-9D	H	H
MW-31	B1, B2, C	B1, B2, C
MW-32	B1, B2, C	B1, B2, C
MW-33	B2, C	B2, C
PZ-F	H	H
PZ-G	H	H
PZ-HR	H	H
PZ-P	H	H
PZ-Q	H	H
PZ-R	H	H
PZ-S	H	H
<b>Area 2</b>		
TW-02R	B1, B2, C	B1, B2, C
PZ-9D	H	H
MW-34	B1, B2, C	B1, B2, C
MW-35	B1, B2, C	B1, B2, C
MW-36	B2, C	B2, C
PZ-I	H	H
PZ-J	H	H
PZ-T	H	H
PZ-U	H	H
PZ-V	H	H
PZ-W	H	H

**Table 4**  
**Long-Term Hydraulic, Biological, and COC Process Control Monitoring Schedule**

**McKesson Envirosystems**  
**Former Bear Street Facility**  
**Syracuse, New York**

Monitoring Location	Sampling Schedule	
	First Sampling Event	Second Sampling Event
<b>Area 3</b>		
MW-8S	B1, B2, C	B1, B2, C
MW-8D	H	H
MW-27	B1, B2, C	B1, B2, C
MW-28	B1, B2, C	B1, B2, C
MW-29	B2, C	B2, C
MW-30	B2, C	B2, C
PZ-A	H	H
PZ-B	H	H
PZ-C	H	H
PZ-D	H	H
PZ-E	H	H
PZ-K	H	H
PZ-L	H	H
PZ-M	H	H
PZ-N	H	H
PZ-O	H	H
MW-11S	H	H
MW-11D	H	H
<b>Downgradient Perimeter Monitoring Locations</b>		
MW-17R	C	C <sup>a</sup>
MW-18	C, H	C, H
MW-19	C, H	C, H
MW-23I	C, H	C, H
MW-23S	C, H	C, H
MW-24SR	H	C, H
MW-24DR	H	C, H
MW-25S	C, H	C, H
MW-25D	C, H	H
PZ-4S	C	
PZ-4D	C, H	H
PZ-5S		C
PZ-5D	H	C, H

**Table 4**  
**Long-Term Hydraulic, Biological, and COC Process Control Monitoring Schedule**

**McKesson Envirosystems**  
**Former Bear Street Facility**  
**Syracuse, New York**

**Notes:**

1. H = Hydraulic Monitoring (Groundwater Level Measurements).
2. B1 = Biological Monitoring for Poly-b-hydroxy alkanate (PHA) and Phospholipid Fatty Acid (PLFA).
3. B2 = Biological Monitoring for Common Biological Indicators and permanent gases including nitrate, total/dissolved iron, total/dissolved manganese, sulfate/sulfide, nitrogen, carbon dioxide, methane, potassium, ortho-phosphate, and ammonia.
4. C = Monitoring for the Chemicals of Concern (COCs).
5. The hydraulic monitoring identified in this table was conducted on a quarterly basis for the first year of the long-term process control monitoring program, and has been/will be conducted on a semi-annual basis thereafter. The hydraulic monitoring also includes measuring the conductivity of groundwater recovered from Area 3 from a sampling port located before the equalization tank.
6. Field groundwater parameters including pH, temperature, conductivity, dissolved oxygen (DO), and oxidation/reduction potential (ORP) are measured during each biological sampling event.
7. Each of the monitoring wells and piezometers used for hydraulic, biological and COC monitoring during the semi-annual monitoring event are checked for the presence (if any) of non-aqueous phase liquid (NAPL).
8. Based on the results obtained, the scope and/or the frequency for the hydraulic, biological, and/or COC components of the long-term process control monitoring program, as detailed herein, may be modified. Any modifications would be made in consultation with the New York State Department of Environmental Conservation (NYSDEC).
9. This table is based on the NYSDEC-approved *Operation and Maintenance (O&M) Plan* (BBL, Revised August 1999), including the NYSDEC-approved December 29, 1999 Addendum.
10. Piezometers PZ-8S/PZ-8D were identified in the *O&M Plan* to be sampled during the long-term process control monitoring program; however, as presented in the August 2000 *Biannual Process Control Monitoring Report*, these piezometers were damaged and no longer needed for the process control monitoring program. These piezometers were abandoned in August 2000.
11. As presented in the August 2000 *Biannual Process Control Monitoring Report*, monitoring well MW-17R was identified in the *O&M Plan* to be sampled only during the first biannual monitoring event; however, because benzene has been detected at concentrations slightly exceeding the NYSDEC Groundwater Quality Standard since the March 2000 sampling event, this well was also sampled during the second biannual monitoring event conducted during 2000 and 2001 (i.e., September 2000 and September 2001).
12. Monitoring wells MW-24SR and MW-24DR were additionally sampled for N,N-dimethylaniline and aniline on June 18, 2002 because N,N-dimethylaniline and/or aniline was detected at nearby downgradient perimeter monitoring locations during the April 2002 sampling event.
13. Monitoring well PZ-4S was additionally sampled for COCs on October 10, 2002 because aniline was detected at this location during the April 2002 sampling event.
14. Monitoring wells MW-17R, MW-18, MW-19, MW-23I, MW-23S, MW-24SR, MW-24DR, MW-25S, PZ-4S, PZ-5S, and PZ-5D were additionally sampled for N,N-dimethylaniline and aniline on January 20, 21, and 23, 2003 because the October 2002 N,N-dimethylaniline and aniline results for these locations were rejected during the validation process due to matrix spike and matrix spike duplicate recoveries below control limits.
15. Monitoring locations MW-24SR and PZ-5D were additionally sampled for COCs during the June 2004 COC biannual sampling event, because there were aniline detections at these locations during the October 2003 sampling event.

Table 5

Revised Long-Term Hydraulic and COC Process Control Monitoring Schedule

McKesson Enviroystems  
Former Bear Street Facility  
Syracuse, New York

Monitoring Location	Annual Sampling Schedule	
	First Sampling Event	Second Sampling Event
<b>Upgradient</b>		
MW-1	C	
MW-3S	C	
MW-3D	H	H
<b>Area 1</b>		
MW-6D	H	H
MW-9S	C	
MW-9D	H	H
MW-31	C	C
MW-32	C	C
MW-33	C	C
PZ-F	H	H
PZ-G	H	H
PZ-HR	H	H
PZ-P	H	H
PZ-Q	H	H
PZ-R	H	H
PZ-S	H	H
<b>Area 2</b>		
TW-02RR	C	C
PZ-9D	H	H
MW-34	C	
MW-35	C	C
MW-36	C	C
PZ-I	H	H
PZ-J	H	H
PZ-T	H	H
PZ-U	H	H
PZ-V	H	H
PZ-W	H	H



Table 5

Revised Long-Term Hydraulic and COC Process Control Monitoring Schedule

McKesson Enviroystems  
Former Bear Street Facility  
Syracuse, New York

Monitoring Location	Sampling Schedule	
	First Sampling Event	Second Sampling Event
<b>Area 3</b>		
MW-8SR	C	C
MW-27	C	C
MW-28	C	C
MW-29	C	
MW-30	C	
PZ-A	H	H
PZ-B	H	H
PZ-C	H	H
PZ-D	H	H
PZ-E	H	H
PZ-K	H	H
PZ-L	H	H
PZ-M	H	H
PZ-N	H	H
PZ-O	H	H
MW-11S	H	H
MW-11D	H	H
<b>Downgradient Perimeter Monitoring Locations</b>		
MW-17R	C	C
MW-18	C, H	C, H
MW-19	C, H	C, H
MW-23I	C, H	C, H
MW-23S	C, H	C, H
MW-24SR	H	C, H
MW-24DR	H	C, H
MW-25S	C, H	C, H
MW-25D	C, H	H
PZ-4S	C	
PZ-4D	C, H	H
PZ-5S		C
PZ-5D	H	C, H


Table 5

Revised Long-Term Hydraulic and COC Process Control Monitoring Schedule


McKesson Enviroystems  
Former Bear Street Facility  
Syracuse, New York

Notes:

1. H = Hydraulic Monitoring (Groundwater Level Measurements).
2. C = Monitoring for the Chemicals of Concern (COCs).
3. The hydraulic monitoring identified in this table will be conducted on a semi-annual basis. The hydraulic monitoring also includes measuring the conductivity of groundwater recovered from Area 3 from a sampling port located before the equalization tank.
4. Field groundwater parameters including pH, temperature, conductivity, dissolved oxygen (DO), and oxidation/reduction potential (ORP) are measured during each COC sampling event.
5. Each of the monitoring wells and piezometers used for hydraulic and COC monitoring during the semi-annual monitoring event are checked for the presence (if any) of non-aqueous phase liquid (NAPL).
6. Based on the results obtained, the scope and/or the frequency for the hydraulic and/or COC components of the long-term process control monitoring program, as detailed herein, may be modified. Any modifications would be made in consultation with the New York State Department of Environmental Conservation (NYSDEC).
7. This table is based on the NYSDEC-approved *Operation and Maintenance (O&M) Plan* (BBL, Revised August 1999), including the NYSDEC-approved December 29, 1999 Addendum with the modifications detailed in the October 2003 *Biannual Process Control Monitoring Report* and reiterated in the June 2004 *Biannual Process Control Monitoring Report*.




X: NONE  
 L: ON=\*, OFF=REF\*  
 P: SYR-BL  
 10/12/04 SYR-85-RCB MTK DMJ  
 26003190/26003801.DWG



- LEGEND:**
- UTILITY POLE
  - CATCH BASIN
  - PM ○ PETROLEUM PIPE LINE MARKER
  - GM ○ GAS LINE MARKER
  - SV ○ SEWER VENT
  - ◇ HYDRANT
  - WATER VALVE
  - MANHOLE

- PROPERTY LINE
- MW-11S ○ GROUNDWATER MONITORING WELL
- PZ-A □ PIEZOMETER
- OR ● BIANNUAL DOWNGRADEMENT PERIMETER GROUNDWATER MONITORING LOCATION
- BOUNDARY OF IMPACTED AREA
- GROUNDWATER WITHDRAWAL TRENCH
- ||||| GROUNDWATER INFILTRATION TRENCH
- PIPING TO BUILDING
- - - PIPING FROM BUILDING
- AREA OF RELATIVELY HIGHER CONCENTRATIONS OF COCs
- 365.0 — GROUNDWATER ELEVATION CONTOUR (FEET ABOVE MEAN SEA LEVEL) DASHED WHERE INFERRED
- (364.58) — GROUNDWATER ELEVATION (FEET ABOVE MEAN SEA LEVEL)
- INFERRED GROUNDWATER FLOW PATH

- NOTES:**
1. THIS FIGURE ONLY IDENTIFIES THE HYDRAULIC MONITORING LOCATIONS.
  2. REPLACED MONITORING WELLS AND PIEZOMETERS ARE IDENTIFIED WITH AN "R" (e.g., MW-24DR).
  3. ELEVATIONS BASED ON NATIONAL GEODETIC VERTICAL DATUM OF 1929.



MCKESSON ENVROSYSTEMS  
 BEAR STREET FACILITY  
 SYRACUSE, NEW YORK  
 BIANNUAL PROCESS CONTROL MONITORING REPORT  
**POTENTIOMETRIC SURFACE OF THE  
 SHALLOW HYDROGEOLOGIC UNIT  
 SAND LAYER - JUNE 14, 2004**




  
 BLASLAND, BOUCK & LEE, INC.  
 engineers & scientists



FIGURE  
**2**

P: PAGESET: BL  
 L: ON=OFF=REF  
 10/12/04 SYR-54-RCB RCA DMJ  
 28003010/28003W01.DWG



**NOTES:**

1. The two ratios: cy17:0/16:1w7c and cy19:0/18:1w7c express a growth rate of the microbial community. The sum of these two ratios falls within the range of 0.1 (log phase) to 5.0 (stationary phase). A lower ratio suggests a higher turnover rate.
2. MW-9S was not scheduled to be sampled during the short-term process control monitoring program, but was sampled in July 1999 (week 52) to provide additional information regarding Area 1. This well is part of the long-term process control monitoring program.


 cy19:0/18:1w7c    
  cy17:0/16:1w7c



MCKESSON ENVIROSYSTEMS  
 FORMER BEAR STREET FACILITY  
 SYRACUSE, NEW YORK  
**BIANNUAL PROCESS CONTROL MONITORING REPORT**

---

**AREA 1 - TURNOVER RATE**



---

  
**BBL**<sup>®</sup>  
 BLASLAND, BOUCK & LEE, INC.  
 engineers, scientists, economists



**NOTES:**

- Ratio above stacked bar graph is PHA to PLFA. PHA/PLFA ratio above 0.2 suggests unbalanced growth of the microbial community.
- \* = Ratio is half the PHA detection limit to PLFA.
- Start up operation began on June 10, 1998.
- Initial discrete RAMM injections were conducted from August 5 to August 12, 1998.
- MW-9S was not scheduled to be sampled during the short-term process control monitoring program, but was sampled in July 1999 (week 52) to provide additional information regarding Area 1. This well is part of the long-term process control monitoring program.
- Additional discrete RAMM injections were conducted on August 28 through August 30, 2000 and on August 27 through August 30, 2001.






**NOTES:**

1. Sum w7U/w7c = The sum of 16:1w7U/16:1w7c and 18:1w7U/18:1w7c.
2. The ratios 16:1w7U/16:1w7c and 18:1w7U/18:1w7c show the effect of toxicity or starvation on the microbial community. The range (for the sum w7U/w7c) is generally between 0.1 (healthy) to 0.6 (starved). A higher ratio indicates increased stress.
3. MW-9S was not scheduled to be sampled during the short-term process control monitoring program, but was sampled in July 1999 (week 52) to provide additional information regarding Area 1. This well is part of the long-term process control monitoring program.

MCKESSON ENVIROSYSTEMS  
 FORMER BEAR STREET FACILITY  
 SYRACUSE, NEW YORK  
**BIANNUAL PROCESS CONTROL MONITORING REPORT**

**AREA 1 - ENVIRONMENTAL STRESS**

**BBL**<sup>®</sup>  
 BLASLAND, BOUCK & LEE, INC.  
 engineers, scientists, economists



- NOTES:**
1. Ratio above stacked bar graph is PHA to PLFA. PHA/PLFA ratio above 0.2 suggests unbalanced growth of the microbial community.
  2. \* = Ratio is half the PHA detection limit to PLFA.
  3. Start up operation began on June 10, 1998.
  4. Initial discrete RAMM injections were conducted from August 5 to August 12, 1998.
  5. PZ-8S was not sampled in July 1999 and in March 2000 because this piezometer was damaged. This piezometer was decommissioned in August 2000.
  6. Additional discrete RAMM injections were conducted on August 28 through August 30, 2000 and on August 27 through August 30, 2001.



MCKESSON ENVIROSYSTEMS  
 FORMER BEAR STREET FACILITY  
 SYRACUSE, NEW YORK  
**BIANNUAL PROCESS CONTROL MONITORING REPORT**

**AREA 2 - BIOMASS  
 PLFA DISTRIBUTION**





**FIGURE  
 6**





**NOTES:**

1. The two ratios: cy17:0/16:1w7c and cy19:0/18:1w7c express a growth rate of the microbial community. The sum of these two ratios falls within the range of 0.1 (log phase) to 5.0 (stationary phase). A lower ratio suggests a higher turnover rate.
2. PZ-8S was not sampled in July 1999 and in March 2000 because this piezometer was damaged. This piezometer was decommissioned in August 2000.

 cy19:0/18:1w7c  
 cy17:0/16:1w7c


MCKESSON ENVIROSYSTEMS  
 FORMER BEAR STREET FACILITY  
 SYRACUSE, NEW YORK

BIANNUAL PROCESS CONTROL MONITORING REPORT


AREA 2 - TURNOVER RATE



FIGURE 8



Short-Term Process Control Monitoring



Long-Term Process Control Monitoring

NOTES:


1. Sum w7/w7c = The sum of 16:1w7U16:1w7c and 18:1w7U18:1w7c.
2. The ratios 16:1w7U16:1w7c and 18:1w7U18:1w7c show the effect of toxicity or starvation on the microbial community. The range (for the sum w7/w7c) is generally between 0.1 (healthy) to 0.6 (starved). A higher ratio indicates increased stress.
3. PZ-8S was not sampled in July 1999 and in March 2000 because this piezometer was damaged. This piezometer was decommissioned in August 2000.

MCKESSON ENVIROSYSTEMS  
FORMER BEAR STREET FACILITY  
SYRACUSE, NEW YORK


BIANNUAL PROCESS CONTROL MONITORING REPORT

AREA 2 - ENVIRONMENTAL STRESS


**BBL**  
BLASLAND, BOUCK & LEE, INC.  
engineers, scientists, economists





Short-Term Process Control Monitoring



Long-Term Process Control Monitoring



- NOTES:**
- Ratio above stacked bar graph is PHA to PLFA. PHA/PLFA ratio above 0.2 suggests unbalanced growth of the microbial community.
  - \* = Ratio is half the PHA detection limit to PLFA.
  - Start up operation began on June 10, 1998.
  - Initial discrete RAMM injections were conducted from August 5 to August 12, 1998.
  - Additional discrete RAMM injections were conducted on August 28 through August 30, 2000 and on August 27 through August 30, 2001.
  - MW-BS was inadvertently not sampled during the October 2003 sampling event.



**NOTES:**

1. Sum w7/w7c = The sum of 16:1w7U16:1w7c and 18:1w7U18:1w7c.
2. The ratios 16:1w7U16:1w7c and 18:1w7U18:1w7c show the effect of toxicity or starvation on the microbial community. The range (for the sum w7/w7c) is generally between 0.1 (healthy) to 0.6 (starved). A higher ratio indicates increased stress.
3. MW-6S was inadvertently not sampled during the October 2003 sampling event.


MCKESSON ENVIROSYSTEMS  
FORMER BEAR STREET FACILITY  
SYRACUSE, NEW YORK

BIANNUAL PROCESS CONTROL MONITORING REPORT


AREA 3 - ENVIRONMENTAL STRESS



FIGURE 10



Short-Term Process Control Monitoring



Long-Term Process Control Monitoring

**NOTE:**

1. The two ratios: cy17:0/16:1w7c and cy19:0/18:1w7c express a growth rate of the microbial community. The sum of these two ratios falls within the range of 0.1 (log phase) to 5.0 (stationary phase). A lower ratio suggests a higher turnover rate.
2. MW-8S was inadvertently not sampled during the October 2003 sampling event.

MCKESSON ENVIROSYSTEMS  
FORMER BEAR STREET FACILITY  
SYRACUSE, NEW YORK


BIANNUAL PROCESS CONTROL MONITORING REPORT

AREA 3 - TURNOVER RATE









**LEGEND**

- UTILITY POLE
- CATCH BASIN
- PERIMETER FENCE LINE
- MARKER
- GAS LINE MARKER
- HYDRANT
- WATER VALVE
- MANHOLE

**PROPERTY LINE**

- GROUNDWATER MONITORING WELL
- PEZ-A PERIMETER
- BIENNIAL DIMENSIONAL PERIMETER
- GROUNDWATER MONITORING LOCATION
- PUMPING WELL
- BOUNDARY OF IMPACTED AREA

**GROUNDWATER WITHDRAWAL TRENCH**

- GROUNDWATER INFILTRATION TRENCH
- PIPING TO BUILDING
- PIPING FROM BUILDING
- AREAS OF RELATIVELY HIGH CONCENTRATIONS OF COCs


**SAMPLE IDENTIFICATION**


Date	9/05	10/05
Acetone	<1,000 NA	<1,000 NA
Trichloroethane	1 J	<1,000 NA
N,N-dimethylamine	1 J	<1,000 NA
Aniline	1 J	<1,000 NA

**CONCENTRATION (ppb)**


**NOTES:**

- REPLACED MONITORING WELLS ARE IDENTIFIED WITH AN "R" (e.g., MW-240R).
- TRENCH LOCATIONS ARE APPROXIMATE.
- MONITORING LOCATIONS ARE APPROXIMATE.
- FIGURE ONLY SHOWS COC CONCENTRATIONS AT MONITORING LOCATIONS WITHIN THE IMPACTED AREAS AND THE CHEMICAL PROCESS CONTROL MONITORING LOCATIONS.
- ONLY DETECTED COCs ARE PRESENTED ON THIS FIGURE.
- < = COMPOUND WAS ANALYZED FOR BUT NOT DETECTED. THE ASSOCIATED NUMERICAL VALUE IS AN ESTIMATED CONCENTRATION ONLY.
- J = THE COMPOUND WAS POSITIVELY IDENTIFIED; HOWEVER, THE ASSOCIATED NUMERICAL VALUE IS AN ESTIMATED CONCENTRATION ONLY.
- D = CONCENTRATION IS BASED ON DILUTED SAMPLE ANALYSES.
- E = IDENTIFIED COMPOUNDS WHOSE CONCENTRATIONS EXCEEDED THE CALIBRATION RANGE OF THE INSTRUMENTS.
- R = THE COMPOUND HAS BEEN FOUND IN THE SAMPLE AS WELL AS IN ITS ASSOCIATED TRENCH; ITS PRESENCE IN THE SAMPLE MAY BE SUSPECT.
- N = THIS ANALYSIS INDICATES THE PRESENCE OF A COMPOUND FOR WHICH THERE IS PRESUMPTIVE EVIDENCE TO MAKE AN TENTATIVE IDENTIFICATION.
- R = THE SAMPLE RESULT WAS REJECTED.
- DETECTIONS EXCEEDING NYSDDEC GROUNDWATER QUALITY STANDARDS ARE INDICATED BY SHADING.
- ANALYSE DATA FOR THE 9/05 SAMPLING EVENT FOR MW-18, MW-19, MW-23S, MW-23, MW-24S, MW-24, MW-25, PZ-5S AND PZ-50 WERE OBTAINED IN 12/04 BECAUSE THE 9/05 RESULTS WERE REJECTED DUE TO LABORATORY ERROR.
- MW-3S WAS RESAMPLED ON 11/01/01 DUE TO ANALYSE DETECTION DURING 9/00/01 SAMPLING EVENT AT A CONCENTRATION OF 600 PPB. ANALYSE WAS DETECTED ON 11/01/01 AT A CONCENTRATION OF 68 PPB.
- MONITORING WELLS MW-17A, MW-18, MW-19, MW-23S AND PZ-4S WERE RESAMPLED ON 11/01/01 DUE TO ANALYSE DETECTION DURING 9/00/01 SAMPLING EVENT AT THESE PERMETER MONITORING LOCATIONS DURING THE APRIL 2002 SAMPLING EVENT. THE RESULTS OF THIS RESAMPLING EVENT ARE SHOWN IN THIS FIGURE. MONITORING WELLS MW-17A, MW-18, MW-19, MW-23S AND PZ-4S WERE ALSO SAMPLED ON JUNE 18, 2002 FOR ANALYSES OF ANILINE AND N,N-DIMETHYLAMINE. AS DETAILED IN THE BIENNIAL REPORT, THESE COMPOUNDS WERE NOT DETECTED.
- ANILINE AND N,N-DIMETHYLAMINE DATA FOR THE 10/02 SAMPLING EVENT FOR MW-17A, MW-18, MW-19, MW-23S, MW-24S, MW-24R, MW-24R, MW-25S, PZ-4S, PZ-5S, AND PZ-50 WERE OBTAINED IN 1/03 BECAUSE THE 10/02 RESULTS WERE REJECTED DUE TO ANALYSE AND MATRIX SPIKE DUPLICATE RECOVERIES BELOW CONTROL LIMITS.
- THE 6/04 SAMPLING EVENT ANILINE AND N,N-DIMETHYLAMINE DATA FOR MW-18 WERE REJECTED DUE TO THE DEVIATION FROM A SURROGATE RECOVERY BELOW 10 PERCENT. THIS MONITORING WELL WAS NOT RESAMPLED.











**LEGEND:**

- UTILITY POLE
- CATCH BASIN
- GAS LINE MARKER
- HYDRANT
- WATER VALVE
- MANHOLE
- PROPERTY LINE
- GROUNDWATER MONITORING WELL
- BIANNUAL DOWNGRADE PERIMETER
- GROUNDWATER MONITORING LOCATION
- PIEZOMETER
- WELL POINT
- DECOMMISSIONED GROUNDWATER MONITORING WELL
- BOUNDARY OF IMPACTED AREA
- GROUNDWATER WITHDRAWAL TRENCH
- GROUNDWATER INFILTRATION TRENCH AND IDENTIFICATION
- PIPING TO BUILDING
- PIPING FROM BUILDING
- AREA OF RELATIVELY HIGHER CONCENTRATIONS OF COCs
- APPROXIMATE LOCATION OF SOIL EXCAVATED TO AN ESTIMATED DEPTH OF 20 FT BELOW GROUND SURFACE (BGS) AND BACKFILLED WITH RAMM AMENDED PEA STONE
- APPROXIMATE LOCATION OF SOIL REMOVED BY 12-INCH OUTSIDE DIAMETER AUGER TO AN ESTIMATED DEPTH OF 20 FT BGS AND BACKFILLED WITH RAMM AND SUGA-LIK™ AMENDED PEA STONE
- APPROXIMATE LOCATION OF SOIL REMOVED BY 12-INCH OUTSIDE DIAMETER AUGER TO AN ESTIMATED DEPTH OF 20 FT BGS AND SOIL AMENDED WITH RAMM AND SUGA-LIK™ WAS RETURNED TO BOREHOLE.



**NOTES:**

1. REPLACED MONITORING WELLS ARE IDENTIFIED WITH AN "R" (e.g., MW-24DR).
2. MW-8D AND MW-8S WERE DECOMMISSIONED.
3. MW-8S WAS REPLACED (LOCATION IS APPROXIMATE).
4. WELL POINTS WP-1 THROUGH WP-3 AND WP-6 THROUGH WP-8 LOCATIONS ARE APPROXIMATE.




McKESSON ENVROSYSTEMS  
 FORMER BEAR STREET FACILITY  
 SYRACUSE, NEW YORK

**BIANNUAL PROCESS CONTROL MONITORING REPORT**

**SUPPLEMENTAL REMEDIAL  
 ACTIVITIES - AREA 3**

**FIGURE  
 14B**

**BBL**  
 BLASLAND, BOUCK & LEE, INC.  
 engineers & scientists



# Attachment 1

---

## Waste Characterization Data



**Environmental Laboratories, Inc.**  
 587 East Middle Turnpike, P.O.Box 370, Manchester, CT 06040  
 Tel. (860) 645-1102 Fax (860) 645-0823

# Analysis Report

August 30, 2004

FOR: Attn: Ms. Christie Sobal  
 Blasland & Bouck Engineers, PC  
 6723 Towpath Road Box 66  
 Syracuse, NY 13214-0066

### Sample Information

Matrix: SOIL  
 Location Code: BLASLAND  
 Rush Request:  
 P.O.#: 26001003

### Custody Information

Collected by: TH  
 Received by: KJB  
 Analyzed by: see "By" below

### Date

08/19/04  
 08/20/04

### Time

13:15  
 10:56

SDG I.D.: GAF79936

Phoenix I.D.: AF79936

## Laboratory Data

Client ID: MCKESSON BEAR ST AREA 1/2 ROLLOFF

Parameter	Result	RL	Units	Date	Time	By	Reference
TCLP Silver	BDL	0.01	mg/L	08/24/04		EK	E1311/SW6010
TCLP Arsenic	0.014	0.01	mg/L	08/24/04		EK	E1311/SW6010
TCLP Barium	1.4	0.01	mg/L	08/24/04		EK	E1311/SW6010
TCLP Cadmium	BDL	0.005	mg/L	08/24/04		EK	E1311/SW6010
TCLP Chromium	BDL	0.01	mg/L	08/24/04		EK	E1311/SW6010
TCLP Lead	BDL	0.015	mg/L	08/24/04		EK	E1311/SW6010
TCLP Selenium	BDL	0.05	mg/L	08/24/04		EK	E1311/SW6010
TCLP Mercury	BDL	0.001	mg/L	08/24/04		KMC	E1311/E245.1
Percent Solid	75		%	08/21/04		C/D	E160.3
Corrosivity	Negative	NONE	None	08/20/04		CD	S423/E150.1
Flash Point	>200	200	degree F	08/23/04		JR	SW846 - 1010
Ignitability	Passed	140	deg F	08/23/04		JR	SW846 - 1010
pH	8.33	0.10	pH Units	08/20/04	23:00	CD	E150.1/SW9045
Reactivity Cyanide	BDL	1.0	mg/Kg	08/21/04		ME	SW 846-7.3
Reactivity Sulfide	BDL	20	mg/Kg	08/21/04		ME	SW846-7.3
Reactivity	Negative			08/21/04		ME	SW 846-7.3
Soil Extraction for PCB	Completed			08/21/04		AB	3545/3550
TCLP Digestion Mercury	Completed			08/22/04		Y	E1311/7470
TCLP Extraction Herbicides	Completed			08/24/04		X/P	EPA 1311
TCLP Extraction Metals	Completed			08/20/04		TH	EPA 1311
TCLP Extraction Pesticides.	Completed			08/23/04		R/X	EPA 1311
TCLP Extraction Semi-Vol	Completed			08/23/04		R/X	EPA 1311
TCLP Extraction Volatiles.	Completed			08/24/04		R/H	EPA 1311
TCLP Metals Digestion	Completed			08/21/04		TH	SW846 - 3005


Parameter	Result	RL	Units	Date	Time	By	Reference
<b><u>Polychlorinated Biphenyls</u></b>							
PCB-1016	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1221	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1232	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1242	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1248	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1254	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1260	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1262	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1268	ND	400	ug/Kg	08/25/04		JH	SW 8082
<b><u>QA/QC Surrogates</u></b>							
% DCBP (Surrogate Rec)	93		%	08/25/04		JH	SW 8082
% TCMX (Surrogate Rec)	75		%	08/25/04		JH	SW 8082
<b><u>TCLP Herbicides</u></b>							
2,4,5-TP (Silvex)	ND	1.0	ug/L	08/26/04		KCA	SW8151
2,4-D	ND	5.0	ug/L	08/26/04		KCA	SW8151
<b><u>QA/QC Surrogates</u></b>							
% DCAA (Surrogate Rec)	41		%	08/26/04		KCA	SW8151
<b><u>TCLP Pesticides</u></b>							
4,4' -DDD	ND	0.1	ug/L	08/25/04		KCA	SW 8081
4,4' -DDE	ND	0.1	ug/L	08/25/04		KCA	SW 8081
4,4' -DDT	ND	0.1	ug/L	08/25/04		KCA	SW 8081
a-BHC	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Aldrin	ND	0.05	ug/L	08/25/04		KCA	SW 8081
b-BHC	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Chlordane	ND	0.3	ug/L	08/25/04		KCA	SW 8081
d-BHC	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Dieldrin	ND	0.1	ug/L	08/25/04		KCA	SW 8081
Endosulfan I	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Endosulfan II	ND	0.1	ug/L	08/25/04		KCA	SW 8081
Endosulfan Sulfate	ND	0.1	ug/L	08/25/04		KCA	SW 8081
Endrin	ND	0.1	ug/L	08/25/04		KCA	SW 8081
Endrin Aldehyde	ND	0.1	ug/L	08/25/04		KCA	SW 8081
g-BHC (Lindane)	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Heptachlor	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Heptachlor epoxide	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Methoxychlor	ND	0.2	ug/L	08/25/04		KCA	SW 8081
Toxaphene	ND	1.0	ug/L	08/25/04		KCA	SW 8081
<b><u>TCLP Volatiles</u></b>							
1,1-Dichloroethylene	ND	50	ug/L	08/27/04		RM	SW 8260
1,2-Dichloroethane	ND	50	ug/L	08/27/04		RM	SW 8260

Parameter	Result	RL	Units	Date	Time	By	Reference
Benzene	ND	50	ug/L	08/27/04		RM	SW 8260
Carbon tetrachloride	ND	50	ug/L	08/27/04		RM	SW 8260
Chlorobenzene	ND	50	ug/L	08/27/04		RM	SW 8260
Chloroform	ND	50	ug/L	08/27/04		RM	SW 8260
Methyl ethyl ketone	ND	50	ug/L	08/27/04		RM	SW 8260
Tetrachloroethene	ND	50	ug/L	08/27/04		RM	SW 8260
Trichloroethene	ND	50	ug/L	08/27/04		RM	SW 8260
Vinyl chloride	ND	50	ug/L	08/27/04		RM	SW 8260
<b>QA/QC Surrogates</b>							
%4-Bromofluorobenzene (Surrogate)	93		%	08/27/04		RM	SW 8260
<b>TCLP Acid/Base-Neutral</b>							
1,4-Dichlorobenzene	ND	170	ug/L	08/27/04		DRC	SW 8270
2,4,5-Trichlorophenol	ND	170	ug/L	08/27/04		DRC	SW 8270
2,4,6-Trichlorophenol	ND	170	ug/L	08/27/04		DRC	SW 8270
2,4-Dinitrotoluene	ND	170	ug/L	08/27/04		DRC	SW 8270
2-Methylphenol (o-Cresol)	ND	170	ug/L	08/27/04		DRC	SW 8270
3&4-Methylphenol (m&p-Cresol)	ND	170	ug/L	08/27/04		DRC	SW 8270
Hexachloro-1,3-butadiene	ND	170	ug/L	08/27/04		DRC	SW 8270
Hexachlorobenzene	ND	170	ug/L	08/27/04		DRC	SW 8270
Hexachloroethane	ND	170	ug/L	08/27/04		DRC	SW 8270
Nitrobenzene	ND	170	ug/L	08/27/04		DRC	SW 8270
Pentachlorophenol	ND	850	ug/L	08/27/04		DRC	SW 8270
Pyridine	ND	170	ug/L	08/27/04		DRC	SW 8270
<b>QA/QC Surrogates</b>							
% 2,4,6-Tribromophenol (Surrog Rec)	38		%	08/27/04		DRC	SW 8270
% 2-Fluorobiphenyl (Surrogate Rec)	85		%	08/27/04		DRC	SW 8270
% 2-Fluorophenol (Surrogate Rec)	Interference		%	08/27/04		DRC	SW 8270
% Nitrobenzene-d5 (Surrogate Rec)	76		%	08/27/04		DRC	SW 8270
% Phenol-d5 (Surrogate Rec)	9.5		%	08/27/04		DRC	SW 8270
% Terphenyl-d14 (Surrogate Rec)	105		%	08/27/04		DRC	SW 8270

**Comments:**

ND=Not detected BDL = Below Detection Limit RL=Reporting Limit

If there are any questions regarding this data, please call Phoenix Client Services at extension 200.

  
 Phyllis Shiller, Laboratory Director  
 August 30, 2004



**Environmental Laboratories, Inc.**  
 587 East Middle Turnpike, P.O.Box 370, Manchester, CT 06040  
 Tel. (860) 645-1102 Fax (860) 645-0823

# Analysis Report

August 30, 2004

FOR: Attn: Ms. Christie Sobal  
 Blasland & Bouck Engineers, PC  
 6723 Towpath Road Box 66  
 Syracuse, NY 13214-0066

### Sample Information

Matrix: SOIL  
 Location Code: BLASLAND  
 Rush Request:  
 P.O.#: 26001003

### Custody Information

Collected by: TH  
 Received by: KJB  
 Analyzed by: see "By" below

### Date

08/19/04  
 08/20/04

### Time

14:30  
 10:56

SDG I.D.: GAF79936

Phoenix I.D.: AF79937

## Laboratory Data

Client ID: MCKESSON BEAR ST AREA 3 ROLLOFF

Parameter	Result	RL	Units	Date	Time	By	Reference
TCLP Silver	BDL	0.01	mg/L	08/24/04		EK	E1311/SW6010
TCLP Arsenic	BDL	0.01	mg/L	08/24/04		EK	E1311/SW6010
TCLP Barium	1.33	0.01	mg/L	08/24/04		EK	E1311/SW6010
TCLP Cadmium	BDL	0.005	mg/L	08/24/04		EK	E1311/SW6010
TCLP Chromium	BDL	0.01	mg/L	08/24/04		EK	E1311/SW6010
TCLP Lead	BDL	0.015	mg/L	08/24/04		EK	E1311/SW6010
TCLP Selenium	BDL	0.05	mg/L	08/24/04		EK	E1311/SW6010
TCLP Mercury	BDL	0.001	mg/L	08/24/04		KMC	E1311/E245.1
Percent Solid	75		%	08/21/04		C/D	E160.3
Corrosivity	7.28	NONE	None	08/20/04		CD	S423/E150.1
Flash Point	>200	200	degree F	08/23/04		JR	SW846 - 1010
Ignitability	Passed	140	deg F	08/23/04		JR	SW846 - 1010
pH	7.28	0.10	pH Units	08/20/04	23:00	CD	E150.1/SW9045
Reactivity Cyanide	BDL	1.0	mg/Kg	08/21/04		ME	SW 846-7.3
Reactivity Sulfide	BDL	20	mg/Kg	08/21/04		ME	SW846-7.3
Reactivity	Negative			08/21/04		ME	SW 846-7.3
Soil Extraction for PCB	Completed			08/21/04		AB	3545/3550
TCLP Digestion Mercury	Completed			08/22/04		Y	E1311/7470
TCLP Extraction Herbicides	Completed			08/24/04		X/P	EPA 1311
TCLP Extraction Metals	Completed			08/20/04		TH	EPA 1311
TCLP Extraction Pesticides.	Completed			08/23/04		R/X	EPA 1311
TCLP Extraction Semi-Vol	Completed			08/23/04		R/X	EPA 1311
TCLP Extraction Volatiles.	Completed			08/24/04		R/H	EPA 1311
TCLP Metals Digestion	Completed			08/21/04		TH	SW846 - 3005


Parameter	Result	RL	Units	Date	Time	By	Reference
<b><u>Polychlorinated Biphenyls</u></b>							
PCB-1016	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1221	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1232	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1242	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1248	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1254	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1260	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1262	ND	400	ug/Kg	08/25/04		JH	SW 8082
PCB-1268	ND	400	ug/Kg	08/25/04		JH	SW 8082
<b><u>QA/QC Surrogates</u></b>							
% DCBP (Surrogate Rec)	66		%	08/25/04		JH	SW 8082
% TCMX (Surrogate Rec)	35		%	08/25/04		JH	SW 8082
<b><u>TCLP Herbicides</u></b>							
2,4,5-TP (Silvex)	ND	1.0	ug/L	08/26/04		KCA	SW8151
2,4-D	ND	5.0	ug/L	08/26/04		KCA	SW8151
<b><u>QA/QC Surrogates</u></b>							
% DCAA (Surrogate Rec)	59		%	08/26/04		KCA	SW8151
<b><u>TCLP Pesticides</u></b>							
4,4' -DDD	ND	0.1	ug/L	08/25/04		KCA	SW 8081
4,4' -DDE	ND	0.1	ug/L	08/25/04		KCA	SW 8081
4,4' -DDT	ND	0.1	ug/L	08/25/04		KCA	SW 8081
a-BHC	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Aldrin	ND	0.05	ug/L	08/25/04		KCA	SW 8081
b-BHC	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Chlordane	ND	0.3	ug/L	08/25/04		KCA	SW 8081
d-BHC	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Dieldrin	ND	0.1	ug/L	08/25/04		KCA	SW 8081
Endosulfan I	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Endosulfan II	ND	0.1	ug/L	08/25/04		KCA	SW 8081
Endosulfan Sulfate	ND	0.1	ug/L	08/25/04		KCA	SW 8081
Endrin	ND	0.1	ug/L	08/25/04		KCA	SW 8081
Endrin Aldehyde	ND	0.1	ug/L	08/25/04		KCA	SW 8081
g-BHC (Lindane)	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Heptachlor	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Heptachlor epoxide	ND	0.05	ug/L	08/25/04		KCA	SW 8081
Methoxychlor	ND	0.2	ug/L	08/25/04		KCA	SW 8081
Toxaphene	ND	1.0	ug/L	08/25/04		KCA	SW 8081
<b><u>TCLP Volatiles</u></b>							
1,1-Dichloroethylene	ND	50	ug/L	08/27/04		RM	SW 8260
1,2-Dichloroethane	ND	50	ug/L	08/27/04		RM	SW 8260

Parameter	Result	RL	Units	Date	Time	By	Reference
Benzene	ND	50	ug/L	08/27/04		RM	SW 8260
Carbon tetrachloride	ND	50	ug/L	08/27/04		RM	SW 8260
Chlorobenzene	ND	50	ug/L	08/27/04		RM	SW 8260
Chloroform	ND	50	ug/L	08/27/04		RM	SW 8260
Methyl ethyl ketone	ND	50	ug/L	08/27/04		RM	SW 8260
Tetrachloroethene	ND	50	ug/L	08/27/04		RM	SW 8260
Trichloroethene	52	50	ug/L	08/27/04		RM	SW 8260
Vinyl chloride	ND	50	ug/L	08/27/04		RM	SW 8260
<b>QA/QC Surrogates</b>							
%4-Bromofluorobenzene (Surrogate)	93		%	08/27/04		RM	SW 8260
<b>TCLP Acid/Base-Neutral</b>							
1,4-Dichlorobenzene	ND	100	ug/L	08/27/04		DRC	SW 8270
2,4,5-Trichlorophenol	ND	100	ug/L	08/27/04		DRC	SW 8270
2,4,6-Trichlorophenol	ND	100	ug/L	08/27/04		DRC	SW 8270
2,4-Dinitrotoluene	ND	100	ug/L	08/27/04		DRC	SW 8270
2-Methylphenol (o-Cresol)	ND	100	ug/L	08/27/04		DRC	SW 8270
3&4-Methylphenol (m&p-Cresol)	ND	100	ug/L	08/27/04		DRC	SW 8270
Hexachloro-1,3-butadiene	ND	100	ug/L	08/27/04		DRC	SW 8270
Hexachlorobenzene	ND	100	ug/L	08/27/04		DRC	SW 8270
Hexachloroethane	ND	100	ug/L	08/27/04		DRC	SW 8270
Nitrobenzene	ND	100	ug/L	08/27/04		DRC	SW 8270
Pentachlorophenol	ND	500	ug/L	08/27/04		DRC	SW 8270
Pyridine	ND	100	ug/L	08/27/04		DRC	SW 8270
<b>QA/QC Surrogates</b>							
% 2,4,6-Tribromophenol (Surrog Rec)	106		%	08/27/04		DRC	SW 8270
% 2-Fluorobiphenyl (Surrogate Rec)	101		%	08/27/04		DRC	SW 8270
% 2-Fluorophenol (Surrogate Rec)	Interference		%	08/27/04		DRC	SW 8270
% Nitrobenzene-d5 (Surrogate Rec)	62		%	08/27/04		DRC	SW 8270
% Phenol-d5 (Surrogate Rec)	3.5		%	08/27/04		DRC	SW 8270
% Terphenyl-d14 (Surrogate Rec)	79		%	08/27/04		DRC	SW 8270

**Comments:**

ND=Not detected BDL = Below Detection Limit RL=Reporting Limit

If there are any questions regarding this data, please call Phoenix Client Services at extension 200.

  
 Phyllis Shiller, Laboratory Director  
 August 30, 2004





**CHAIN OF CUSTODY RECORD**

587 East Middle Turnpike, P.O. Box 370, Manchester, CT 06040  
 EMail: service@phoenixlabs.com Fax (860) 645-0823

Client Services (860) 645-8726

Temp Pg of

Data Delivery (check one):  
 Fax #:  
 Email:  
 Format:  Excel  Pdf  Gis Key

Project P.O.: 260-01003  
 Phone #: 315 446-0570 x 325  
 Fax #:

Customer: EBL TALK  
 Address: 6723 Tompkins Rd  
Syracuse, NY 13214

Client Sample - Information - Identification

Sampler's Signature: [Signature] Date: 8/19/04

Matrix Code:  
 DW=drinking water S=soil/solid O=other  
 GW=groundwater SL=sludge A=air

Phoenix Sample #	Customer Sample Identification	Sample Matrix	Date Sampled	Time Sampled
79936	AREA 1/2 ROLLOFF	S	8/19/04	1:15 PM
79937	AREA 3 ROLLOFF	S	8/19/04	2:30 PM

Analysis Request

Analysis Request	TCLP - Metals	TCLP - PCBs	TCLP - VOC	TCLP - SVOC	TCM - PCBs	TCM - VOC	TCM - SVOC	TCM - PCBs	TCM - SVOC	TCM - PCBs	TCM - SVOC	TCM - PCBs	TCM - SVOC	TCM - PCBs	TCM - SVOC
Soil VOA Vials (Methanol) [Sod Burette]	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
GL Sol container ( ) oz	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
40 ml VOA Vial (As is) [HCl]	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
PL As is (1250ml) [As is] [HCl]	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
PL H2SO4 (1250ml) [As is] [H2SO4]	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
PL HNO3 250ml [250ml] [500ml]	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
PL NaOH 250ml [250ml] [500ml]	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Bacteria Bottle															

Reinquished by:	Accepted by:	Date:	Time:
<u>[Signature]</u>	<u>[Signature]</u>	8/19/04	10:58

Comments, Special Requirements or Regulations:

Turnaround:  
 1 Day\*  
 2 Days\*  
 3 Days\*  
 Standard  
 Other

Requirements for CI:  
 Res. Criteria  
 GW Protection  
 GA Mobility  
 GB Mobility  
 SW Protection  
 Res. Vol.  
 Ind. Vol.

Requirements for MA:  
 GW-1  
 GW-2  
 GW-3  
 S-1  
 S-2  
 S-3  
 MCP Certification  
 Other

\* Surcharge Applies

## **Attachment 2**

---

# **Waste Manifests and Bills of Lading**

Please print or type  
(Form designed for use on elite (12-pitch) typewriter.)

# NON-HAZARDOUS WASTE MANIFEST

1. Generator's US EPA ID No.

Manifest Doc. No.

2. Page 1  
of 1

04001

3. Generator's Name and Mailing Address

**McKesson Corporation**  
1 Post Street, 32nd Floor  
San Francisco CA 94104

Van Rensselaer and Bear Street  
Syracuse NY 13204

4. Generator's Phone ( 415 ) 983 - 7598

5. Transporter 1 Company Name

**Hazmat Environmental Group Inc.**

6. US EPA ID Number

**NYD980769947**

A. Transporter's Phone

**716 827-7200**

7. Transporter 2 Company Name

8. US EPA ID Number

B. Transporter's Phone

9. Designated Facility Name and Site Address

**CWM Chemical Services, LLC**  
1550 Balmer Road, PO Box 200  
Model City NY 14107

10. US EPA ID Number

**NYD049836879**

C. Facility's Phone

**716 754-8231**

11. Waste Shipping Name and Description

12. Containers  
No. Type

13. Total  
Quantity

14. Unit  
Wt/Vol

a. **Non-regulated material  
(soil and concrete)**

EST  
001 CM 25000 P

b.

c.

d.

D. Additional Descriptions for Materials Listed Above

E. Handling Codes for Wastes Listed Above

a. c.  
b. d.

a. c.  
b. d.

15. Special Handling Instructions and Additional Information

a)VA7434

WTS#13744  
SR#736186

SB192

16. GENERATOR'S CERTIFICATION: I certify the materials described above on this manifest are not subject to federal regulations for reporting proper disposal of Hazardous Waste.

Printed/Typed Name

*John Albrecht*

Signature

*[Signature]*

Month Day Year

10/05/04

17. Transporter 1 Acknowledgement of Receipt of Materials

Printed/Typed Name

*Kevin Muggard*

Signature

*[Signature]*

Month Day Year

10/05/04

18. Transporter 2 Acknowledgement of Receipt of Materials

Printed/Typed Name

Signature

Month Day Year

19. Discrepancy Indication Space

20. Facility Owner or Operator: Certification of receipt of waste materials covered by this manifest except as noted in Item 19.

Printed/Typed Name

Signature

Month Day Year

GENERATOR

TRANSPORTER

FACILITY

# HAZMAT



DATE

291643

ENVIRONMENTAL GROUP, INC  
60 Commerce Drive, Buffalo, NY 14218  
www.hazmatinc.comFAX (716) 827-7217  
(716) 827-7200NYDEC #9A-278  
EPA ID# NYD980769947**PICK UP****DELIVERY**

SHIPPER

CONSIGNEE

NAME MCKESSON CHEMICAL

STREET 40 BEAR STREET

CITY SYRACUSE STATE NY ZIP CODE \_\_\_\_\_

CONTACT NAME \_\_\_\_\_ PHONE \_\_\_\_\_

SCHEDULED TIME \_\_\_\_\_

NAME WASTE MANAGEMENT

STREET 1500 BALMER ROAD

CITY MODEL CITY STATE NY ZIP CODE 14104

CONTACT NAME \_\_\_\_\_ PHONE \_\_\_\_\_

**ADDITIONAL INFORMATION / EQUIPMENT DAMAGE**  
If damaged at pickup site, did you send in Equipment Damage Report (EDR) via Qualcomm? Y N Explain damage below.

Pursuant to 6NYCRR 372.2 (b) (2) (iii) HazMat certifies that it is Authorized to deliver this shipment of manifested waste to the TSDf listed on this Bill of Lading. Shipment valuation limits apply from HazMat Rules Publication 101, Item 848.

**ADDITIONAL INFORMATION / EQUIPMENT DAMAGE**  
If damaged at delivery site, did you send in Equipment Damage Report (EDR) via Qualcomm? Y N Explain damage below.

PURCHASE ORDER NO. \_\_\_\_\_ WORK ORDER NUMBER \_\_\_\_\_ MANIFEST NUMBER \_\_\_\_\_ H.M. NUMBER 4104

LOAD NUMBER \_\_\_\_\_ TRACTOR R1L3 TRAILER UNENOW1 ROLL OFF BOX \_\_\_\_\_ DRIVER NUMBER MACGREG DRIVER'S NAME MACGREG, KEVIN

EQUIPMENT	MATERIAL DESCRIPTION / MANIFEST NUMBER	QUANTITY
EQUIPMENT TYPE _____ UNIT# DROPPED _____ UNIT# PICKED UP _____ CONDITION REPORT _____	<u>23197</u>	

**PICK UP****DELIVERY**

PICK UP DATE \_\_\_\_\_

ARRIVAL TIME \_\_\_\_\_ AM/PM RELEASE TIME \_\_\_\_\_ AM/PM

DAY #2 DATE \_\_\_\_\_

ARRIVAL TIME \_\_\_\_\_ AM/PM RELEASE TIME \_\_\_\_\_ AM/PM

TRAILER EMPTY UPON ARRIVAL  YES (if not, explain below—)

DIP MEASUREMENT (Tankers Only) \_\_\_\_\_ INCHES

COMMENTS: (EXPLAIN ALL DELAYS) \_\_\_\_\_

DRIVER \_\_\_\_\_ DAY #1 DATE \_\_\_\_\_

ARRIVAL TIME \_\_\_\_\_ AM/PM RELEASE TIME \_\_\_\_\_ AM/PM

DAY #2 DATE \_\_\_\_\_ ARRIVAL TIME \_\_\_\_\_ AM/PM RELEASE TIME \_\_\_\_\_ AM/PM

DAY #3 DATE \_\_\_\_\_ ARRIVAL TIME \_\_\_\_\_ AM/PM RELEASE TIME \_\_\_\_\_ AM/PM

TRAILER CLEAN AND EMPTY UPON DEPARTURE  YES  NO (if not, explain below—)

COMMENTS: (Explain all delays or discrepancies) \_\_\_\_\_

HAZMAT MATERIALS USED (ex. overpacks, etc.):  YES  NO

IF YES EXPLAIN:

I, THE UNDERSIGNED, CERTIFY THAT THE ABOVE INFORMATION IS TRUE AND COMPLETE.

IF YES EXPLAIN:

I, THE UNDERSIGNED, CERTIFY THAT THE ABOVE INFORMATION IS TRUE AND COMPLETE.

SHIPPER'S SIGNATURE

Date

CONSIGNEE'S SIGNATURE

Date

Please print or type  
(Form designed for use on elite (12-pitch) typewriter.)

<b>NON-HAZARDOUS WASTE MANIFEST</b>		1. Generator's US EPA ID No.	Manifest Doc. No. <b>04002</b>	2. Page 1 of <b>1</b>
3. Generator's Name and Mailing Address <b>McKesson Corporation 1 Post Street, 32nd Floor San Francisco CA 94104</b>			Van Rensselear and Bear Street Syracuse NY 13204	
4. Generator's Phone ( <b>415</b> ) <b>983-7598</b>			6. US EPA ID Number <b>NYD980769947</b>	A. Transporter's Phone <b>716 827-7200</b>
5. Transporter 1 Company Name <b>Hazmat Environmental Group Inc.</b>		7. Transporter 2 Company Name	8. US EPA ID Number	B. Transporter's Phone
9. Designated Facility Name and Site Address <b>CWM Chemical Services, LLC 1550 Balmer Road, PO Box 200 Model City NY 14107</b>			10. US EPA ID Number <b>NYD049836679</b>	C. Facility's Phone <b>716 754-8231</b>
11. Waste Shipping Name and Description			12. Containers	13. Total Quantity
a. <b>Non-regulated material (soil and concrete)</b>			No. <b>001</b>	Type <b>CM</b>
b.				<b>FT</b>
c.				<b>36000</b>
d.				<b>PX</b>
D. Additional Descriptions for Materials Listed Above			E. Handling Codes for Wastes Listed Above	
a. <b>c</b>			a. <b>c</b>	
b. <b>d</b>			b. <b>d</b>	
15. Special Handling Instructions and Additional Information <b>a) VA7434</b>			<b>WTS#15744</b> <b>SR# 236136</b>  <b>RB 187</b>	
16. GENERATOR'S CERTIFICATION: I certify the materials described above on this manifest are not subject to federal regulations for reporting proper disposal of Hazardous Waste.				
Printed/Typed Name <b>Jordan Mitchell</b>		Signature <i>Jordan Mitchell</i>		Month Day Year <b>10/05/04</b>
17. Transporter 1 Acknowledgement of Receipt of Materials		Printed/Typed Name <b>MICHAEL RONCONE</b>		Signature <i>Michael Roncone</i>
18. Transporter 2 Acknowledgement of Receipt of Materials		Printed/Typed Name		Signature
19. Discrepancy Indication Space				
20. Facility Owner or Operator: Certification of receipt of waste materials covered by this manifest except as noted in Item 19.				
Printed/Typed Name		Signature		Month Day Year

GENERATOR

TRANSPORTER

FACILITY

# HAZMAT

ENVIRONMENTAL GROUP, INC  
 60 Commerca Drive, Buffalo, NY 14218  
 www.hazmatinc.com

FAX (716) 827-7217  
 (716) 827-7200



NYDEC #9A-278  
 EPA ID# NYD980769947

DATE

29164

**PICK UP**

**DELIVERY**

**S H I P P E R**

NAME: WASTE MANAGEMENT

STREET: 1500 BROADWAY

CITY: ALBANY STATE: NY ZIP CODE: 12202

CONTACT NAME: \_\_\_\_\_ PHONE: \_\_\_\_\_

SCHEDULED TIME: \_\_\_\_\_

**C O N S I G N E E**

NAME: WASTE MANAGEMENT

STREET: 1500 BROADWAY

CITY: ALBANY STATE: NY ZIP CODE: 12202

CONTACT NAME: \_\_\_\_\_ PHONE: \_\_\_\_\_

**ADDITIONAL INFORMATION / EQUIPMENT DAMAGE**  
 If damaged at pickup site, did you send in Equipment Damage Report (EDR) via Qualcomm? Y N Explain damage below.

Pursuant to 6NYCRR 372.2 (b) (2) (iii) HazMat certifies that it is Authorized to deliver this shipment of manifested waste to the TSDf listed on this Bill of Lading. Shipment valuation limits apply from HazMat Rules Publication 101, Item 848.

**ADDITIONAL INFORMATION / EQUIPMENT DAMAGE**  
 If damaged at delivery site, did you send in Equipment Damage Report (EDR) via Qualcomm? Y N Explain damage below.

PURCHASE ORDER NO. \_\_\_\_\_ WORK ORDER NUMBER \_\_\_\_\_ MANIFEST NUMBER 71702 H.M. NUMBER 94101

LOAD NUMBER \_\_\_\_\_ TRACTOR FIELD TRAILER/UNKNOWN RA192 ROLL OFF BOX \_\_\_\_\_ DRIVER NUMBER 111 DRIVER'S NAME ONE, MICHAEL

EQUIPMENT	MATERIAL DESCRIPTION / MANIFEST NUMBER	QUANTITY
EQUIPMENT TYPE _____ UNIT# DROPPED _____ UNIT# PICKED UP <u>RA192</u> CONDITION REPORT _____	<u>NON-REB</u>	<u>EST. 36,000 P</u>

**PICK UP**

**DELIVERY**

PICK UP DATE 10/5/04

ARRIVAL TIME 7:15 AM/PM \_\_\_\_\_ RELEASE TIME \_\_\_\_\_ AM/PM \_\_\_\_\_

DAY #2 DATE \_\_\_\_\_

ARRIVAL TIME \_\_\_\_\_ AM/PM \_\_\_\_\_ RELEASE TIME \_\_\_\_\_ AM/PM \_\_\_\_\_

TRAILER EMPTY UPON ARRIVAL  YES (if not, explain below—)

DIP MEASUREMENT (Tankers Only) \_\_\_\_\_ INCHES

COMMENTS: (EXPLAIN ALL DELAYS) AFW

HAZMAT MATERIALS USED (ex. overpacks, etc.):  YES  NO

IF YES EXPLAIN: \_\_\_\_\_

I, THE UNDERSIGNED, CERTIFY THAT THE ABOVE INFORMATION IS TRUE AND COMPLETE.

SHIPPER'S SIGNATURE \_\_\_\_\_ Date 10/5/04

DRIVER \_\_\_\_\_ DAY #1 DATE \_\_\_\_\_

ARRIVAL TIME \_\_\_\_\_ AM/PM \_\_\_\_\_ RELEASE TIME \_\_\_\_\_ AM/PM \_\_\_\_\_

DAY #2 DATE \_\_\_\_\_ ARRIVAL TIME \_\_\_\_\_ AM/PM \_\_\_\_\_ RELEASE TIME \_\_\_\_\_ AM/PM \_\_\_\_\_

DAY #3 DATE \_\_\_\_\_ ARRIVAL TIME \_\_\_\_\_ AM/PM \_\_\_\_\_ RELEASE TIME \_\_\_\_\_ AM/PM \_\_\_\_\_

TRAILER CLEAN AND EMPTY UPON DEPARTURE  YES  NO (if not, explain below—)

COMMENTS: (Explain all delays or discrepancies) \_\_\_\_\_

IF YES EXPLAIN: \_\_\_\_\_

I, THE UNDERSIGNED, CERTIFY THAT THE ABOVE INFORMATION IS TRUE AND COMPLETE.

CONSIGNEE'S SIGNATURE \_\_\_\_\_ Date \_\_\_\_\_

Please print or type  
(Form designed for use on elite (12-pitch) typewriter.)

<b>NON-HAZARDOUS WASTE MANIFEST</b>		1. Generator's US EPA ID No.	Manifest Doc. No. 04003	2. Page 1 of 1
3. Generator's Name and Mailing Address McKesson Corporation 1 Post Street, 32nd Floor San Francisco CA 94104			Van Rensselaer and Bear Street Syracuse NY 13204	
4. Generator's Phone ( 415) 983-7598		6. US EPA ID Number NYD980769947	A. Transporter's Phone 716 827-7200	
5. Transporter 1 Company Name Hazmat Environmental Group Inc.		8. US EPA ID Number	B. Transporter's Phone	
7. Transporter 2 Company Name		10. US EPA ID Number NYD049836679	C. Facility's Phone 716 754-8231	
9. Designated Facility Name and Site Address CWM Chemical Services, LLC 1550 Balmer Road, PO Box 200 Model City NY 14107		C. Facility's Phone		
11. Waste Shipping Name and Description			12. Containers No. Type	13. Total Quantity
a. Non-regulated material (soil and concrete)			001 CM	EST. 200.00
b.				
c.				
d.				
D. Additional Descriptions for Materials Listed Above		E. Handling Codes for Wastes Listed Above		
a. c.		a. c.		
b. d.		b. d.		
15. Special Handling Instructions and Additional Information VA7434 Roll off RB 129			WTS#13744 SR# 736137	
16. GENERATOR'S CERTIFICATION: I certify the materials described above on this manifest are not subject to federal regulations for reporting proper disposal of Hazardous Waste.				
Printed/Typed Name TIAW ALLEN		Signature <i>[Signature]</i>		Month Day Year 11 01 07 04
17. Transporter 1 Acknowledgement of Receipt of Materials				
Printed/Typed Name MICHAEL RONCONE		Signature <i>[Signature]</i>		Month Day Year 11 01 07 04
18. Transporter 2 Acknowledgement of Receipt of Materials				
Printed/Typed Name		Signature		Month Day Year
19. Discrepancy Indication Space				
20. Facility Owner or Operator: Certification of receipt of waste materials covered by this manifest except as noted in Item 19.				
Printed/Typed Name		Signature		Month Day Year

GENERATOR

TRANSPORTER

FACILITY

OCIATES, INC.

GENERATOR'S COPY

12-BLS-C5 Rev. 12/98

# HAZMAT



DATE

29172

ENVIRONMENTAL GROUP, INC  
60 Commerce Drive, Buffalo, NY 14218  
www.hazmatinc.comFAX (716) 827-7217  
(716) 827-7200NYDEC #9A-278  
EPA ID# NYD980769947**PICK UP****DELIVERY**

**S H I P P E R**

NAME ADMISSIONS CENTER

STREET 1000 STATE STREET

CITY SYRACUSE STATE NY ZIP CODE 13202

CONTACT NAME \_\_\_\_\_ PHONE \_\_\_\_\_

SCHEDULED TIME \_\_\_\_\_

**C O N S I G N E E**

NAME WASTE MANAGEMENT

STREET 1000 STATE STREET

CITY SYRACUSE STATE NY ZIP CODE 13202

CONTACT NAME \_\_\_\_\_ PHONE \_\_\_\_\_

**ADDITIONAL INFORMATION / EQUIPMENT DAMAGE**  
If damaged at pickup site, did you send in Equipment Damage Report (EDR) via Qualcomm? Y N Explain damage below.

Pursuant to 6NYCRR 372.2 (b) (2) (iii) HazMat certifies that it is Authorized to deliver this shipment of manifested waste to the TSDF listed on this Bill of Lading. Shipment valuation limits apply from HazMat Rules Publication 101, Item 848.

**ADDITIONAL INFORMATION / EQUIPMENT DAMAGE**  
If damaged at delivery site, did you send in Equipment Damage Report (EDR) via Qualcomm? Y N Explain damage below.

PURCHASE ORDER NO. \_\_\_\_\_ WORK ORDER NUMBER \_\_\_\_\_ MANIFEST NUMBER MAN. NO. = 11103 H.M. NUMBER 4100

LOAD NUMBER \_\_\_\_\_ TRACTOR RTLS TRAILER UNKNOWN ROLL OFF BOX RE 124 DRIVER NUMBER RONCUBAC DRIVER'S NAME RONCUBAC, MICHAEL

EQUIPMENT	MATERIAL DESCRIPTION / MANIFEST NUMBER	QUANTITY
EQUIPMENT TYPE _____ UNIT# DROPPED _____ UNIT# PICKED UP <u>1</u> CONDITION REPORT _____	<u>NON-FEG</u>	<u>EST. 20,000 P</u>

**PICK UP****DELIVERY**

PICK UP DATE 12/7/04

ARRIVAL TIME 7:45 AM/PM PM RELEASE TIME 7:15 AM/PM PM

DAY #2 DATE \_\_\_\_\_

ARRIVAL TIME \_\_\_\_\_ AM/PM PM RELEASE TIME \_\_\_\_\_ AM/PM PM

TRAILER EMPTY UPON ARRIVAL  YES (if not, explain below—)

DIP MEASUREMENT (Tankers Only) \_\_\_\_\_ INCHES

COMMENTS: (EXPLAIN ALL DELAYS) CLU REF 124

HAZMAT MATERIALS USED (ex. overpacks, etc.):  YES  NO

IF YES EXPLAIN:

I, THE UNDERSIGNED, CERTIFY THAT THE ABOVE INFORMATION IS TRUE AND COMPLETE.

SHIPPER'S SIGNATURE \_\_\_\_\_ Date \_\_\_\_\_

DRIVER \_\_\_\_\_ DAY #1 DATE \_\_\_\_\_

ARRIVAL TIME \_\_\_\_\_ AM/PM PM RELEASE TIME \_\_\_\_\_ AM/PM PM

DAY #2 DATE \_\_\_\_\_ ARRIVAL TIME \_\_\_\_\_ AM/PM PM RELEASE TIME \_\_\_\_\_ AM/PM PM

DAY #3 DATE \_\_\_\_\_ ARRIVAL TIME \_\_\_\_\_ AM/PM PM RELEASE TIME \_\_\_\_\_ AM/PM PM

TRAILER CLEAN AND EMPTY UPON DEPARTURE  YES  NO (if not, explain below—)

COMMENTS: (Explain all delays or discrepancies) \_\_\_\_\_

IF YES EXPLAIN:

I, THE UNDERSIGNED, CERTIFY THAT THE ABOVE INFORMATION IS TRUE AND COMPLETE.

CONSIGNEE'S SIGNATURE \_\_\_\_\_ Date \_\_\_\_\_



Please print or type  
(Form designed for use on elite (12-pitch) typewriter.)

<b>NON-HAZARDOUS WASTE MANIFEST</b>		1. Generator's US EPA ID No.	Manifest Doc. No. <b>04004</b>	2. Page 1 of <b>1</b>
3. Generator's Name and Mailing Address <b>McKesson Corporation 1 Post Street, 32nd Floor San Francisco CA 94104</b>			Van Rensselaer and Bear Street Syracuse NY 13204	
4. Generator's Phone ( <b>415</b> ) <b>983 - 7598</b>				
5. Transporter 1 Company Name <b>Hazmat Environmental Group Inc.</b>		6. US EPA ID Number <b>NYD980769947</b>		A. Transporter's Phone <b>716 827-7200</b>
7. Transporter 2 Company Name		8. US EPA ID Number		B. Transporter's Phone
9. Designated Facility Name and Site Address <b>CWM Chemical Services, LLC 1550 Balmer Road, PO Box 200 Model City NY 14107</b>		10. US EPA ID Number <b>NYD049836679</b>		C. Facility's Phone <b>716 754-8231</b>
11. Waste Shipping Name and Description <b>a. Non-regulated material (soil and concrete)</b>			12. Containers No.	13. Total Quantity
			Type	14. Unit Wt/Vol
			<b>001</b>	<b>CM</b>
				<b>EST. 30000</b>
				<b>P 4</b>
D. Additional Descriptions for Materials Listed Above			E. Handling Codes for Wastes Listed Above	
a.			a.	
b.			c.	
c.			d.	
d.				
15. Special Handling Instructions and Additional Information				
a) <b>VA7434</b> <i>POWDER SOLIDS</i>			<b>WTS#13744</b> <b>SR# 736/197</b>	
16. GENERATOR'S CERTIFICATION: I certify the materials described above on this manifest are not subject to federal regulations for reporting proper disposal of Hazardous Waste.				
Printed/Typed Name <i>John Mitchell</i>		Signature <i>[Signature]</i>		Month Day Year <b>10 6 7 0 4</b>
17. Transporter 1 Acknowledgement of Receipt of Materials				
Printed/Typed Name <i>Kevin Maggard</i>		Signature <i>[Signature]</i>		Month Day Year <b>10 6 7 0 4</b>
18. Transporter 2 Acknowledgement of Receipt of Materials				
Printed/Typed Name		Signature		Month Day Year
19. Discrepancy Indication Space				
20. Facility Owner or Operator: Certification of receipt of waste materials covered by this manifest except as noted in Item 19.				
Printed/Typed Name		Signature		Month Day Year

GENERATOR

TRANSPORTER

FACILITY

# HAZMAT



DATE

29171

ENVIRONMENTAL GROUP, INC  
60 Commerce Drive, Buffalo, NY 14218  
www.hazmatinc.comFAX (716) 827-7217  
(716) 827-7200NYDEC #9A-278  
EPA ID# NYD980769947**PICK UP****DELIVERY**

<b>S H I P P E R</b>	NAME <u>ENVIRONMENTAL GROUP, INC</u>	<b>C O N S I G N E E</b>	NAME <u>WASTE MANAGEMENT</u>
	STREET <u>100 BAY STREET</u>		STREET <u>BALMAIN ROAD</u>
	CITY <u>WILMINGTON</u> STATE <u>NY</u> ZIP CODE <u>14203</u>		CITY <u>WILMINGTON</u> STATE <u>NY</u> ZIP CODE <u>14203</u>
	CONTACT NAME <u>JOHN J. BROWN</u> PHONE <u>716-827-7200</u>		CONTACT NAME <u>JOHN J. BROWN</u> PHONE <u>716-827-7200</u>
	SCHEDULED TIME		

**ADDITIONAL INFORMATION / EQUIPMENT DAMAGE**  
If damaged at pickup site, did you send in Equipment Damage Report (EDR) via Qualcomm?  Y  N Explain damage below.

Pursuant to 6NYCRR 372.2 (b) (2) (iii) HazMat certifies that it is Authorized to deliver this shipment of manifested waste to the TSDF listed on this Bill of Lading. Shipment valuation limits apply from HazMat Rules Publication 101, Item 848.

**ADDITIONAL INFORMATION / EQUIPMENT DAMAGE**  
If damaged at delivery site, did you send in Equipment Damage Report (EDR) via Qualcomm?  Y  N Explain damage below.

PURCHASE ORDER NO.	WORK ORDER NUMBER	MANIFEST NUMBER	H.M. NUMBER <u>4100</u>
--------------------	-------------------	-----------------	----------------------------

LOAD NUMBER	TRACTOR <u>1013</u>	TRAILER <u>1013</u>	ROLL OFF BOX	DRIVER NUMBER <u>1013</u>	DRIVER'S NAME <u>ALVARADO, KEVIN</u>
-------------	------------------------	------------------------	--------------	------------------------------	---

EQUIPMENT	MATERIAL DESCRIPTION / MANIFEST NUMBER	QUANTITY
EQUIPMENT TYPE _____ UNIT# DROPPED _____ UNIT# PICKED UP _____ CONDITION REPORT _____		

**PICK UP****DELIVERY**

PICK UP DATE _____	DRIVER _____	DAY #1 DATE _____
ARRIVAL TIME _____ AM/PM	ARRIVAL TIME _____ AM/PM	RELEASE TIME _____ AM/PM
DAY #2 DATE _____	DAY #2 DATE _____	ARRIVAL TIME _____ AM/PM
ARRIVAL TIME _____ AM/PM	DAY #3 DATE _____	ARRIVAL TIME _____ AM/PM
RELEASE TIME _____ AM/PM	RELEASE TIME _____ AM/PM	RELEASE TIME _____ AM/PM
TRAILER EMPTY UPON ARRIVAL <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO (if not, explain below—)	TRAILER CLEAN AND EMPTY UPON DEPARTURE <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO (if not, explain below—)	
DIP MEASUREMENT (Tankers Only) _____ INCHES	COMMENTS: (Explain all delays or discrepancies) _____	
COMMENTS: (EXPLAIN ALL DELAYS) _____	_____	
HAZMAT MATERIALS USED (ex. overpacks, etc.): <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	IF YES EXPLAIN:	
IF YES EXPLAIN:	IF YES EXPLAIN:	
I, THE UNDERSIGNED, CERTIFY THAT THE ABOVE INFORMATION IS TRUE AND COMPLETE.	I, THE UNDERSIGNED, CERTIFY THAT THE ABOVE INFORMATION IS TRUE AND COMPLETE.	
SHIPPER'S SIGNATURE _____ Date _____	CONSIGNEE'S SIGNATURE _____ Date _____	

## **Attachment 3**

---

# **Well Construction Logs**

**Date Start/Finish:** 8/10/04  
**Drilling Company:** Parratt Wolff  
**Driller's Name:** Robert Baldoze  
**Drilling Method:** HSA and DRC 3 7/8" Tricone Bit  
**Bit Size:** 4 1/4"  
**Auger Size:** 4 1/4" HSA  
**Rig Type:** CME 850  
**Sampling Method:** NA

**Northing:** NA  
**Easting:** NA  
**Casing Elevation:** NA  
**Borehole Depth:** 20' below grade  
**Surface Elevation:** 372.70'  
**Geologist:** Ricardo Jaimes

**Well/Boring ID:** MW-8SR  
**Client:** McKesson Envirosystems  
**Location:** Bear Steet Facility  
 Syracuse, NY

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
375											Stick up with protective casing with locking cover
0										No samples collected from 0' - 20.0' bgs. See log for MW-8S for Stratigraphic description.	2" ID Sch. 40 PVC Riser (2.5' ags - 10.0' bgs)
370											2" ID Sch. 40 PVC Riser (2.5' ags - 10.0' bgs)
5											Cement-Bentonite Grout (0' - 6.0' bgs)
365											Hydrated bentonite chips seal (6.0' - 8.0' bgs)
10											Grade #00 Silica Sand Pack (8.0' - 20.0' bgs)
360											2" 0.010 Slot Sch. 40 PVC Screen (10.0' - 20.0' bgs)
15											



**Remarks:** NA = Not Applicable/Available; bgs = below ground surface.  
 Tricone bit was used to drill the interval between 7.0' and 20' bgs.

**Client:**  
McKesson EnviroSystems

**Site Location:**  
Bear Steet Facility  
Syracuse, NY

**Well/Boring ID:** MW-8SR

**Borehole Depth:** 20' below grade

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
355										No samples collected from 0' - 20.0' bgs. See log for MW-8S for Stratigraphic description.	<p>2" 0.010 Slot Sch. 40 PVC Screen (10.0' - 20.0' bgs)</p> <p>Grade #00 Silica Sand Pack (8.0' - 20.0' bgs)</p> <p>PVC Bottom cap</p>
20											
350											
25											
345											
30											
340											
35											



**Remarks:** NA = Not Applicable/Available; bgs = below ground surface.  
Tricone bit was used to drill the interval between 7.0' and 20' bgs.

<b>Date Start/Finish:</b> 8/10/04 <b>Drilling Company:</b> Parratt Wolff <b>Driller's Name:</b> Robert Baldoze <b>Drilling Method:</b> HSA and DRC 3 7/8" Tricone Bit <b>Bit Size:</b> 4 1/4" <b>Auger Size:</b> 4 1/4" HSA <b>Rig Type:</b> CME 850 <b>Sampling Method:</b> NA	<b>Northing:</b> NA <b>Easting:</b> NA <b>Casing Elevation:</b> NA  <b>Borehole Depth:</b> 20' below grade <b>Surface Elevation:</b> 373.3'  <b>Geologist:</b> Ricardo Jaimes	<b>Well/Boring ID:</b> TW-02RR  <b>Client:</b> McKesson EnviroSystems  <b>Location:</b> Bear Steet Facility Syracuse, NY
--	--	---

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
375											<p>Stick up with protective casing with locking cover</p> <p>2" ID Sch. 40 PVC Riser (2.5' ags - 10.0' bgs)</p>
0										No samples collected from 0' - 20.0' bgs. See log for TW-02 for Stratigraphic description.	<p>2" ID Sch. 40 PVC Riser (2.5' ags - 10.0' bgs)</p> <p>Cement-Bentonite Grout (0' - 6.0' bgs)</p> <p>Hydrated bentonite chips seal (6.0' - 8.0' bgs)</p> <p>Grade #00 Silica Sand Pack (8.0' - 20.0' bgs)</p> <p>2" 0.010 Slot Sch. 40 PVC Screen (10.0' - 20.0' bgs)</p>
370											
5											
365											
10											
360											
15											

	<b>Remarks:</b> NA = Not Applicable/Available; bgs = below ground surface; Tricone bit was used to drill the interval between 7.0' and 20' bgs.
--	--

**Client:**  
 McKesson EnviroSystems  
**Site Location:**  
 Bear Steet Facility  
 Syracuse, NY

**Well/Boring ID:** TW-02RR  
**Borehole Depth:** 20' below grade

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
355										No samples collected from 0' - 20.0' bgs. See log for TW-02 for Stratigraphic description.	<p>2" 0.010 Slot Sch. 40 PVC Screen (10.0' - 20.0' bgs)</p> <p>Grade #00 Silica Sand Pack (8.0' - 20.0' bgs)</p> <p>PVC Bottom cap</p>
20											
350											
25											
345											
30											
340											
35											

**BBL**  
 BLASLAND, BOUCK & LEE, INC.  
 engineers & scientists

**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;  
 Tricone bit was used to drill the interval between 7.0' and 20' bgs.

Date Start/Finish: 8/4/04  
 Drilling Company: Parratt Wolff  
 Driller's Name: Robert Baldoze  
 Drilling Method: HSA  
 Bit Size: 4 1/4"  
 Auger Size: 4 1/4" HSA  
 Rig Type: CME 850  
 Sampling Method: NA

Northing: NA  
 Easting: NA  
 Casing Elevation: NA  
 Borehole Depth: 17' below grade  
 Surface Elevation: NA  
 Geologist: Ricardo Jaimes

Well/Boring ID: WP-1  
 Client: McKesson Envirosystems  
 Location: Bear Steet Facility  
 Syracuse, NY

DEPTH	ELEVATION	Sample Run Number	Sample/In/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
0	0									No samples collected from 0' - 17.0' bgs. See log for MW-28 for Stratigraphic description.	<p>1" ID Black steel Riser (2.5' ags - 7.0' bgs)</p> <p>1" ID Black steel Riser (2.5' ags - 7.0' bgs)</p> <p>Cement-Bentonite Grout (0' - 4.5' bgs)</p> <p>Hydrated bentonite chips seal (4.5' - 6.5' bgs)</p> <p>1" 0.010 Slot Sch. Stainless Steel Screen (7.0' - 17.0' bgs)</p> <p>Grade #00 Silica Sand Pack (6.5' - 17.0' bgs)</p>
5	-5										
10-10											
15-15											



Remarks: NA = Not Applicable/Available; bgs = below ground surface;




**Client:**  
McKesson Envirosystems

**Site Location:**  
Bear Steet Facility  
Syracuse, NY

**Well/Boring ID:** WP-1

**Borehole Depth:** 17' below grade

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
										No samples collected from 0' - 17.0' bgs. See log for MW-28 for Stratigraphic description.	 <p>Grade #00 Silica Sand Pack (6.5' - 17.0' bgs)</p> <p>1" 0.010 Slot Sch. Stainless Steel Screen (7.0' - 17.0' bgs)</p> <p>Steel Bottom cap</p>
20-20											
25-25											
30-30											
35-35											



**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;

**Date Start/Finish:** 8/10/04  
**Drilling Company:** Parratt Wolff  
**Driller's Name:** Robert Baldoze  
**Drilling Method:** HSA  
**Bit Size:** 4 1/4"  
**Auger Size:** 4 1/4" HSA  
**Rig Type:** CME 850  
**Sampling Method:** NA

**Northing:** NA  
**Easting:** NA  
**Casing Elevation:** NA  
**Borehole Depth:** 17' below grade  
**Surface Elevation:** NA  
**Geologist:** Ricardo Jaimes

**Well/Boring ID:** WP-2  
**Client:** McKesson Envirosystems  
**Location:** Bear Steet Facility  
 Syracuse, NY

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
0	0										1" ID Black steel Riser (2.5' ags - 7.0' bgs)
5	-5									No samples collected from 0' - 17.0' bgs. See log for MW-28 for Stratigraphic description.	1" ID Black steel Riser (2.5' ags - 7.0' bgs) Cement-Bentonite Grout (0' - 4.5' bgs) Hydrated bentonite chips seal (4.5' - 6.5' bgs)
10-10											1" 0.010 Slot Sch. Stainless Steel Screen (7.0' - 17.0' bgs)
15-15											Grade #00 Silica Sand Pack (6.5' - 17.0' bgs)




**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;

**Client:**  
McKesson EnviroSystems

**Well/Boring ID:** WP-2

**Site Location:**  
Bear Steet Facility  
Syracuse, NY


**Borehole Depth:** 17' below grade

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
										No samples collected from 0' - 17.0' bgs. See log for MW-28 for Stratigraphic description.	 <p>Grade #00 Silica Sand Pack (6.5' - 17.0' bgs)</p> <p>1" 0.010 Slot Sch. Stainless Steel Screen (7.0' - 17.0' bgs)</p> <p>Steel Bottom cap</p>
20-20											
25-25											
30-30											
35-35											



**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;

<b>Date Start/Finish:</b> 8/4/04 <b>Drilling Company:</b> Parratt Wolff <b>Driller's Name:</b> Robert Baldoze <b>Drilling Method:</b> HSA <b>Bit Size:</b> 4 1/4" <b>Auger Size:</b> 4 1/4" HSA <b>Rig Type:</b> CME 850 <b>Sampling Method:</b> NA	<b>Northing:</b> NA <b>Easting:</b> NA <b>Casing Elevation:</b> NA  <b>Borehole Depth:</b> 17' below grade <b>Surface Elevation:</b> NA  <b>Geologist:</b> Ricardo Jaimes	<b>Well/Boring ID:</b> WP-3  <b>Client:</b> McKesson EnviroSystems  <b>Location:</b> Bear Steet Facility Syracuse, NY
--	--	--

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
0	0									No samples collected from 0' - 17.0' bgs. See log for MW-28 for Stratigraphic description.	 <p>1" ID Black steel Riser (2.5' ags - 7.0' bgs)</p> <p>1" ID Black steel Riser (2.5' ags - 7.0' bgs)</p> <p>Cement-Bentonite Grout (0' - 4.5' bgs)</p> <p>Hydrated bentonite chips seal (4.5' - 6.5' bgs)</p> <p>1" 0.010 Slot Sch. Stainless Steel Screen (7.0' - 17.0' bgs)</p> <p>Grade #00 Silica Sand Pack (6.5' - 17.0' bgs)</p>
5	-5										
10	-10										
15	-15										




**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;

**Client:**  
McKesson EnviroSystems

**Site Location:**  
Bear Steet Facility  
Syracuse, NY

**Well/Boring ID:** WP-3

**Borehole Depth:** 17' below grade

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
										No samples collected from 0' - 17.0' bgs. See log for MW-28 for Stratigraphic description.	 <p>Grade #00 Silica Sand Pack (6.5' - 17.0' bgs)</p> <p>1" 0.010 Slot Sch. Stainless Steel Screen (7.0' - 17.0' bgs)</p> <p>Steel Bottom cap</p>
20-20											
25-25											
30-30											
35-35											

**BBL**  
BLASLAND, BOUCK & LEE, INC.  
engineers & scientists

**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;

**Date Start/Finish:** 8/9/04  
**Drilling Company:** Parratt Wolff  
**Driller's Name:** Robert Baldoze  
**Drilling Method:** HSA  
**Bit Size:** 4 1/4"  
**Auger Size:** 4 1/4" HSA  
**Rig Type:** CME 850  
**Sampling Method:** NA

**Northing:** NA  
**Easting:** NA  
**Casing Elevation:** NA  
**Borehole Depth:** 19' below grade  
**Surface Elevation:** NA  
**Geologist:** Ricardo Jaimes

**Well/Boring ID:** WP-4  
**Client:** McKesson Envirosystems  
**Location:** Bear Steet Facility  
 Syracuse, NY

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
0	0									No samples collected from 0' - 19.0' bgs. See log for MW-33 for Stratigraphic description.	1" ID Black steel Riser (2.5' ags - 9.0' bgs)  1" ID Black steel Riser (2.5' ags - 9.0' bgs)  Cement-Bentonite Grout (0' - 6.5' bgs)  Hydrated bentonite chips seal (6.5' - 8.5' bgs)  1" 0.010 Slot Sch. Stainless Steel Screen (9.0' - 19.0' bgs)  Grade #00 Silica Sand Pack (8.5' - 19.0' bgs)
5	-5										
10	-10										
15	-15										




**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;

**Client:**  
McKesson Envirosystems

**Well/Boring ID:** WP-4

**Site Location:**  
Bear Steet Facility  
Syracuse, NY

**Borehole Depth:** 19' below grade

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
										No samples collected from 0' - 19.0' bgs. See log for MW-33 for Stratigraphic description.	 <p>Grade #00 Silica Sand Pack (8.5' - 19.0' bgs) 1" 0.010 Slot Sch. Stainless Steel Screen (9.0' - 19.0' bgs) Steel Bottom cap</p>
20-20											
25-25											
30-30											
35-35											



**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;

**Date Start/Finish:** 8/9/04  
**Drilling Company:** Parratt Wolff  
**Driller's Name:** Robert Baldoze  
**Drilling Method:** HSA  
**Bit Size:** 4 1/4"  
**Auger Size:** 4 1/4" HSA  
**Rig Type:** CME 850  
**Sampling Method:** NA

**Northing:** NA  
**Easting:** NA  
**Casing Elevation:** NA  
  
**Borehole Depth:** 19' below grade  
**Surface Elevation:** NA  
  
**Geologist:** Ricardo Jaimes

**Well/Boring ID:** WP-5  
**Client:** McKesson Envirosystems  
  
**Location:** Bear Steet Facility  
 Syracuse, NY

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
0	0										1" ID Black steel Riser (2.5' ags - 9.0' bgs)
5	-5									No samples collected from 0' - 19.0' bgs. See log for MW-33 for Stratigraphic description.	1" ID Black steel Riser (2.5' ags - 9.0' bgs) Cement-Bentonite Grout (0' - 6.5' bgs) Hydrated bentonite chips seal (6.5' - 8.5' bgs) 1" 0.010 Slot Sch. Stainless Steel Screen (9.0' - 19.0' bgs) Grade #00 Silica Sand Pack (8.5' - 19.0' bgs)
10-10											
15-15											



**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;




**Client:**  
McKesson Envirosystems

**Well/Boring ID:** WP-5

**Site Location:**  
Bear Steet Facility  
Syracuse, NY


**Borehole Depth:** 19' below grade

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
										No samples collected from 0' - 19.0' bgs. See log for MW-33 for Stratigraphic description.	 <p>Grade #00 Silica Sand Pack (8.5' - 19.0' bgs) 1" 0.010 Slot Sch. Stainless Steel Screen (9.0' - 19.0' bgs) Steel Bottom cap</p>
20-20											
25-25											
30-30											
35-35											



**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;

<b>Date Start/Finish:</b> 8/10/04 <b>Drilling Company:</b> Parratt Wolff <b>Driller's Name:</b> Robert Baldoze <b>Drilling Method:</b> HSA <b>Bit Size:</b> 4 1/4" <b>Auger Size:</b> 4 1/4" HSA <b>Rig Type:</b> CME 850 <b>Sampling Method:</b> NA	<b>Northing:</b> NA <b>Easting:</b> NA <b>Casing Elevation:</b> NA  <b>Borehole Depth:</b> 18' below grade <b>Surface Elevation:</b> NA  <b>Geologist:</b> Ricardo Jaimes	<b>Well/Boring ID:</b> WP-6  <b>Client:</b> McKesson Envirosystems  <b>Location:</b> Bear Steet Facility Syracuse, NY
---	--	--

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
0	0									No samples collected from 0' - 18.0' bgs. See log for MW-27 for Stratigraphic description.	 <p>1" ID Black steel Riser (2.5' ags - 8.0' bgs)</p> <p>1" ID Black steel Riser (2.5' ags - 8.0' bgs)</p> <p>Cement-Bentonite Grout (0' - 5.5' bgs)</p> <p>Hydrated bentonite chips seal (5.5' - 7.5' bgs)</p> <p>1" 0.010 Slot Sch. Stainless Steel Screen (8.0' - 18.0' bgs)</p> <p>Grade #00 Silica Sand Pack (7.5' - 18.0' bgs)</p>


<h1 style="margin: 0;">BBL</h1> <p style="margin: 0;">BLASLAND, BOUCK &amp; LEE, INC. engineers &amp; scientists</p>	<b>Remarks:</b> NA = Not Applicable/Available; bgs = below ground surface;
--	--

**Client:**  
McKesson Envirosystems

**Well/Boring ID:** WP-6

**Site Location:**  
Bear Steet Facility  
Syracuse, NY

**Borehole Depth:** 18' below grade

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
										No samples collected from 0' - 18.0' bgs. See log for MW-27 for Stratigraphic description.	 <p>Grade #00 Silica Sand Pack (7.5' - 18.0' bgs) 1" 0.010 Slot Sch. Stainless Steel Screen (8.0' - 18.0' bgs) Steel Bottom cap</p>
20-20											
25-25											
30-30											
35-35											




**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;

**Date Start/Finish:** 8/12/04  
**Drilling Company:** Parratt Wolff  
**Driller's Name:** Robert Baldoze  
**Drilling Method:** HSA  
**Bit Size:** 4 1/4"  
**Auger Size:** 4 1/4" HSA  
**Rig Type:** CME 850  
**Sampling Method:** NA

**Northing:** NA  
**Easting:** NA  
**Casing Elevation:** NA  
  
**Borehole Depth:** 18' below grade  
**Surface Elevation:** NA  
  
**Geologist:** Ricardo Jaimes

**Well/Boring ID:** WP-7  
**Client:** McKesson Envirosystems  
  
**Location:** Bear Steet Facility  
 Syracuse, NY

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
0	0										
5	-5									No samples collected from 0' - 18.0' bgs. See log for MW-27 for Stratigraphic description.	
10	-10										
15	-15										




**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;

**Client:**  
McKesson Envirosystems

**Well/Boring ID:** WP-7

**Site Location:**  
Bear Steet Facility  
Syracuse, NY

**Borehole Depth:** 18' below grade

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
										No samples collected from 0' - 18.0' bgs. See log for MW-27 for Stratigraphic description.	 <p>Grade #00 Silica Sand Pack (7.5' - 18.0' bgs) 1" 0.010 Slot Sch. Stainless Steel Screen (8.0' - 18.0' bgs) Steel Bottom cap</p>
20-20											
25-25											
30-30											
35-35											



**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;

**Date Start/Finish:** 8/12/04  
**Drilling Company:** Parratt Wolff  
**Driller's Name:** Robert Baldoze  
**Drilling Method:** HSA  
**Bit Size:** 4 1/4"  
**Auger Size:** 4 1/4" HSA  
**Rig Type:** CME 850  
**Sampling Method:** NA

**Northing:** NA  
**Easting:** NA  
**Casing Elevation:** NA  
  
**Borehole Depth:** 18' below grade  
**Surface Elevation:** NA  
  
**Geologist:** Ricardo Jaimes

**Well/Boring ID:** WP-8  
  
**Client:** McKesson Envirosystems  
  
**Location:** Bear Steet Facility  
 Syracuse, NY

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
0	0									No samples collected from 0' - 18.0' bgs. See log for MW-27 for Stratigraphic description.	<p>           1" ID Black steel Riser (2.5' ags - 8.0' bgs)            1" ID Black steel Riser (2.5' ags - 8.0' bgs)            Cement-Bentonite Grout (0' - 5.5' bgs)            Hydrated bentonite chips seal (5.5' - 7.5' bgs)            1" 0.010 Slot Sch. Stainless Steel Screen (8.0' - 18.0' bgs)            Grade #00 Silica Sand Pack (7.5' - 18.0' bgs)         </p>

**BBL**  
 BLASLAND, BOUCK & LEE, INC.  
 engineers & scientists


**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;

**Client:**  
McKesson EnviroSystems

**Well/Boring ID:** WP-8

**Site Location:**  
Bear Steet Facility  
Syracuse, NY

**Borehole Depth:** 18' below grade

DEPTH	ELEVATION	Sample Run Number	Sample/Int/Type	Recovery (feet)	Blows / 6 Inches	N - Value	PID Headspace (ppm)	Analytical Sample	Geologic Column	Stratigraphic Description	Well/Boring Construction
										No samples collected from 0' - 18.0' bgs. See log for MW-27 for Stratigraphic description.	 <p>Grade #00 Silica Sand Pack (7.5' - 18.0' bgs)</p> <p>1" 0.010 Slot Sch. Stainless Steel Screen (8.0' - 18.0' bgs)</p> <p>Steel Bottom cap</p>
20-20											
25-25											
30-30											
35-35											

**BBL**  
BLASLAND, BOUCK & LEE, INC.  
engineers & scientists

**Remarks:** NA = Not Applicable/Available; bgs = below ground surface;