

The electronic version of this file/report should have the file name:

Type of document.Spill Number.Year-Month.File *Year-Year* or Report name.pdf

letter._____._____._____.File spillfile_____.pdf

report.hw915147.2004-06-18.WORK PLAN.pdf

Project **Site** numbers will be proceeded by the following:

Municipal Brownfields - b

Superfund - hw

Spills - sp

ERP - e

VCP - v

BCP - c

non-releasable - put .nf.pdf

Example: letter.sp9875693.1998-01.Filespillfile.nf.pdf



Infrastructure, buildings, environment, communications

RECEIVED

JUN 18 2004

NYSDEC REG 9
FOIL
___REL___UNREL

ARCADIS G&M, Inc.
441 New Karner Road
Suite 4
Albany
New York
Tel 518 452 7826
Fax 518 452 4398

Transmittal Letter

To:
Mr. Martin ~~Doster~~, P.E.
Mr. David ~~Locey~~ ✓

Copies:
Mr. David Sordi
Ingersoll-Rand Company

ENVIRONMENTAL

From:
Marc Sanford

Date:
17 June 2004

Subject:
Pneumatic Fracturing Work Plan
ARO Corporation Site – Cheektowaga, NY

ARCADIS Project No.:
AY000220.0008

We are sending you:

☒ Attached

☐ Under Separate Cover Via _____ the Following Items:

☐ Shop Drawings

☐ Plans

☐ Specifications

☐ Change Order

☐ Prints

☐ Samples

☐ Copy of Letter

☐ Reports

☐ Other: _____

Copies	Date	Drawing No.	Rev.	Description	Action*
2				Pneumatic Fracturing Work Plan	

Action*

☐ A Approved

☐ CR Correct and Resubmit

☐ Resubmit _____ Copies

☐ AN Approved As Noted

☐ F File

☐ Return _____ Copies

☐ AS As Requested

☐ FA For Approval

☐ Review and Comment

☐ Other: _____

Mailing Method

☒ U.S. Postal Service 1st Class

☐ Courier/Hand Delivery

☐ FedEx Priority Overnight

☐ FedEx 2-Day Delivery

☐ Certified/Registered Mail

☐ United Postal Service (UPS)

☐ FedEx Standard Overnight

☐ FedEx Economy

☐ Other: _____

Comments: _____

X

RECEIVED

JUN 18 2004

NYSDEC REG 9
FOIL
___REL___UNREL

**Work Plan
Remedial Enhancement via
Pneumatic Fracturing
Technology**

ARO Corporation Site
Cheektowaga, New York





Infrastructure, buildings, environment, communications

PREPARED FOR

Ingersoll-Rand Corporation

ARCADIS


Erich Zimmerman, P.E.
Senior Engineer
Marc W. Sanford
Principal Scientist

Work Plan
Remedial Enhancement via
Pneumatic Fracturing
Technology

ARO Corporation Site,
Cheektowaga, New York

Prepared for:
Ingersoll-Rand Corporation

Prepared by:
ARCADIS G&M, Inc.
441 New Karner Road
Suite 4
Albany
New York 12205
Tel 518 452 7826
Fax 518 452 4398

Our Ref.:
AY000220.0007

Date:
June 17, 2004

This document is intended only for the use of the individual or entity for which it was prepared and may contain information that is privileged, confidential, and exempt from disclosure under applicable law. Any dissemination, distribution, or copying of this document is strictly prohibited.

ARCADIS

Work Plan Remedial Enhancement via Pneumatic Fracturing ARO Corporation Site Cheektowaga, NY

1.	Introduction	2
2.	Background	2
3.	Pneumatic Fracturing Process	2
4.	Pilot Study Objective	3
5.	Scope of Work	3
5.1	Baseline Monitoring	4
5.2	Pneumatic Fracturing Pilot Study	4
5.3	Reporting	5
6.	Schedule	5

Figures

- 1 Fracture Well Cross Section, ARO Corporation Site, Cheektowaga, New York
- 2 Site Layout and Well Location Map, ARO Corporation Site, Cheektowaga, New York
- 2 Project Schedule

ARCADIS

Work Plan Remedial Enhancement via Pneumatic Fracturing

ARO Corporation Site
Cheektowaga, NY

1. Introduction

ARCADIS G&M, Inc. (ARCADIS) was retained by Ingersoll-Rand Corporation (IR) to prepare this Work Plan for evaluating pneumatic fracturing (PF) technology as a means to enhance the existing Vacuum-Enhanced Recovery (VER) system at the former ARO Corporation (ARO) Site. The goal of the PF program is to pneumatically enhance the intrinsic permeability of the geologic formation, thereby increasing the radial influence (RI) of the existing VER recovery wells. This will increase the rate of induced airflow through the vadose zone, thereby increasing the mass removal rate for volatile organic compounds (VOCs) present within the overburden, while greatly reducing the flow rate of co-produced groundwater. Pneumatic fracturing is proposed at two locations on site.

2. Background

The ARO Corporation site is an inactive hazardous waste site in Cheektowaga, New York. The site is currently in the remedial action (RA) phase of the remedial program under a Consent Order with the NYSDEC. ARCADIS designed and installed a VER system in 1998 to remediate chlorinated hydrocarbons (CAHs) in groundwater at the site. A total of ten recovery wells are operated under the current VER system configuration. Performance monitoring activities are currently completed in accordance with the approved New York Department of Environmental Conservation monitoring schedule and include the following:

- Monthly analysis of groundwater and vapor samples from the VER system; and
- Semi-Annual groundwater monitoring of monitoring wells; and submission of an annual report.

3. Pneumatic Fracturing Process

Pneumatic fracturing is a patented technology, which enhances the in situ removal and treatment of VOCs in low permeable formations. The process may be generally described as injecting a gas into a contaminated geologic formation at a pressure, which exceeds the natural in situ stresses, and at a flow rate, which exceeds the permeability of the formation. This causes failure of the geologic unit and creates a fracture network radiating from the injection point (e.g., radially or directionally).

ARCADIS

Work Plan Remedial Enhancement via Pneumatic Fracturing

ARO Corporation Site
Cheektowaga, NY

Once established, the fractures increase the rate at which vapors or liquids can travel through the formation (i.e., increases advective flow and shortens diffusive flow paths) thereby making the VOCs more acceptable to remediation. For example, at the ARO Site, the process is expected to create new convective pathways in the formation (extend the ROI of existing VER recovery wells) resulting in increase permeability and shorten diffusive distances in the target treatment zone.

4. Pilot Study Objective

The objective of the pilot study is to evaluate the use of PF technology to enhance the performance of the existing VER system. This includes the creation of a network of radial fractures in the target treatment zone (e.g., 5 feet to 19 feet below grade surface (bgs) in two test areas.

The effectiveness of the PF enhancement program will be based upon the following criteria:

- Increased ROI of the existing recovery wells (e.g., \approx 5 feet to >15 feet),
- Improved intrinsic permeability of dense till soils within the pilot study area (e.g., increased air flow rates),
- Increased VOCs mass removal rates (e.g., 2 to 3 times), and
- Increase the distribution of VOCs in the vapor phase (i.e., percentage of individual compounds compared with baseline conditions).

5. Scope of Work

The scope of work for the PF pilot study consists of three major tasks, including baseline monitoring, the performance of the pneumatic fracturing pilot study and reporting of results. A more complete description of these tasks is provided within the following sections.

Prior to the performance of any field activities, ARCADIS will revise the site-specific Health & Safety Plan (HASP) in compliance with 29 CFR 1910.20 to reflect modifications to the project scope of work, and outline any additional hazards anticipated.

ARCADIS

Work Plan Remedial Enhancement via Pneumatic Fracturing

ARO Corporation Site
Cheektowaga, NY

5.1 Baseline Monitoring

ARCADIS will perform baseline monitoring prior to implementing this pilot study to confirm existing site conditions and system performance characteristics. Parameters to be evaluated will include groundwater elevation measurements and vacuum gauge readings in monitoring wells, measurement of airflow rates, groundwater flow rates, and collection of influent vapor and water samples to determine VOC mass removal rates and distribution of VOCs in the selected VER recovery wells RW-1 and RW-10.

Subsequent to the completion of baseline monitoring, ARCADIS will shut down the VER system to avoid upsets during the installation and development of the pneumatic fracturing well network.

5.2 Pneumatic Fracturing Pilot Study

Based upon a desktop evaluation of the Site data and use of the pneumatic fracturing model, ARCADIS proposes to install two fracture wells (FWs) in each of the two test plots. Fracture wells will be installed at a radial distance of approximately 12 feet and 18 feet from RW-1, and approximately 15 feet and 21 feet from RW-10, respectively.

RW-1 is located downgradient from the former loading dock source area, and was the site of the first VER pilot study. This area was selected because the VER pilot study results, although favorable, could not be duplicated in other areas of the site during full-scale system operation. Implementing PF in this area should also greatly increase the VOC mass removal rate, and provide a means to cost-effectively shorten the O&M period at this site.

The second pilot study area will be located near the former metals preparation source area (i.e., surrounding RW-10). This area was selected because the effectiveness of the VER system is currently limited (i.e., VER pilot study results were not duplicated) by the low permeability of soils in this area, and high VOC concentrations are currently measured in the groundwater. Performance of the pilot study in this area will also provide a clear point of comparison between locations with distinctly different subsurface characteristics.

Wells will be pneumatically fractured using a proprietary radial nozzle in two-foot lifts for a total of seven fracture zones per well, twenty-eight for all four PF wells. All PF

ARCADIS

Work Plan
Remedial Enhancement
via Pneumatic Fracturing
ARO Corporation Site
Cheektowaga, NY

wells will subsequently be developed to assure steady-state conditions within the subsurface.

Subsequent to the completion of pneumatic fracturing and well development activities, ARCADIS will restart the VER system and perform a subsequent round of monitoring to assess variations in system performance, mass removal rate and groundwater recovery. The following data will be recorded daily for a period of one week to assess changes as the system approaches steady-state operation:

- Groundwater elevations in system monitoring wells
- Induced vacuum at the liquid ring pump, existing VER extraction wells, fracture wells and fracture monitoring wells;
- Groundwater recovery rate
- Induced air flow rate
- VOC concentrations at the system exhaust (measured at the discharge from the vapor/liquid separator)

Figure 1 shows a schematic of a typical FW in each of the two pilot study areas. Figure 2 identifies the location of existing and proposed wells to be instrumented during the PF program.


5.3 Reporting

Upon completion of these tasks, ARCADIS will prepare a findings report summarizing the work performed and evaluating pre- and post-fracturing parameters. The report will include the system performance data sheets, summary data tables and figures depicting well installation logs, anticipated fracture cross sections and the anticipated extent of fracture zones based on vacuum influence readings detected during the pilot study.

6. Schedule

The proposed project schedule is shown on Figure 3. The task estimates assume that the fieldwork is not delayed due to weather, access, regulatory review or other unforeseen delays.





NOTES:

- 1) PRE-DRILL A 3.5"–3.75" ϕ PILOT HOLE WITH SOLID STEM AUGER
- 2) PRESS OR PUSH ON DRIVE POINT TO SET WELL DEPTH SHOWN ON DRAWING OR AS DIRECTED BY ARCADIS REPRESENTATIVE.
- 3) FINAL DEPTH OF WELLS WILL BE DETERMINED AT TIME OF INSTALLATION
- 4) 2' x 4" ϕ SUMP TO BE PRESSED 1'–2' BEYOND DEPTH OF AUGERED BOREHOLE



441 New Karner Rd., Suite 4
Albany, New York, 12205
Tel: 518/452-7825 Fax: 518/452-4398


**TYPICAL PNEUMATIC
FRACTURING WELL DETAIL**

ARO CORPORATION SITE
CHEEKTOWAGA, NEW YORK

PROJECT MANAGER T. CARIGNAN	DRAWING NUMBER G266N
CHECKED BY M. SANFORD	PROJECT NUMBER AY0002200006
DRAWN BY C9W/FJF	FIGURE NUMBER 1
DATE DRAWN 09-09-03	

NOTES:

1. SOURCE: RAY L. SONNENBERGER LAND SURVEYOR, 1997



NO.	DATE	REVISION DESCRIPTION	BY	CHKD.
-----	------	----------------------	----	-------




441 New Karner Rd., Suite 4
Albany, New York 12203
Tel: 518/482-7826 Fax: 518/482-4396

**SITE PLAN SHOWING
LOCATIONS OF PILOT
TEST AND LAYOUT OF
PNEUMATIC
FRACTURING WELLS**

ARO CORPORATION SITE
CHEEKTOWAGA, NEW YORK

PROJECT MANAGER M. SANFORD	DRAWING NUMBER G266M
CHECKED BY T. CARIGNAN	PROJECT NUMBER AY000220006
DRAWN BY TAD/TJF	FIGURE NUMBER 2
DATE DRAWN 9-02-03	

Remedial Enhancements via Pneumatic Fracturing Former ARO Corporation Site - Cheektowaga, New York Project Schedule



Project: PF Project Schedule Date: Thu 6/17/04	Task	■	Milestone	◆	External Tasks	■
	Split	Summary	▬	External Milestone	◆
	Progress	■	Project Summary	▬	Deadline	↓

Figure 3