10-73 Beach 21st Street, Far Rockaway, New York 11691

NOVA PROJECT NUMBER:

18-1079

DATED:

December 21, 2018

PREPARED FOR:

Langan

21 Penn Plaza 360 West 31st Street, 8th Floor New York, New York 10001

PREPARED BY:



NOVA GEOPHYSICAL SERVICES

SUBSURFACE MAPPING SOLUTIONS

56-01 Marathon Parkway #765, Douglaston, New York 11362 Ph. 347-556-7787 Fax. 718-261-1527 www.nova-gsi.com

December 21, 2018

Jennifer Armstrong
Senior Project Manager

Langan
21 Penn Plaza
360 West 31st Street, 8th Floor
New York, New York 10001
P: 212.479.5537 | E: jarmstrong@langan.com

Re: Geophysical Engineering Survey (GES) Report 10-73 Beach 21st Street,

Far Rockaway, New York 11691

Dear Ms. Armstrong,

Nova Geophysical Services (NOVA) is pleased to provide the findings of the geophysical engineering survey (GES) at the above referenced project site: 10-73 Beach 21st Street, Far Rockaway, New York 11691 (the "Site").

INTRODUCTION TO GEOPHYSICAL ENGINEERING SURVEY (GES)

NOVA performed a geophysical engineering survey (GES) consisting of a Ground Penetrating Radar (GPR) and Electromagnetic (EM) survey at the site. The purpose of this survey is to locate and identify utilities, underground storage tanks and other substructures as well as to clear abd mark proposed boring locations on December 12th, 2018.

The equipment selected for this investigation was a Sensors and Software Noggin 250 MHz ground penetrating radar (GPR) with a shielded antenna and a Radio Detection RD7100 Electromagnetic utility locator.

A GPR system consists of a radar control unit, control cable, and transducer (antenna). The control unit transmits a trigger pulse at a normal repetition rate of 250 MHz. The trigger pulse is sent to the transmitter electronics in the transduce via the control cable. The transmitter electronics amplify the trigger pulse into bipolar pulses that are radiated to the surface. The transformed pulses vary in shape and frequency according to the transducer used. In the subsurface, variations of the signal occur at boundaries where there is a dielectric contrast (void,

OER Jump Start Site 10-73 Beach 21st Street,

Far Rockaway, New York 11691

steel, soil type, etc.). Signal reflections travel back to the control unit and are represented as color graphic images for interpolation.

A typical electromagnetic (EM) utility locating system consists of a transmitter unit and a receiver unit. The receiver unit can be used independently of the transmitter unit in order to detect utility lines with an inherent EM signature (electric utility lines, water lines, etc.). If needed a current at a specific frequency can also be placed on a utility that is being located. This can be done via the transmitter unit by either direct connection or induction via an EM field varying at specific frequency. The receiver unit is then set to the selected frequency and the electromagnetic field created by the current running through the utility can be located allowing the utility to be marked.

GEOPHYSICAL METHODS


The project site was screened using GPR to search the specified area and inspected for reflections, which could be indicative of substructures and utilities within the subsurface. An EM utility locator was used to help determine the locations of utilities within the survey area.

EM data was collected and interpreted on site and suspected utilities marked as needed. GPR data profiles were collected for the areas of the Site specified by the client and processed as specified below.

DATA PROCESSING


In order to improve the quality of the results and to better identify anomalies NOVA processed the collected data. The processing work flow is briefly described in this section.

Step 1. Import Raw RAMAC data to standard processing format




Far Rockaway, New York 11691


Step 2. Remove instrument noise (dewow)




Step 3. Correct for attenuation losses (energy decay function)



Step 4. Remove static from bottom of profile (time cut)



Step 5. Mute horizontal ringing/noise (subtracting average)



The above example shows the significance of data processing. The last image (step 5) has higher resolution than the starting image (raw data – step 1) and represents the subsurface anomalies much more accurately.

OER Jump Start Site 10-73 Beach 21st Street,

Far Rockaway, New York 11691

PHYSICAL SETTINGS

NOVA observed the following physical conditions at the time of the survey.

Weather: Sunny

Temperature: 35° F

Surface: Asphalt, Concrete, Gravel, Vegetation

Geophysical Noise Level: The geophysical noise at the site was high due to being located in an

urban environment. Portions of the site were also covered by cars at the time of the survey.

RESULTS

The results of the geophysical engineering survey (GES) identified the following at the project

site:

Anomalies resembling potential subsurface utilities (such as electric, telecommunications,

and drainage) were identified during the GES. The approximate locations are shown in

the survey plan.

No large geophysical anomalies resembling underground storage tanks (USTs) were

identified in the GES.

All detected subsurface anomalies were marked in the onsite mark out.

All cleared boring locations were marked in the onsite mark out.

OER Jump Start Site 10-73 Beach 21st Street, Far Rockaway, New York 11691

If you have any questions, please do not hesitate to contact the undersigned.

Sincerely,

NOVA Geophysical Services

Levent Eskicakit, P.G., E.P.

Sweet Chil


Project Engineer

Attachments:

Location Map

Survey Plan

Geophysical Images



NOVA Geophysical Services

Subsurface Mapping Solutions 56-01 Marathon Parkway, # 765 Douglaston, New York 11362 Phone (347) 556-7787 * Fax (718) 261-1527 www.nova-gsi.com

Location Map

SITE: **OER Jump Start Site** 10-73 Beach 21st Street,

Far Rockaway, New York 11691

CLIENT: Langan

DATE: December 12th, 2018

AUTH: Chris Steinley **LEGEND**



NOVA Geophysical Services

Subsurface Mapping Solutions 56-01 Marathon Parkway, # 765 Douglaston, New York 11362 Phone (347) 556-7787 * Fax (718) 261-1527 www.nova-gsi.com

SURVEY PLAN

SITE: **OER Jump Start Site**

10-73 Beach 21st Street, Far Rockaway, New York 11691

CLIENT: Langan

DATE: December 12th, 2018

AUTH: Chris Steinley

LEGEND

Survey Area

Drainage

Electric

Communications

Overhead Light

Parking Meter

