



SDS # : 082077

CLERANE 180

Date of the previous version: 2016-11-22

Revision Date: 2017-06-30

Version 2

**DANGER****Hazard Statements**

Combustible liquid
May be fatal if swallowed and enters airways

Precautionary Statements - Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Wear protective gloves/protective clothing/eye protection/face protection

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place

Precautionary Statements - Disposal

Dispose of contents/ container to an approved waste disposal plant

Unknown Acute Toxicity

No information available

Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

Other information**Physical-Chemical Properties**

Vapors may form explosive mixtures with air. Vapours are heavier than air and may spread near ground level to sources of ignition .

Properties Affecting Health

Repeated exposure may cause skin dryness or cracking. Prolonged skin contact may defat the skin and produce dermatitis.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Substance****Chemical nature**

A complex and variable combination of paraffinic and cyclic hydrocarbons having a carbon number range predominantly of C10 to C13 and boiling in the range of approximately 160°C



SDS # : 082077

CLERANE 180

Date of the previous version: 2016-11-22

Revision Date: 2017-06-30

Version 2

to 245°C.

Chemical Name	CAS-No	Weight %
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	^	100

Additional information

Related CAS number: 64742-48-9

4. FIRST AID MEASURES**First aid measures for different exposure routes**

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.
Skin contact	Remove contaminated clothing and shoes. Wash off with soap and water.
Inhalation	In case of exposure to intense concentrations of vapours, fumes or spray, transport the person away from the contaminated zone, keep warm and allow to rest.
Ingestion	Do not ingest. If swallowed then seek immediate medical assistance. Risk of product entering the lungs on vomiting after ingestion. In this case, the casualty should be sent immediately to hospital.
Protection of First-aiders	Use personal protective equipment.

Most important symptoms/effects, acute and delayed

Skin contact	Prolonged contact may cause redness and irritation.
Eye contact	Burning feeling and temporary redness.
Inhalation	The inhalation of vapours or aerosols may be irritating for the respiratory tract and for mucous membranes, Eye Irritation. Vapors inhaled in strong concentration have a narcotic effect on the central nervous system.
Ingestion	If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious pulmonary lesions (medical survey during 48 hours). Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Abdominal pain. May cause central nervous system depression.
Symptoms	Redness.



SDS # : 082077

CLERANE 180

Date of the previous version: 2016-11-22

Revision Date: 2017-06-30

Version 2

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media** Foam. Dry powder. Carbon dioxide (CO₂).**Uniform Fire Code** Combustible Liquid: III-A**Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire.**Special Hazard** Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.**Explosion Data****Sensitivity to Mechanical Impact** None.**Sensitivity to Static Discharge** May be ignited by friction, heat, sparks or flames.**Protective Equipment and Precautions for Firefighters** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures****General Information** Use personal protective equipment.
Evacuate non-essential personnel.
Ensure adequate ventilation, especially in confined areas.
ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
Do not touch or walk through spilled material.**Other information** Remove all sources of ignition.
Stop all work that requires a naked flame, stop all vehicles, stop all machines and equipment that may cause sparks or flames.**Environmental precautions****General Information** Prevent further leakage or spillage if safe to do so. Dike to collect large liquid spills. The product should not be allowed to enter drains, water courses or the soil. Local authorities should be advised if significant spillages cannot be contained. See Section 12 for additional Ecological Information.**Methods and material for containment and cleaning up****Methods for cleaning up** Use non-sparking handtools and explosionproof electrical equipment.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).



SDS # : 082077

CLERANE 180

Date of the previous version: 2016-11-22

Revision Date: 2017-06-30

Version 2

Following product recovery, flush area with water.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist.
Avoid contact with skin, eyes and clothing.

Technical measures

Ensure adequate ventilation.
Do not spray at high pressure (> 3 bar) .
WHILE MOVING THE PRODUCT: To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Do not allow splash loading and ensure that the product is poured slowly, particularly at the beginning of the operation.

Prevention of fire and explosion

OPERATE ONLY ON COLD AND DEGASSED TANKS IN VENTILATED PREMISES (TO AVOID RISK OF EXPLOSION).
Handle away from any source of ignition (open flame and sparks) and heat (hot manifolds or casings). Do not smoke.
Use explosionproof electrical equipment. Take precautionary measures against static discharges. Do not use compressed air for filling, discharging or handling.
Design installations (machinery and equipment) to prevent burning product from spreading (tanks, retention systems, interceptors (traps) in drainage systems).

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke.
Regular cleaning of equipment, work area and clothing is recommended. Do not dry hands with rags that have been contaminated with product. Do not use abrasives, solvents or fuels.
Wash hands before breaks and at the end of workday.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts.
Storage installations should be designed with adequate bunds so as to prevent ground or water pollution in case of leaks or spills. Use explosionproof electrical equipment.
Keep in a bunded area. Keep in a dry, cool and well-ventilated place.
Keep away from open flames, hot surfaces and sources of ignition. Ground/bond containers, tanks and transfer/receiving equipment. Store at room temperature.
Keep containers tightly closed and properly labelled.

Packaging material

Use material compatible with: Keep only in the original container or in a suitable container for this kind of product. steel . Stainless steel. Recommended materials for containers, or container linings use mild steel, stainless steel.

Materials to Avoid

Strong acids. Oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters



SDS # : 082077

CLERANE 180

Date of the previous version: 2016-11-22

Revision Date: 2017-06-30

Version 2

Exposure limits Ingredients with workplace control parameters

Advisory OEL CEFIC-HSPA : 1200 mg/m³

Exposure controls

Engineering Measures When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment. Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

General Information Protective engineering solutions should be implemented and in use before personal protective equipment is considered. These recommendations apply to the product as supplied. If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers.

Eye/face protection If splashes are likely to occur, wear: Safety glasses with side-shields.

Skin and body protection Wear suitable protective clothing. Protective shoes or boots.

Hand Protection Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended. Do not dry hands with rags that have been contaminated with product. Do not use abrasives, solvents or fuels. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Color	colorless
Physical State @20°C	liquid
Odor	Petroleum solvent
Odor Threshold	No information available



SDS # : 082077

CLERANE 180

Date of the previous version: 2016-11-22

Revision Date: 2017-06-30

Version 2

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		Not applicable	
Melting point/range		No information available	
Boiling point/boiling range	175 - 235 °C 347 - 455 °F		EN ISO 3405 EN ISO 3405
Flash point	> 63 °C > 145 °F		ASTM D 93 ASTM D 93.
Evaporation rate	191	EtEt=1	DIN 53170
Flammability Limits in Air			
upper	7 %		
Lower	0.6 %		
Vapor Pressure	0.38 hPa	@ 20 °C	
Vapor density		No information available	
Relative density	0.80	No information available	
Density	800 kg/m ³	@ 15 °C	ISO 12185
Water solubility		Substance is a UVCB. Standard tests for this endpoint are not appropriate	
Solubility in other solvents		Soluble in many common organic solvents	
logPow		Not applicable	
Autoignition temperature	> 230 °C	This temperature may be significantly lower under particular conditions (slow oxidation on finely divided materials...)	ASTM E 659
Decomposition temperature	> 446 °F	No information available	ASTM E 659
Viscosity, kinematic	< 20.5 mm ² /s	@ 40 °C	ASTM D 445
Explosive properties	Not considered explosive based on chemical structure and oxygen balance considerations		
Oxidizing Properties	This product is not considered oxidising based on chemical structure considerations		
Possibility of hazardous reactions	None under normal processing		
<u>Other information</u>			
Surface tension	0.0249 N/m	@ 25 °C	EN 14370
Freezing Point		No information available	

10. STABILITY AND REACTIVITY

<u>Reactivity</u>	None under normal processing.
<u>Chemical stability</u>	Stable under recommended storage conditions.
<u>Possibility of hazardous reactions</u>	None under normal processing.
<u>Conditions to avoid</u>	Heat, flames and sparks. Take precautionary measures against static discharges.



SDS # : 082077

CLERANE 180

Date of the previous version: 2016-11-22

Revision Date: 2017-06-30

Version 2

Incompatible materials Strong acids. Oxidizing agents.**Hazardous Decomposition Products** Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Principle Routes of Exposure	Inhalation, Ingestion, Eye contact, Skin contact.
Symptoms	Redness.
Skin contact	Prolonged contact may cause redness and irritation.
Eye contact	Burning feeling and temporary redness.
Inhalation	The inhalation of vapours or aerosols may be irritating for the respiratory tract and for mucous membranes, Eye Irritation. Vapors inhaled in strong concentration have a narcotic effect on the central nervous system.
Ingestion	If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious pulmonary lesions (medical survey during 48 hours). Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Abdominal pain. May cause central nervous system depression.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Acute toxicity - Product Information**

Product Information	Product does not present an acute toxicity hazard based on known or supplied information.
Oral ATEmix (oral)	Not classified. 5001 mg/kg
Dermal ATEmix (dermal)	Not classified. 5001 mg/kg
Inhalation	Not classified

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	LD50 > 5000 mg/kg bw (rat - OECD 401)	LD50 (24h) > 2000 mg/kg bw (rat - OECD 402)	LC50(8h) > 5000 mg/m ³ (Rat - Vapours - OECD 403)



SDS # : 082077

CLERANE 180

Date of the previous version: 2016-11-22

Revision Date: 2017-06-30

Version 2

^			
---	--	--	--

Skin corrosion/irritation	Not classified.
Serious eye damage/eye irritation	Not classified.
Sensitization	Not classified as a sensitizer.
Carcinogenicity	This product is not classified carcinogenic.

Mutagenicity	This product is not classified as mutagenic.
Reproductive toxicity	This product does not present any known or suspected reproductive hazards.
Developmental Toxicity	Not classified.
STOT - single exposure	None under normal use conditions.
STOT - repeated exposure	None under normal use conditions.
Other adverse effects	Frequent or prolonged skin contact destroys the lipoacid cutaneous layer and may cause dermatitis.
Aspiration hazard	May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Acute aquatic toxicity - Product Information**

Not applicable

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics ^	ErL50 (72h) > 1000 mg/l (Pseudokirchneriella subcapitata - OECD 201) EbL50 (72h) > 1000 mg/l (Pseudokirchneriella subcapitata - OECD 201)	LL50 (96h) > 1000 mg/l (Oncorhynchus mykiss - OECD 203)	EL50 (48h) > 1000 mg/l (Daphnia magna - OECD 202)	-

Chronic aquatic toxicity - Product Information

Not applicable

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics ^	NOELR (72h) = 1000 mg/l (Pseudokirchneriella subcapitata - biomass - OECD 201) NOELR (72h) = 1000 mg/l (Pseudokirchneriella subcapitata - growth rate - OECD 201)	NOELR (21d) = 0,18 mg/l (Daphnia magna - QSAR Petrotox)	NOELR (28d) = 0,10 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	



SDS # : 082077

CLERANE 180

Date of the previous version: 2016-11-22

Revision Date: 2017-06-30

Version 2

Effects on terrestrial organisms No information available.**Persistence and degradability****General Information** Readily biodegradable (80 % after 28 days).

Biodegradation							
Type	Method	Sampling time	Specific effects	Values	Unit	Biodegradability	Source
	OECD 301F	28 days		80	%	Readily biodegradable	

Bioaccumulative potential**Product Information** Measured experimental data on hydrocarbon UVCB substances are not meaningful, since each of the constituents is likely to behave differently.**logPow** Not applicable**Component Information** Not applicable.**Mobility****Soil** Given its physical and chemical characteristics, the product has no soil mobility.**Air** The product evaporates readily**Water** The product is insoluble and floats on water**Other adverse effects****General Information** No information available**13. DISPOSAL CONSIDERATIONS****Waste treatment****Waste Disposal Methods** Dispose of in accordance with local regulations.**Contaminated packaging** Empty containers may contain flammable or explosive vapors. Empty containers should be taken to an approved waste handling site for recycling or disposal.**14. TRANSPORT INFORMATION****Note** **DOT classification for bulk shipments only:** This material has been determined to be NOT COMBUSTIBLE according to 49 CFR 173.120; it does not sustain combustion by



SDS # : 082077

CLERANE 180

Date of the previous version: 2016-11-22

Revision Date: 2017-06-30

Version 2

	ASTM D4206
<u>DOT</u>	Not regulated
<u>TDG</u>	Not regulated
<u>MEX</u>	Not regulated
<u>ICAO/IATA</u>	Not regulated
<u>IMDG/IMO</u>	Not regulated
<u>ADR/RID</u>	Not regulated
<u>ADN</u>	
UN/ID No	UN9003
Proper shipping name	SUBSTANCES WITH A FLASH-POINT ABOVE 60°C AND NOT MORE THAN 100°C
Hazard class	9
Description	UN9003, SUBSTANCES WITH A FLASH-POINT ABOVE 60°C AND NOT MORE THAN 100°C, 9

15. REGULATORY INFORMATION

REACH registration No 01-2119457273-39
Related CAS number 64742-48-9

International Inventories The substance is listed or exempted from listing in the following inventories:
 Europe (EINECS/ELINCS/NLP)
 U.S.A. (TSCA)
 Canada (DSL/NDSL)
 Australia (AICS)
 Korea (KECL)
 China (IECSC)
 Japan (ENCS)
 Philippines (PICCS)
 New Zealand (NZIoC)
 Taiwan (TCSI)

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No



SDS # : 082077

CLERANE 180

Date of the previous version: 2016-11-22

Revision Date: 2017-06-30

Version 2

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

No information available

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 1	Flammability 2	Instability 0	Physical and chemical hazards -
<u>HMIS</u>	Health Hazard 1	Flammability 2	Physical Hazard 0	Personal protection X

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2017-06-30

Revision Note (M)SDS sections updated: 14

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one



SDS # : 082077

CLERANE 180

Date of the previous version: 2016-11-22

Revision Date: 2017-06-30

Version 2

half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

Legend

Section 8

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH - National Institute for Occupational Safety and Health

TLV - Threshold Limit Values

PEL - Permissible Exposure Limits

IDHL - Immediately Dangerous to Life or Health concentrations

TWA - Time Weight Average

STEL - Short Term Exposure Limits

S* - Skin notation

TSCA - Toxic Substance Control Act

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet