




REALSTAR, U.S.A.

Executive Offices
1900 Meredith Park Drive
McDonough, GA 30253
Phone: (404) 361-7775
Fax: (404) 361-2454

May 9, 2018

Attention: New York State Department of Environmental Conservation
Division of Air Resources, Bureau of Stationary Sources
Attn: Eric L. Wade, Chief, Enforcement Section
625 Broadway
Albany, New York 12233-3254



Re: Statement of Compliance for REALSTAR machine models RS215 Ultra Diamond and RS135 Ultra Diamond

This letter is to confirm that each of the following uncertified perchloroethylene (perc) dry cleaning machines models is identical to a model previously certified by the New York State Department of Environmental Conservation (NYSDEC), other than for name change and cosmetic differences. These REALSTAR uncertified machine models are identical in design and construction to the NYSDEC certified models listed below:

OLD:

REALSTAR T-280 Capacity 35 lbs. Carbon regeneration Every 50 loads or once a week, whichever comes first.
*See Realstar's 02/2001 manual for Realstar machines had the R22 HIGH working pressure as 18-20 bar; and the LOW gauge pressure as "4.5 to 5 bar during drying, 3.5 to 4 bar during cooldown and even lower values of 1-3 bar during the deodorization stage."

NEW:

REALSTAR RS215 Ultra Diamond Capacity 35 lbs. Carbon regeneration Every 50 loads or once a week, whichever comes first.
*See Realstar's manual for R404a or R407-C FREON HIGH working pressure as 18-20 bar; and the LOW gauge pressure as "4.5 to 5 bar during drying, 3.5 to 4 bar during cooldown and even lower values of 1-3 bar during the deodorization stage."

OLD:

REALSTAR M280 Capacity 35 lbs. Carbon regeneration Every 50 loads or once a week, whichever comes first.
*See Realstar's 02/2001 manual for Realstar machines had the R22 HIGH working pressure as 18-20 bar; and the LOW gauge pressure as "4.5 to 5 bar during drying, 3.5 to 4 bar during cooldown and even lower values of 1-3 bar during the deodorization stage"

NEW:

REALSTAR RS315 Ultra Diamond Capacity 35 lbs. Carbon regeneration Every 50 loads or once a week, whichever comes first.
*See Realstar's manual for R404a or R407-C FREON HIGH working pressure as 18-20 bar; and the LOW gauge pressure as "4.5 to 5 bar during drying, 3.5 to 4 bar during cooldown and even lower values of 1-3 bar during the deodorization stage."

Sincerely,


Victor Williams
Vice President

